



ABRAMS®
PREMIUM STEEL

PRECISION

IN

TOOL STEEL

HIGH SPEED STEEL

STAINLESS STEEL, corrosion resistant

STAINLESS STEEL, acid resistant

HEAT-TREATABLE STEEL

CASE HARDENING STEEL

NITRIDING STEEL

70 STEEL GRADES IN 33.895 DIMENSIONS

EX WORKS FROM OSNABRÜCK / GERMANY

DELIVERY IN 3-5 WORKING DAYS (SUBJECT TO AVAILABILITY)


WITHOUT MINIMUM ORDER VALUE OR QUANTITY

FROM EUROPE'S LARGEST RANGE OF SEMI-FINISHED PRODUCTS

SPECIAL CUSTOM DIMENSIONS ON REQUEST – SAWN – MILLED – GROUND

CONSISTENTLY DYNAMIC !

... that is ABRAMS®.



Yours sincerely,


Dr. Jürgen Abrams
Managing Director

VERSATILE !

ABRAMS®
PREMIUM STEEL

PREMIUM STEEL


- 70 steel grades in 33.895 dimensions
- **PRECISION FLAT STEEL** with / without machining allowance
- **€co-Präz**® - Standardized precision blanks
- **Hart-Präz**® - Hardened precision plates
- **PRECISION ROUND STEEL**
with / without machining allowance
- **ROUND STEEL**
- **EROSION BLOCK** annealed / hardened
- WITHOUT MINIMUM ORDER VALUE OR QUANTITY
- SPECIAL CUSTOM DIMENSIONS SAWN - MILLED - GROUND



ABRAMS®
PREMIUM ALUMINIUM

PREMIUM-ALUMINIUM

- 8 alloys in 4.307 dimensions
- In 3 specification
 - **ALU-PRÄZ**®
 - **PRECISION ROUND ALUMINIUM**
 - **ROUND ALUMINIUM**



ABRAMS®
PREMIUM TOOLS

PREMIUM-UNIVERSAL-TAPS

- 96 items in 6 categories
- Metric standard thread
 - For clearance holes
 - For blind holes
 - **M-DIN 371-Form B**
 - **M-DIN 371-Form C**
 - **M-DIN 376-Form B**
 - **M-DIN 376-Form C**
- Metric fine thread
 - For clearance holes
 - For blind holes
 - **MF-DIN 374-Form B**
 - **MF-DIN 374-Form C**



THE ABRAMS STEEL GUIDE® !

Our patented application can be downloaded onto your smartphone (iPhone/ android phones) or tablet (iPad/android tablets), as well as being available as a free web browser on your PC (see www.steel-guide.eu). The following graphics have been taken from the iPhone version.

ABRAMS®
PREMIUM STEEL

1.2990 mod.	1.2714+QT L6+QT	1.2361	1.2312 P20+S		1.4841 314	1.4122	1.7227 4140
1.2842 O2	1.2709 ERS	1.2360 ~ Chipper	1.2311 P20	1.2083 ESU 420 ESR	1.4571 316Ti	1.4112 440B	1.7225 4140
1.2510 O1	1.2550 S1	1.2358	1.2294	1.2080 mod. D3 mod.	1.4418 S 165 M	1.4104 430F	1.7225+QT 4140+QT
1.2826	1.2436 D6	1.2344 H13	1.2210 L2	1.2067 L3 / L1	1.4404 316L	1.4057 431	1.7147 5120
1.2767 6F7	1.2379 D2	1.2344 ESU H13 ESR	1.2162	1.1730 1045	HSS 1.3343 M2	1.4401 316	1.7131 5115
1.2767 ESU 6F7 ESR	1.2367	1.2343 H11	1.2099	1.0570 (St 52-3)	HSS PM 30 PM 30	1.4305 303	1.6587 4820
1.2738 P20+Ni L6	1.2365 H10	1.2343 ESU H11 ESR	1.2085 420FM	Toolox 33	HSS PM 23 M3	1.4301 304	1.6582 4337
1.2714 L6	1.2363 A2	1.2316	1.2083 420	Toolox 44	HSS PM 4 M4	1.4125 440C	1.6580 4340

TWO POSSIBLE WAYS TO START

E.g. you need TOOL STEEL for a stamping tool.

STEP 1 A

You know the technical requirements and you are looking for the suitable steel grade.

STEP 1 B

Choose a steel grade you know and usually work with.

ABRAMS®
PREMIUM STEEL

1.2990 mod.	1.2714+QT L6+QT	1.2361	1.2312 P20+S		1.4841 314	1.4122	1.7227 4140
1.2842 O2	1.2709 ERS	1.2360 ~ Chipper	1.2311 P20	1.2083 ESU 420 ESR	1.4571 316Ti	1.4112 440B	1.7225 4140
1.2510 O1	1.2550 S1	1.2358	1.2294	1.2080 mod. D3 mod.	1.4418 S 165 M	1.4104 430F	1.7225+QT 4140+QT
1.2826	1.2436 D6	1.2344 H13	1.2210 L2	1.2067 L3 / L1	1.4404 316L	1.4057 431	1.7147 5120
1.2767 6F7	1.2379 D2	1.2344 ESU H13 ESR	1.2162	1.1730 1045	HSS 1.3343 M2	1.4401 316	1.7131 5115
1.2767 ESU 6F7 ESR	1.2367	1.2343 H11	1.2099	1.0570 (St 52-3)	HSS PM 30 PM 30	1.4305 303	1.6587 4820
1.2738 P20+Ni L6	1.2365 H10	1.2343 ESU H11 ESR	1.2085 420FM	Toolox 33	HSS PM 23 M3	1.4301 304	1.6582 4337
1.2714 L6	1.2363 A2	1.2316	1.2083 420	Toolox 44	HSS PM 4 M4	1.4125 440C	1.6580 4340

Steel guide

Search

Properties

Specifications

Glossary

ABRAMS®
PREMIUM STEEL

1.2990 mod.	1.2714+QT L6+QT	1.2361	1.2312 P20+S		1.4841 314	1.4122	1.7227 4140
1.2842 O2	1.2709 ERS	1.2360 ~ Chipper	1.2311 P20	1.2083 ESU 420 ESR	1.4571 316Ti	1.4112 440B	1.7225 4140
1.2510 O1	1.2550 S1	1.2358	1.2294	1.2080 mod. D3 mod.	1.4418 S 165 M	1.4104 430F	1.7225+QT 4140+QT
1.2826	1.2436 D6	1.2344 H13	1.2210 L2	1.2067 L3 / L1	1.4404 316L	1.4057 431	1.7147 5120
1.2767 6F7	1.2379 D2	1.2344 ESU H13 ESR	1.2162	1.1730 1045	HSS 1.3343 M2	1.4401 316	1.7131 5115
1.2767 ESU 6F7 ESR	1.2367	1.2343 H11	1.2099	1.0570 (St 52-3)	HSS PM 30 PM 30	1.4305 303	1.6587 4820
1.2738 P20+Ni L6	1.2365 H10	1.2343 ESU H11 ESR	1.2085 420FM	Toolox 33	HSS PM 23 M3	1.4301 304	1.6582 4337
1.2714 L6	1.2363 A2	1.2316	1.2083 420	Toolox 44	HSS PM 4 M4	1.4125 440C	1.6580 4340

BS BD 3 mod.

BS BD 3 mod.
~X210Cr12

Max. hardness (deliv. condition) 250 HB
Max. working hardness 62 HRC

Your desired steel grade will be shown with first indicative traits.

STEP 2 A

For example, click to open the property view.

ABRAMS®
PREMIUM STEEL

1.2990 mod.	1.2714 QT L6+QT	1.2361 P20+5	1.2312 P20+5	1.4041 314	1.4102 316	1.2727 4140
1.2842 O2	1.2709 ERS	1.2360 P20 - Chipper	1.2311 P20	1.2083 ESR 420 ESR	1.4071 316Ti	1.4102 316
1.2510 O1	1.2550 S1	1.2358 1.2394	1.2380 mod. 32 mod.	1.4418 316L	1.4104 316L	1.2725 QT 4140 QT
1.2826 1.2436 D6	1.2344 H13	1.2310 L2	1.2067 L2 / L1	1.4024 316L	1.4027 316L	1.2747 515
1.2767 6F7	1.2379 O2	1.2344 ESR H13 ESR	1.2162 1.1730 1.1730 302	1.4041 316	1.4041 316	1.2711 515
1.2767 ESR 6F7 ESR	1.2367 H11	1.2343 1.2099 1.0070 1.4050 1.4050 303	1.4051 303	1.4051 303	1.4051 303	1.4051 303
1.2738 P20+H1	1.2365 H10	1.2343 ESR H11 ESR 402PM	1.2085 1.4081 1.4081 402	1.4081 402	1.4081 402	1.4081 402
1.2714 L6	1.2363 A2	1.2316 1.2083 1.2083 402	1.4083 402	1.4083 402	1.4083 402	1.4083 402

Properties

- ☒ Tensile strength (deliv... 810 N/mm²
- ☐ Working hardness
- ☒ Working temperature 200 °C
- ☐ Machinability
- ☐ Toughness
- ☒ Wear resistance ★★★★★
- ☒ Corrosion resistance ★★★★★

Choose the most important technical properties – in any desired combination.

STEP 3 A

Click to choose each of the properties to optimise them.

ABRAMS®
PREMIUM STEEL

1.2990 mod.	1.2714 QT L6+QT	1.2361 P20+5	1.2312 P20+5	1.4041 314	1.4102 316	1.2727 4140
1.2842 O2	1.2709 ERS	1.2360 P20 - Chipper	1.2311 P20	1.2083 ESR 420 ESR	1.4071 316Ti	1.4102 316
1.2510 O1	1.2550 S1	1.2358 1.2394	1.2380 mod. 32 mod.	1.4418 316L	1.4104 316L	1.2725 QT 4140 QT
1.2826 1.2436 D6	1.2344 H13	1.2310 L2	1.2067 L2 / L1	1.4024 316L	1.4027 316L	1.2747 515
1.2767 6F7	1.2379 O2	1.2344 ESR H13 ESR	1.2162 1.1730 1.1730 302	1.4041 316	1.4041 316	1.2711 515
1.2767 ESR 6F7 ESR	1.2367 H11	1.2343 1.2099 1.0070 1.4050 1.4050 303	1.4051 303	1.4051 303	1.4051 303	1.4051 303
1.2738 P20+H1	1.2365 H10	1.2343 ESR H11 ESR 402PM	1.2085 1.4081 1.4081 402	1.4081 402	1.4081 402	1.4081 402
1.2714 L6	1.2363 A2	1.2316 1.2083 1.2083 402	1.4083 402	1.4083 402	1.4083 402	1.4083 402

Wear resistance

Wear resistance: ★★★★★

less important ————— very important

Here you can optimise any property, such as wear resistance – e.g. if it is less important or very important for your stamping tool. You immediately get the steel grade you need.

STEP 2 B

Click to get the detailed view.

ABRAMS®
PREMIUM STEEL

×

1.8550

1.8519

1.7227 4140

1.7225 4140

1.7225+QT 4140+QT

1.7147 5120

1.7131 5115

1.6587 4820

1.6582 4337

PREMIUM 1.2080 mod.

Properties of this steel grade

Chemical composition of this steel grade

Specifications of this steel grade

Alternatives to this steel grade

ABRAMS online-Shop

Here you have all the details of the chosen steel grade: technical properties, chemical composition and specifications. Sea ch for alternatives and get direct access to our online shop.

STEP 3 B

Here we have chosen the function "alternatives to the grade AISI / SAE D3 mod".

ABRAMS®
PREMIUM STEEL

1.2990 mod.	1.2714 QT L6+QT	1.2361 P20+5	1.2312 P20+5	1.4041 314	1.4102 316	1.2727 4140
1.2842 O2	1.2709 ERS	1.2360 P20 - Chipper	1.2311 P20	1.2083 ESR 420 ESR	1.4071 316Ti	1.4102 316
1.2510 O1	1.2550 S1	1.2358 1.2394	1.2380 mod. 32 mod.	1.4418 316L	1.4104 316L	1.2725 QT 4140 QT
1.2826 1.2436 D6	1.2344 H13	1.2310 L2	1.2067 L2 / L1	1.4024 316L	1.4027 316L	1.2747 515
1.2767 6F7	1.2379 O2	1.2344 ESR H13 ESR	1.2162 1.1730 1.1730 302	1.4041 316	1.4041 316	1.2711 515
1.2767 ESR 6F7 ESR	1.2367 H11	1.2343 1.2099 1.0070 1.4050 1.4050 303	1.4051 303	1.4051 303	1.4051 303	1.4051 303
1.2738 P20+H1	1.2365 H10	1.2343 ESR H11 ESR 402PM	1.2085 1.4081 1.4081 402	1.4081 402	1.4081 402	1.4081 402
1.2714 L6	1.2363 A2	1.2316 1.2083 1.2083 402	1.4083 402	1.4083 402	1.4083 402	1.4083 402

Properties

- ☒ Tensile strength (deliv... 850 N/mm²
- ☒ Working hardness 62 HRC
- ☒ Working temperature 200 °C
- ☒ Machinability ★★★★★
- ☒ Toughness ★★★★★
- ☒ Wear resistance ★★★★★
- ☒ Corrosion resistance ★★★★★

As a result, a highlighted list of steel grades appears with similar or possibly better properties than AISI / SAE D3 mod. You can adjust or delete single properties, thus enabling you to find the ideal steel grade for your stamping tool.

PRODUCTION + STOCK !

ABRAMS PREMIUM STEEL® is a licensed distributor for many European industrial enterprises.

THERE ARE 3 GOOD REASONS FOR THIS:



① FLEXIBILITY

because we produce for you
on site in Osnabrück/Germany.



② SHORT DELIVERY TIMES

because we have large storage capabilities
of raw materials and precision steel.

PREMIUM QUALITY RIGHT DOWN TO THE FINEST DETAIL !



③ PREMIUM QUALITY

because we use certified Mass Spectrometry (high-precision photomultiplier) and hardening testing technologies.

SPECIFICATIONS !

Our delivery program contains 33.955 different specifications /standard dimensions.

Any dimension is available in different **heights**, **widths** and **lengths**. On request – according to your needs!



Precision flat steel without machining allowance [PFS] acc. to DIN 59350

For example: 100,0 x 20,0 x 1.000 mm

- **W** ground / milled, tol. +0,2 /-0 mm
- **T** coplanar ground, tol. +0,05 /-0 mm
- **L** milled / sawn, tol. +35 /-0 mm
- Exception: **PREMIUM 1.1730 – AISI / SAE 1045**:
W +0,4 /-0 mm, **T** +0,25 /-0 mm, **T** +0,25 /-0 mm



Precision round steel without machining allowance [PRS]

- bright ground, tol.: Ø ISO h8, L +10 /-10 mm
- bright drawn / finely peeled / ground, tol.: Ø ISO h9, L +10 /-10 mm
- bright finely peeled, tol.: Ø ISO h11, L +10 /-10 mm



Precision flat steel with machining allowance [PRS/BA]

For example: 100,3 x 20,3 x 1.000 mm

- **W** ground / milled, tol. +0,4 /-0 mm
- **T** coplanar ground / finely milled, tol. +0,4 /-0 mm
- **L** milled / sawn, tol. +35 /-0 mm



Precision round steel with machining allowance [PRS/BA]

- peeled / rough-turned, tol.: Ø +tol. /-0 mm, L +tol. /-0 mm
- **Exception PREMIUM 1.3343 – AISI / SAE M2**:
L 1.000 mm, tol. L +10 /-10 mm
- **Particularity: PREMIUM 1.2826 – AISI / SAE 1.2826**,
PREMIUM 1.2360 – AISI / SAE –Chipper,
PREMIUM 1.2067 – AISI / SAE L3:
Ø are metric full values (for example 30,0 mm), therefore there is no basic machining allowance (for example 30,5 mm)



4co-Präz® [4co]

For example: 103 x 20,3 x 500 mm

- **W** sawn/ black, tol. +3 /-0 mm
- **T** finely milled, tol. +0,4/-0 mm
- **L** sawn/ black, tol. +15 /-0 mm



Round steel [RS]

- black, tol.: Ø +1 /-1 mm (aspired), L +tol. /-0 mm



Hart-Präz® [Hart]

For example: 250 x 10,2 x 500 mm

- **W** sawn/black, tol. +10/-0 mm
- **T** coplanar ground, Tol. +0,2/-0 mm
- **L** sawn/black, tol. +10/-0 mm

Planeness: +0,2/-0 mm of the entire surface (aspired)



Erosion block/EDM block – annealed or hardened [EB]

For example: 200,3 x 200,3 x 40,0 mm

- **Square** dimension milled /ground, tol. +2 /-0 mm
- **T** finely milled/ground, tol. +0,25/-0 mm
- Grain structure is vertically directed in relation to base **surface**



Premium P-Plates [PPP]

Eg.: 296,0 x 346,0 x 17,0 mm

- **W** fine milled, tol. +0,15 /-0 mm
- **L** fine milled, tol. +0,15 /-0 mm
- **T** ground, Tol. +0,35 /+0,20 mm

STEEL CLASSIFICATIONS

Steel grades are classified by their technical properties and /or by their **intended use**.

For example:

Cold work steel, hot work steel, plastic mould steel, high speed steel, corrosion resistant steel or case hardening steel.

Steel grades are often assigned to several classification groups. For more details on classification see www.steel-guide.eu/glossary




TOOL STEEL		TOOL STEEL I				TOOL STEEL II				HIGH SPEED STEEL				STAINLESS STEEL corrosion resistant / acid resistant				HEAT-TREATABLE STEEL, CASE HARDENING- & NITRIDING STEEL				INFORMATION							
STEEL GRADE	Description	Description																											
		PPS 500 mm	PPS 1.000 mm	PPS /BA 500 mm	PPS /BA 1.000 mm	PPS /BA 200, 300, 400, 800 mm	Eco-Präz [®] 300, 500, 1.000 mm	Hart-Präz [®] 250, 500 mm	Erosion block (annealed, hardened)	PPS ISO H8 / H9 / H11 1.000 mm	PPS /BA 500 mm	PPS /BA 1.000 mm	RS 500 mm	RS 1.000 mm	Delivery hardness (annealed/tempered) max. [HB]	Delivery hardness (hardened) approx. [HRC]	Approx. tensile strength [N/mm²] (deliv. cond.)	Max. working hardness [N/mm²]	Cold work steel	Hot work steel	Plastic mould steel	High speed steel	Corrosion resistant steel	Acid resistant steel	Heat-treatable steel	Case hardening steel	Nitriding steel		
PREMIUM 1.2990 mod. AISI / SAE 1.2990 mod.	~X100CrMoV8-2					✓				✓	✓			250	850	63	✓		✓								1.2990 mod. 1.2990 mod.		
PREMIUM 1.2842/1.2510 AISI / SAE O2/O1	90MnCrV8/100MnCrW4	✓	✓	✓	✓		✓		✓	✓	✓			229	57	770	62	✓		✓							1.2842 O2/O1		
PREMIUM 1.2826 AISI / SAE 1.2826	60MnSiCr4								✓		✓			220	750	60	✓										1.2826 1.2826		
PREMIUM 1.2767 AISI / SAE 6F7	45NiCrMo16			✓	✓				✓	✓	✓			260	880	54	✓	✓	✓								1.2767 6F7		
PREMIUM 1.2767 ESU AISI / SAE 6F7 ESR	45NiCrMo16					✓								260	880	54	✓	✓	✓								1.2767 ESU 6F7 ESR		
PREMIUM 1.2738 AISI / SAE P20+Ni	40CrMnNiMo8-6-4					✓				✓	✓			325	1100	50	✓		✓								1.2738 P20+Ni		
PREMIUM 1.2714 AISI / SAE L6	55NiCrMoV7					✓				✓	✓			250	850	54		✓									1.2714 L6		
PREMIUM 1.2714+QT AISI / SAE L6+QT	55NiCrMoV7+QT					✓						✓	✓	400	1350	54		✓									1.2714+QT L6+QT		
PREMIUM 1.2709 ESU AISI / SAE 1.2709 ESR	X3NiCoMoTi18-9-5									✓	✓	✓	✓	325	1100	56	✓	✓	✓								1.2709 ESU 1.2709 ESR		
PREMIUM 1.2550 AISI / SAE S1	60WCrV8					✓				✓	✓			229	770	60	✓										1.2550 S1		
PREMIUM 1.2436 AISI / SAE D6	X210CrW12	✓		✓	✓		✓			✓	✓			255	59	860	63	✓									1.2436 D6		
PREMIUM 1.2379 AISI / SAE D2	X153CrMoV12			✓	✓	✓	✓	✓	✓	✓	✓			255	57	860	62	✓		✓							1.2379 D2		
PREMIUM 1.2367 AISI / SAE 1.2367	X38CrMoV5-3					✓				✓	✓			229	770	54		✓	✓								1.2367 1.2367		
PREMIUM 1.2365 AISI / SAE H10	32CrMoV12-28					✓				✓	✓			229	770	52		✓	✓								1.2365 H10		
PREMIUM 1.2363 AISI / SAE A2	X100CrMoV5-1			✓	✓					✓	✓			241	815	62	✓		✓								1.2363 A2		
PREMIUM 1.2361 AISI / SAE 1.2361	X91CrMoV18				✓		✓	✓		✓	✓			265	53	900	58	✓		✓		✓	✓				1.2361 1.2361		
PREMIUM 1.2360/mod. AISI / SAE ~ Chipper/mod.	X48CrMoV8-1-1					✓				✓	✓			250	850	60	✓										1.2360 ~ Chipper		
PREMIUM 1.2358 AISI / SAE 1.2358	60CrMoV18-5					✓								325	1100	60	✓	✓	✓								1.2358 1.2358		
PREMIUM 1.2344 AISI / SAE H13	X40CrMoV5-1									✓	✓			229	770	56		✓	✓								1.2344 H13		
PREMIUM 1.2344 ESU AISI / SAE H13 ESR	X40CrMoV5-1					✓								229	770	56		✓	✓								1.2344 ESU H13 ESR		

PREMIUM 1.2990 mod. – AISI / SAE 1.2990 mod. (~X100CrMoV8-2)

€co-Präz® 500 [€co]

Length: 500 mm

		THICKNESS [mm]															
		8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH		Available dimensions [mm]															
1.2842 O2/O1	33	■	■	■	■	■	■	■									
1.2826	43	■	■	■	■	■	■	■	■								
1.2767 6F7	53	■	■	■	■	■	■	■	■	■							
1.2767 ESU 6F7 ESR	63	■	■	■	■	■	■	■	■	■	■						
1.2738 P20+Ni	73	■	■	■	■	■	■	■	■	■	■	■					
1.2714 L6	83	■	■	■	■	■	■	■	■	■	■	■	■				
1.2714+QT L6+QT	93	■	■	■	■	■	■	■	■	■	■	■	■	■			
1.2709 ESU 1.2709 ESR	103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
1.2550 S1	123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
1.2436 D6	143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1.2379 D2	153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1.2367 1.2367	163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1.2365 H10	183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1.2363 A2	203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1.2361 1.2361	223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1.2360 ~ Chipper	243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1.2358 1.2358	253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1.2344 H13	263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1.2344 ESU H13 ESR	283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
	303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values**

Delivery condition: maximum 250 HB
Chemical composition: (+additives):

C	Cr	Mo	V
1,0	8,0	1,8	0,15
1,0	8,0	2,7	0,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/2990mod-5

**Technical properties**

An all-rounder amongst the cold work steels: high toughness, good pressure resistance, excellent compression strength, excellent wear and tempering resistance. It is secondary-hardened and has a good dimensional stability, good erosion quality and excellent nitridability. Working hardness: approx. 57-63 HRC.

**Applications**

Blanking tools, stamping tools, precision cutting tools, dies, punches, thread rolling tools, cold pilger mandrels, plastic moulds, cold rollings, cold extrusion tools, cold forming tools, deep drawing dies, woodworking tools, embossing tools, bending tools, machine knives, circular shear knives, machine parts.

**AISI / SAE 1.2990 mod. – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2990mod

via smartphone/tablet:



PREMIUM 1.2990 mod. – AISI / SAE 1.2990 mod. (~X100CrMoV8-2)

Precision round steel with machining allowance [PRS/BA]

Specification: peeled/rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
25,5	●	●
30,5	●	●
35,5	●	●
40,5	●	●
50,5	●	●
60,5	●	●
70,5		●
80,5		●
90,5		●
100,5		●


Larger diameters, up to 450,5 mm and different lengths (e.g. round blanks) available on request!

**Technical properties**

An all-rounder amongst the cold work steels: high toughness, good pressure resistance, excellent compression strength, excellent wear and tempering resistance. It is secondary-hardened and has a good dimensional stability, good erosion quality and excellent nitridability. Working hardness: approx. 57-63 HRC.

**Applications**

Blanking tools, stamping tools, precision cutting tools, dies, punches, thread rolling tools, cold pilger mandrels, plastic moulds, cold rollings, cold extrusion tools, cold forming tools, deep drawing dies, woodworking tools, embossing tools, bending tools, machine knives, circular shear knives, machine parts.

**Tolerances****Standard values**

Delivery condition: maximum 250 HB

Chemical composition: (+additives):

C	Cr	Mo	V
1,0	8,0	1,8	0,15
1,0	8,0	2,7	0,5

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**
www.premium-steel.eu/2990mod-7
**AISI / SAE 1.2990 mod. – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2990mod

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2990 mod.
1.2990 mod.1.2842
O2/O11.2826
1.28261.2767
6F71.2767 ESU
6F7 ESR1.2738
P20+Ni1.2714
L61.2714+QT
L6+QT1.2709 ESU
1.2709 ESR1.2550
S11.2436
D61.2379
D21.2367
1.23671.2365
H101.2363
A21.2361
1.23611.2360
~ Chipper1.2358
1.23581.2344
H131.2344 ESU
H13 ESR

PREMIUM 1.2842/1.2510 – AISI / SAE O2/O1 (90MnCrV8/100MnCrW4)

Precision flat steel without machining allowance, DIN 59350 [PFS]

Length: 500 mm


	THICKNESS [mm]																			
	1,0	1,5	2,0	3,0	4,0	5,0	6,0	8,0	10,0	12,0	15,0	16,0	18,0	20,0	25,0	30,0	40,0	50,0	60,0	
WIDTH	Available dimensions [mm]																			
4,0					■															
5,0						■														
6,0							■													
8,0								■												
10,0	■	■	■	■	■	■	■	■	■											
12,0	■	■	■	■	■	■	■	■	■	■										
15,0	■	■	■	■	■	■	■	■	■	■	■									
16,0												■								
18,0													■							
20,0	■	■	■	■	■	■	■	■	■	■	■			■						
25,0	■	■	■	■	■	■	■	■	■	■	■				■					
30,0	■	■	■	■	■	■	■	■	■	■	■				■	■				
35,0	■	■	■	■	■	■	■	■	■	■	■				■	■	■			
40,0	■	■	■	■	■	■	■	■	■	■	■				■	■	■	■		
50,0	■	■	■	■	■	■	■	■	■	■	■				■	■	■	■	■	
60,0	■	■	■	■	■	■	■	■	■	■	■				■	■	■	■	■	
70,0	■	■	■	■	■	■	■	■	■	■	■				■	■	■	■	■	
80,0	■	■	■	■	■	■	■	■	■	■	■				■	■	■	■	■	
100,0	■	■	■	■	■	■	■	■	■	■	■				■	■	■	■	■	
120,0	■	■	■	■	■	■	■	■	■	■	■				■	■	■	■	■	
125,0	■	■	■	■	■	■	■	■	■	■	■				■	■	■	■	■	
150,0	■	■	■	■	■	■	■	■	■	■	■				■	■	■	■	■	
160,0	■	■	■	■	■	■	■	■	■	■	■				■	■	■	■	■	
180,0	■	■	■	■	■	■	■	■	■	■	■				■	■	■	■	■	
200,0	■	■	■	■	■	■	■	■	■	■	■				■	■	■	■	■	
250,0	■	■	■	■	■	■	■	■	■	■	■				■	■	■	■	■	
300,0	■	■	■	■	■	■	■	■	■	■	■				■	■	■	■	■	

**Technical properties**

Alloyed oil hardener with focus on cold work; can be used for a wide range of applications: full hardenability, high degree of dimensional stability, good cutting power and good toughness. Its technical properties and its applications are similar to those of AISI / SAE O1. Working hardness: 57-62 HRC.

**Applications**

Blanking and stamping tools (up to 6 mm thickness), shear knives, threading tools, thread dies, reamers, chasers, measuring tools, plastic moulds, rubber moulds, calibres, guide rails, dies, punches, woodworking tools, machine knives.

**Tolerances****Standard values (AISI / SAE O2)**

Delivery condition: maximum 229 HB
Chemical composition:

C	Si	Mn	P	S	Cr	V
0,85	0,1	1,8	0	0	0,2	0,05
0,95	0,4	2,2	0,03	0,03	0,5	0,2

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/O2-1

**AISI / SAE O2 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/O2

via smartphone/tablet:



PREMIUM 1.2842/1.2510 – AISI / SAE O2/O1 (90MnCrV8/100MnCrW4)

Precision flat steel without machining allowance, DIN 59350 [PFS]

Length: 1.000 mm

	THICKNESS [mm]																
	2,0	3,0	4,0	5,0	6,0	8,0	10,0	12,0	15,0	16,0	18,0	20,0	25,0	30,0	40,0	50,0	60,0
WIDTH	Available dimensions [mm]																
4,0			■														
5,0				■													
6,0					■												
8,0						■											
10,0	■	■	■	■	■	■	■										
12,0	■	■	■	■	■	■	■	■									
15,0	■	■	■	■	■	■	■	■	■								
16,0										■							
18,0											■						
20,0	■	■	■	■	■	■	■	■	■			■					
25,0	■	■	■	■	■	■	■	■	■			■	■				
30,0	■	■	■	■	■	■	■	■	■			■	■	■			
35,0	■	■	■	■	■	■	■	■	■			■	■	■			
40,0	■	■	■	■	■	■	■	■	■			■	■	■	■		
50,0	■	■	■	■	■	■	■	■	■			■	■	■	■	■	
60,0	■	■	■	■	■	■	■	■	■			■	■	■	■	■	■
70,0	■	■	■	■	■	■	■	■	■			■	■	■	■	■	
80,0	■	■	■	■	■	■	■	■	■			■	■	■	■	■	
100,0	■	■	■	■	■	■	■	■	■			■	■	■	■	■	
120,0	■	■	■	■	■	■	■	■	■			■	■	■	■	■	
125,0	■	■	■	■	■	■	■	■	■			■	■	■	■	■	
150,0	■	■	■	■	■	■	■	■	■			■	■	■	■	■	
160,0	■	■	■	■	■	■	■	■	■			■	■	■	■	■	
180,0	■	■	■	■	■	■	■	■	■			■	■	■	■	■	
200,0	■	■	■	■	■	■	■	■	■			■	■	■	■	■	
250,0	■	■	■	■	■	■	■	■	■			■	■	■	■	■	
300,0	■	■	■	■	■	■	■	■	■			■	■	■	■	■	

**Technical properties**


Alloyed oil hardener with focus on cold work; can be used for a wide range of applications: full hardenability, high degree of dimensional stability, good cutting power and good toughness. Its technical properties and its applications are similar to those of AISI / SAE O1. Working hardness: 57-62 HRC.

**Applications**

Blanking and stamping tools (up to 6 mm thickness), shear knives, threading tools, thread dies, reamers, chasers, measuring tools, plastic moulds, rubber moulds, calibres, guide rails, dies, punches, woodworking tools, machine knives.

**Tolerances**

T +0,05 / -0 mm



W +0,2 / -0 mm

**Standard values (AISI / SAE O2)**

Delivery condition: maximum 229 HB

Chemical composition:

C	Si	Mn	P	S	Cr	V
0,85	0,1	1,8	0	0	0,2	0,05
0,95	0,4	2,2	0,03	0,03	0,5	0,2

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**
www.premium-steel.eu/O2-2
**AISI/SAE O2, all at a glance!**

Datasheets, online shop, ABRAMS STEEL GUIDE® for alternatives: www.premium-steel.eu/O2

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2990 mod.
1.2990 mod.**1.2842
O2/O1**1.2826
1.28261.2767
6F71.2767 ESU
6F7 ESR1.2738
P20+Ni1.2714
L61.2714+QT
L6+QT1.2709 ESU
1.2709 ESR1.2550
S11.2436
D61.2379
D21.2367
1.23671.2365
H101.2363
A21.2361
1.23611.2360
~ Chipper1.2358
1.23581.2344
H131.2344 ESU
H13 ESR

PREMIUM 1.2842/1.2510 – AISI / SAE O2/O1 (90MnCrV8/100MnCrW4)

Precision flat steel with machining allowance [PFS/BA]

Length: 500 mm

	THICKNESS [mm]																				
	2,2	3,2	4,2	5,2	6,2	8,2	10,3	12,3	15,3	16,3	18,3	20,3	25,3	30,3	32,3	40,3	50,3	60,3	63,3	80,3	100,3
WIDTH	Available dimensions [mm]																				
8,2						■															
10,3	■	■	■	■	■	■	■														
12,3	■	■	■	■	■	■	■	■													
15,3	■	■	■	■	■	■	■	■	■												
16,3										■											
18,3											■										
20,3	■	■	■	■	■	■	■	■	■	■		■									
25,3	■	■	■	■	■	■	■	■	■	■		■	■								
30,3	■	■	■	■	■	■	■	■	■	■		■	■	■							
32,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■						
35,3	■	■	■	■	■	■	■	■	■	■		■	■	■							
40,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■					
50,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■				
60,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■			
63,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■		
70,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	
80,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■
100,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■
120,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■
125,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■
150,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■
160,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■
175,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■
180,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■
200,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■
250,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■
300,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■				
500 *						■	■	■	■			■	■	■		■					


* Width and length sawn/black with +tol./-0 mm

**Technical properties**

Alloyed oil hardener with focus on cold work; can be used for a wide range of applications: full hardenability, high degree of dimensional stability, good cutting power and good toughness. Its technical properties and its applications are similar to those of AISI / SAE O1. Working hardness: 57-62 HRC.

**Applications**

Blanking and stamping tools (up to 6 mm thickness), shear knives, threading tools, thread dies, reamers, chasers, measuring tools, plastic moulds, rubber moulds, calibres, guide rails, dies, punches, woodworking tools, machine knives.

**Tolerances****Standard values (AISI / SAE O2)**

Delivery condition: maximum 229 HB
Chemical composition:

C	Si	Mn	P	S	Cr	V
0,85	0,1	1,8	0	0	0,2	0,05
0,95	0,4	2,2	0,03	0,03	0,5	0,2

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/O2-3

**AISI / SAE O2 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/O2

via smartphone/tablet:



PREMIUM 1.2842/1.2510 – AISI / SAE O2/O1 (90MnCrV8/100MnCrW4)

Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm

	THICKNESS [mm]																					
	2,2	3,2	4,2	5,2	6,2	8,2	10,3	12,3	15,3	16,3	18,3	20,3	25,3	30,3	32,3	40,3	50,3	60,3	63,3	80,3	100,3	
WIDTH	Available dimensions [mm]																					
8,2						■																
10,3	■	■	■	■	■	■	■															
12,3	■	■	■	■	■	■	■	■														
15,3	■	■	■	■	■	■	■	■	■													
16,3										■												
18,3											■											
20,3	■	■	■	■	■	■	■	■	■	■		■										
25,3	■	■	■	■	■	■	■	■	■	■		■	■									
30,3	■	■	■		■	■	■	■	■	■		■	■	■								
32,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■							
35,3	■	■	■	■		■	■	■	■	■		■	■	■								
40,3	■	■			■	■	■	■	■	■		■	■	■	■	■						
50,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■					
60,3	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■				
63,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■		■			
70,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■			
80,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■		
100,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	
120,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	
125,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	
150,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	
160,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	
175,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	
180,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	
200,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	
250,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	
300,3	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■					
500 *					■	■	■	■	■			■	■	■		■						


* Width and length sawn/black with +tol./-0 mm

**Technical properties**

Alloyed oil hardener with focus on cold work; can be used for a wide range of applications: full hardenability, high degree of dimensional stability, good cutting power and good toughness. Its technical properties and its applications are similar to those of AISI / SAE O1. Working hardness: 57-62 HRC.

**Applications**

Blanking and stamping tools (up to 6 mm thickness), shear knives, threading tools, thread dies, reamers, chasers, measuring tools, plastic moulds, rubber moulds, calibres, guide rails, dies, punches, woodworking tools, machine knives.

**Tolerances****Standard values (AISI / SAE O2)**

Delivery condition: maximum 229 HB

Chemical composition:

C	Si	Mn	P	S	Cr	V
0,85	0,1	1,8	0	0	0,2	0,05
0,95	0,4	2,2	0,03	0,03	0,5	0,2

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**
www.premium-steel.eu/O2-4
**AISI / SAE O2 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/O2

via smartphone / tablet:

NAVIGATION/
STEEL GRADES1.2990 mod.
1.2990 mod.**1.2842
O2/O1**1.2826
1.28261.2767
6F71.2767 ESU
6F7 ESR1.2738
P20+Ni1.2714
L61.2714+QT
L6+QT1.2709 ESU
1.2709 ESR1.2550
S11.2436
D61.2379
D21.2367
1.23671.2365
H101.2363
A21.2361
1.23611.2360
~ Chipper1.2358
1.23581.2344
H131.2344 ESU
H13 ESR

PREMIUM 1.2842/1.2510 – AISI / SAE O2/O1 (90MnCrV8/100MnCrW4)**Hart-Präz® 250 [Hart]**

Length: 250 mm


	THICKNESS [mm]													
	2,2	2,7	3,2	3,7	4,2	4,7	5,2	6,2	7,2	8,2	9,2	10,2	12,2	14,2
WIDTH	Available dimensions [mm]													
250	■	■	■	■	■	■	■	■	■	■	■	■	■	■

Hart-Präz® 500 [Hart]

Length: 500 mm

	THICKNESS [mm]													
	2,2	2,7	3,2	3,7	4,2	4,7	5,2	6,2	7,2	8,2	9,2	10,2	12,2	14,2
WIDTH	Available dimensions [mm]													
250	■	■	■	■	■	■	■	■	■	■	■	■	■	■


Hardened dimensions are delivered with approx. 57 HRC, at least 2x tempered.

**Technical properties**

Alloyed oil hardener with focus on cold work; can be used for a wide range of applications: full hardenability, high degree of dimensional stability, good cutting power and good toughness. Its technical properties and its applications are similar to those of AISI / SAE O1. Working hardness: 57-62 HRC.

**Applications**

Blanking and stamping tools (up to 6 mm thickness), shear knives, threading tools, thread dies, reamers, chasers, measuring tools, plastic moulds, rubber moulds, calibres, guide rails, dies, punches, woodworking tools, machine knives.

**Tolerances****Standard values (AISI / SAE O2)**

Delivery condition: approx. 57 HRC
Chemical composition:

C	Si	Mn	P	S	Cr	V
0,85	0,1	1,8	0	0	0,2	0,05
0,95	0,4	2,2	0,03	0,03	0,5	0,2

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/O2-11-H

**AISI / SAE O2 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/O2

via smartphone/tablet:



PREMIUM 1.2842/1.2510 – AISI / SAE O2/O1 (90MnCrV8/100MnCrW4)

Precision round steel without machining allowance [PRS]
Specification: bright ground, ISO h8

Ø [mm]	LENGTH [mm]
	1.000
Available dimensions [•]	
4,5	•
5,0	•
6,0	•
8,0	•
10,0	•
12,0	•
15,0	•
20,0	•
25,0	•

Precision round steel with machining allowance [PRS/BA]
Specification: peeled / rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
Available dimensions [•]		
10,5	•	•
15,5	•	•
20,5	•	•
25,5	•	•
30,5	•	•
35,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
55,5	•	•
60,5	•	•
65,5		•
70,5		•
75,5		•
80,5		•
85,5		•
90,5		•
95,5		•
100,5		•


Larger diameters, up to 500,5 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Alloyed oil hardener with focus on cold work; can be used for a wide range of applications: full hardenability, high degree of dimensional stability, good cutting power and good toughness. Its technical properties and its applications are similar to those of AISI / SAE O1. Working hardness: 57-62 HRC.

**Applications**

Blanking and stamping tools (up to 6 mm thickness), shear knives, threading tools, thread dies, reamers, chasers, measuring tools, plastic moulds, rubber moulds, calibres, guide rails, dies, punches, woodworking tools, machine knives.

**Tolerances****Standard values (AISI / SAE O2)**

Delivery condition: maximum 229 HB
Chemical composition:

C	Si	Mn	P	S	Cr	V
0,85	0,1	1,8	0	0	0,2	0,05
0,95	0,4	2,2	0,03	0,03	0,5	0,2

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop [PRS]**

www.premium-steel.eu/O2-6
[PRS/BA]
www.premium-steel.eu/O2-7

**AISI / SAE O2 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/O2

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13

1.2344 ESU
H13 ESR



PRECISION ROUND STEEL WITHOUT MACHINING ALLOWANCE – ISO h8, h9, h11

ABRAMS!
PREMIUM STEEL

PREMIUM 1.2826 – AISI / SAE 1.2826 (60MnSiCr4)

Precision round steel without machining allowance [PRS]
Specification: bright finely peeled, ISO h11

	LENGTH [mm]
	1.000
Ø [mm]	Available dimensions [•]
18,0	•
22,0	•
23,0	•
24,0	•
26,0	•
27,0	•
28,0	•
30,0	•
33,0	•
35,0	•
36,0	•
38,0	•
40,0	•
43,0	•
45,0	•
48,0	•
50,0	•
52,0	•
54,0	•
58,0	•
60,0	•

Precision round steel [PRS/BA]
Specification: peeled / rough-turned

	LENGTH [mm]
	1.000
Ø [mm]	Available dimensions [•]
62,0	•
66,0	•
70,0	•
72,0	•
75,0	•
80,0	•
85,0	•
90,0	•
92,0	•
95,0	•
100,0	•


Larger diameters, up to 400,0 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Cold work steel with excellent wear resistance, high toughness and excellent spring properties when tempered.
Working hardness: 57-60 HRC.

**Applications**

Collet chucks, split chucks, dies (small quantities), hot cutting tools, trimming tools, ejectors, press plates, cold bending tools, shear knives, punches, screwdrivers, drifts, mandrels, centre punches.

**Tolerances****Standard values**

Delivery condition: maximum 220 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,58	0,8	0,8	0	0	0,2
0,65	1,0	1,2	0,03	0,03	0,4

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop [PRS]**

www.premium-steel.eu/2826-6
[PRS/BA]
www.premium-steel.eu/2826-7

**AISI / SAE 1.2826 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2826

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13

1.2344 ESU
H13 ESR

PREMIUM 1.2767 – AISI / SAE 6F7 (45NiCrMo16)

Precision flat steel with machining allowance [PFS/BA]

Length: 500 mm

	THICKNESS [mm]																			
	4,2	5,2	6,2	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	40,3	50,3	60,3	63,3	70,3	80,3	90,3	100,3
WIDTH	Available dimensions [mm]																			
10,3	■	■	■	■	■															
12,3	■	■	■	■	■	■														
15,3	■	■	■	■	■	■	■													
16,3	■	■	■	■	■	■		■												
20,3	■	■	■	■	■	■	■	■	■											
25,3	■	■	■	■	■	■	■	■	■	■										
30,3	■	■	■	■	■	■	■	■	■	■	■									
32,3	■	■	■	■	■	■	■	■	■	■	■	■								
40,3	■	■	■	■	■	■	■	■	■	■	■	■	■							
50,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■						
60,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■					
63,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
70,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
80,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
90,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
100,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
125,3				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
150,3				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
200,3				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
250,3				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
300,3				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
500 *					■	■	■		■	■	■		■	■						


* Width and length sawn/black with +tol./-0 mm

**Technical properties**

Steel grade with focus on cold work, high toughness (nickel content), good through-hardenedability (even for large cross-sections), as well as high impact strength and pressure resistance. Polishable, etchable and erodible. For very special purity and homogeneousness we recommend AISI / SAE 6F7 ESR. Working hardness: 50-54 HRC.

**Applications**

Cutting tools, cutlery punches, embossing tools, bending tools, cold hobbing tools, pressure bars, billet shear knives, cold shear knives, plastic moulds, hot press tools, light metal processing, heavy metal processing, drawing jaws, reinforcements.

**Tolerances****Standard values**

Delivery condition: maximum 260 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni
0,4	0,1	0,2	0	0	1,2	0,15	3,8
0,5	0,4	0,5	0,03	0,03	1,5	0,35	4,3

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/6F7-3

**AISI / SAE 6F7 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/6F7

via smartphone/tablet:



PREMIUM 1.2767 – AISI / SAE 6F7 (45NiCrMo16)

Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm

	THICKNESS [mm]																			
	4,2	5,2	6,2	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	40,3	50,3	60,3	63,3	70,3	80,3	90,3	100,3
WIDTH	Available dimensions [mm]																			
10,3	■	■	■	■	■															
12,3	■	■	■	■	■	■														
15,3							■													
16,3	■	■	■	■	■	■		■												
20,3	■	■	■	■	■	■	■	■	■											
25,3	■	■	■	■	■	■	■	■	■	■										
30,3	■	■	■	■	■	■	■	■	■	■	■									
32,3	■	■	■	■	■	■	■	■	■	■	■	■								
40,3	■	■	■	■	■	■	■	■	■	■	■	■	■							
50,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■						
60,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■					
63,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
70,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
80,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
90,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
100,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
125,3				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
150,3				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
200,3				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
250,3				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
300,3				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
500 *					■	■	■		■	■	■		■	■						


* Width and length sawn/black with +tol./-0 mm

**Technical properties**

Steel grade with focus on cold work, high toughness (nickel content), good through-hardening (even for large crosssections), as well as high impact strength and pressure resistance. Polishable, etchable and erodible. For very special purity and homogeneousness we recommend AISI / SAE 6F7 ESR. Working hardness: 50-54 HRC.

**Applications**

Cutting tools, cutlery punches, embossing tools, bending tools, cold hobbing tools, pressure bars, billet shear knives, cold shear knives, plastic moulds, hot press tools, light metal processing, heavy metal processing, drawing jaws, reinforcements.

**Tolerances****Standard values**

Delivery condition: maximum 260 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni
0,4	0,1	0,2	0	0	1,2	0,15	3,8
0,5	0,4	0,5	0,03	0,03	1,5	0,35	4,3

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/6F7-4

**AISI / SAE 6F7 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/6F7

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

**1.2767
6F7**

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2




1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13

1.2344 ESU
H13 ESR



70 STEEL GRADES IN 32.629 STANDARD DIMENSIONS AVAILABLE FROM STOCK!

ABRAMS!
PREMIUM STEEL®

PREMIUM 1.2767 – AISI / SAE 6F7 (45NiCrMo16)

Precision round steel without machining allowance [PRS]
Specification: bright ground, ISO h8

	LENGTH [mm]
	1.000
Ø [mm]	Available dimensions [•]
10,0	•
12,0	•
15,0	•
20,0	•
25,0	•

Precision round steel with machining allowance [PRS/BA]
Specification: peeled / rough-turned

	LENGTH [mm]	
	500	1.000
Ø [mm]	Available dimensions [•]	
10,5	•	•
20,5	•	•
25,5	•	•
30,5	•	•
35,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
55,5	•	•
60,5	•	•
65,5		•
70,5		•
75,5		•
80,5		•
85,5		•
90,5		•
95,5		•
100,5		•


Larger diameters, up to 500,5 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Steel grade with focus on cold work, high toughness (nickel content), good through-hardening (even for large crosssections), as well as high impact strength and pressure resistance. Polishable, etchable and erodible. Working hardness: 50-54 HRC.

**Applications**

Cutting tools, cutlery punches, embossing tools, bending tools, cold hobbing tools, pressure bars, billet shear knives, cold shear knives, plastic moulds, hot press tools, light metal processing, heavy metal processing, drawing jaws, reinforcements.

**Tolerances****Standard values**

Delivery condition: maximum 260 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni
0,4	0,1	0,2	0	0	1,2	0,15	3,8
0,5	0,4	0,5	0,03	0,03	1,5	0,35	4,3

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop [PRS]**

www.premium-steel.eu/6F7-6

[PRS/BA]

www.premium-steel.eu/6F7-7

**AISI / SAE 6F7 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/6F7

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

**1.2767
6F7**

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13


1.2344 ESU
H13 ESR

PREMIUM 1.2767 ESU – AISI / SAE 6F7 ESR (45NiCrMo16)

€co-Präz® 300 [€co]

Length: 300 mm

	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values**

Delivery condition: maximum 260 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni
0,4	0,1	0,2	0	0	1,2	0,15	3,8
0,5	0,4	0,5	0,03	0,03	1,5	0,35	4,3

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/6F7ESR-3-5

**Technical properties**

Steel grade with focus on cold work, high toughness (nickel content), good through-hardenability (even for large crosssections), as well as high impact strength and pressure resistance. Polishable, etchable and erodible. For very special purity and homogeneousness we recommend AISI / SAE 6F7 ESR. Working hardness: 50-54 HRC.

**Applications**

Cutting tools, cutlery punches, embossing tools, bending tools, cold hobbing tools, pressure bars, billet shear knives, cold shear knives, plastic moulds, hot press tools, light metal processing, heavy metal processing, drawing jaws, reinforcements.



AISI / SAE 6F7 ESR – all at a glance!
Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/6F7ESR

via smartphone/tablet:



PREMIUM 1.2767 ESU – AISI / SAE 6F7 ESR (45NiCrMo16)

Eco-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Steel grade with focus on cold work, high toughness (nickel content), good through-hardening (even for large crosssections), as well as high impact strength and pressure resistance. Polishable, etchable and erodible. For very special purity and homogeneity we recommend AISI / SAE 6F7 ESR. Working hardness: 50-54 HRC.

**Applications**

Cutting tools, cutlery punches, embossing tools, bending tools, cold hobbing tools, pressure bars, billet shear knives, cold shear knives, plastic moulds, hot press tools, light metal processing, heavy metal processing, drawing jaws, reinforcements.

**Tolerances****Standard values**

Delivery condition: maximum 260 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni
0,4	0,1	0,2	0	0	1,2	0,15	3,8
0,5	0,4	0,5	0,03	0,03	1,5	0,35	4,3

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/6F7ESR-5-5

**AISI / SAE 6F7 ESR – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/6F7ESR

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13


1.2344 ESU
H13 ESR

PREMIUM 1.2738 – AISI / SAE P20+Ni (40CrMnNiMo8-6-4)

€co-Präz® 500 [€co]

Length: 500 mm

	THICKNESS [mm]																	
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3	150,3	
WIDTH	Available dimensions [mm]																	
33	■	■	■	■	■	■	■											
43	■	■	■	■	■	■	■	■										
53	■	■	■	■	■	■	■	■	■									
63	■	■	■	■	■	■	■	■	■	■								
73	■	■	■	■	■	■	■	■	■	■	■							
83	■	■	■	■	■	■	■	■	■	■	■	■						
93	■	■	■	■	■	■	■	■	■	■	■	■	■					
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	

**Tolerances****Standard values**

Delivery condition: maximum 325 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni
0,35	0,2	1,3	0	0	1,8	0,15	0,9
0,45	0,4	1,6	0,03	0,03	2,1	0,25	1,2

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/P20Ni-5

**Technical properties**

Steel grade with focus on plastic mould making; nickel additives for a better through-hardening (constant strength), also for thicknesses > 400 mm. Low sulphur steel and therefore polishable and grainable. Working hardness: approx. 32 HRC (delivery condition: quenched and tempered) up to 50 HRC.

**Applications**

Plastic moulds, moulding frames, die casting moulds, dies, forging tools, metal extrusion tools, tube presses, hydroforming tools.

**AISI / SAE P20+Ni – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/P20Ni

via smartphone/tablet:



PREMIUM 1.2738 – AISI / SAE P20+Ni (40CrMnNiMo8-6-4)

Precision round steel with machining allowance [PRS/BA]

Specification: peeled / rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
	Available dimensions [•]	
20,5	•	•
25,5	•	•
30,5	•	•
35,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
55,5	•	•
60,5	•	•
65,5		•
70,5		•
75,5		•
80,5		•
85,5		•
90,5		•
100,5		•


Larger diameters, up to 655,5 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Steel grade with focus on plastic mould making; nickel additives for a better through-hardenability (constant strength), also for thicknesses > 400 mm. Low sulphur steel and therefore polishable and grainable. Working hardness: approx. 32 HRC (delivery condition: quenched and tempered) up to 50 HRC.

**Applications**

Plastic moulds, moulding frames, die casting moulds, dies, forging tools, metal extrusion tools, tube presses, hydroforming tools.

**Tolerances****Standard values**

Delivery condition: maximum 325 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni
0,35	0,2	1,3	0	0	1,8	0,15	0,9
0,45	0,4	1,6	0,03	0,03	2,1	0,25	1,2

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/P20Ni-7

**AISI / SAE P20+Ni – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/P20Ni

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13


1.2344 ESU
H13 ESR

PREMIUM 1.2714 – AISI / SAE L6 (55NiCrMoV7)

€co-Präz® 500 [€co]

Length: 500 mm

	THICKNESS [mm]																	
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3	150,3	
WIDTH	Available dimensions [mm]																	
33	■	■	■	■	■	■	■											
43	■	■	■	■	■	■	■	■										
53	■	■	■	■	■	■	■	■	■									
63	■	■	■	■	■	■	■	■	■	■								
73	■	■	■	■	■	■	■	■	■	■	■							
83	■	■	■	■	■	■	■	■	■	■	■	■						
93	■	■	■	■	■	■	■	■	■	■	■	■	■					
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	

**Tolerances****Standard values**

Delivery condition: maximum 250 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni	V
0,5	0,1	0,6	0	0	0,8	0,35	1,5	0,05
0,6	0,4	0,9	0,03	0,03	1,2	0,55	1,8	0,15

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/L6-5

**Technical properties**

Hot work steel that can be used for a wide range of applications. With good through-hardening, tempering resistance, toughness, pressure and heat resistance. Delivery condition: annealed. Working hardness: approx. 40-54 HRC.

**Applications**

Forging dies, slides, punch heads, extruding stamps, press tools, hot shear knives, extrusion press tools, die holders, support tools, tool holders, pressure plates, armoured die plates.

**AISI / SAE L6 – all at a glance!**

Datasheets, online shop, ABRAMS STEEL GUIDE® for alternatives: www.premium-steel.eu/L6

via smartphone/tablet:



PREMIUM 1.2714 – AISI / SAE L6 (55NiCrMoV7)

Precision round steel with machining allowance [PRS/BA]

Specification: peeled / rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
	Available dimensions [•]	
20,5	•	•
25,5	•	•
30,5	•	•
35,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
55,5	•	•
60,5	•	•
65,5		•
70,5		•
75,5		•
80,5		•
85,5		•
90,5		•
95,5		•
100,5		•




Larger diameters, up to 905,5 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Hot work steel that can be used for a wide range of applications. With good through-hardening, tempering resistance, toughness, pressure and heat resistance. Delivery condition: annealed. Working hardness: approx. 40-54 HRC.

**Applications**

Forging dies, slides, punch heads, extruding stamps, press tools, hot shear knives, extrusion press tools, die holders, support tools, tool holders, pressure plates, armoured die plates.

**Tolerances****Standard values**

Delivery condition: maximum 250 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni	V
0,5	0,1	0,6	0	0	0,8	0,35	1,5	0,05
0,6	0,4	0,9	0,03	0,03	1,2	0,55	1,8	0,15

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/L6-7

**AISI / SAE L6 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/L6

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13


1.2344 ESU
H13 ESR

PREMIUM 1.2714+QT – AISI / SAE L6+QT (55NiCrMoV7+QT)

€co-Präz® 500 [€co]

Length: 500 mm

	THICKNESS [mm]																	
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3	150,3	
WIDTH	Available dimensions [mm]																	
33	■	■	■	■	■	■	■											
43	■	■	■	■	■	■	■	■										
53	■	■	■	■	■	■	■	■	■									
63	■	■	■	■	■	■	■	■	■	■								
73	■	■	■	■	■	■	■	■	■	■	■							
83	■	■	■	■	■	■	■	■	■	■	■	■						
93	■	■	■	■	■	■	■	■	■	■	■	■	■					
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	

**Tolerances****Standard values**

Delivery condition: maximum 400 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni	V
0,5	0,1	0,6	0	0	0,8	0,35	1,5	0,05
0,6	0,4	0,9	0,03	0,03	1,2	0,55	1,8	0,15

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/L6QT-5

**Technical properties**

Hot work steel that can be used for a wide range of applications. With good through-hardenability, tempering resistance, toughness, pressure and heat resistance. Delivery condition: tempered. Working hardness: approx. 40 HRC (delivery condition) up to 54 HRC.

**Applications**

Forging dies, slides, punch heads, extruding stamps, press tools, hot shear knives, extrusion press tools, die holders, support tools, tool holders, pressure plates, armoured die plates.

**AISI / SAE L6+QT – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/L6QT

via smartphone/tablet:



PREMIUM 1.2714+QT – AISI / SAE L6+QT (55NiCrMoV7+QT)

Round steel [RS]
Specification: black

Ø [mm]	LENGTH [mm]	
	500	1.000
	Available dimensions [•]	
20	•	•
25	•	•
30	•	•
35	•	•
40	•	•
50	•	•
55	•	•
60	•	•
65		•
70		•
80		•
85		•
90		•
100		•


Larger diameters, up to 705 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Hot work steel that can be used for a wide range of applications. With good through-hardening, tempering resistance, toughness, pressure and heat resistance. Delivery condition: tempered. Working hardness: approx. 40 HRC (delivery condition) up to 54 HRC.

**Applications**

Forging dies, slides, punch heads, extruding stamps, press tools, hot shear knives, extrusion press tools, die holders, support tools, tool holders, pressure plates, armoured die plates.

**Tolerances****Standard values**

Delivery condition: maximum 400 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni	V
0,5	0,1	0,6	0	0	0,8	0,35	1,5	0,05
0,6	0,4	0,9	0,03	0,03	1,2	0,55	1,8	0,15

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/L6QT-8

**AISI / SAE L6+QT – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/L6QT

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

**1.2714+QT
L6+QT**

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13

1.2344 ESU
H13 ESR

SUPERIORITY !



PREMIUM 1.2709 ESU – AISI / SAE 1.2709 ESR (X3NiCoMoTi18-9-5)

Precision round steel with machining allowance [PRS/BA]
Specification: peeled /rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
Available dimensions [•]		
15,5	•	•
20,5	•	•
25,5	•	•
30,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
60,5	•	•
70,5		•
80,5		•
100,5		•

Larger diameters, up to 120,5 mm and different lengths (e.g. round blanks) available on request!


Round steel [RS]
Specification: black

Ø [mm]	LENGTH [mm]	
	500	1.000
Available dimensions [•]		
15	•	•
20	•	•
25	•	•
30	•	•
40	•	•
45	•	•
50	•	•
60	•	•
65		•
70		•
80		•
90		•
110		•

Larger diameters, up to 180 mm, and different lengths (e.g. round blanks) available on request!



Tolerances



Standard values

Delivery condition: maximum 325 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni	Ti	Co
0,03	0,1	0,15	0,01	0,01	0,25	5,2	19,0	1,2	10,0



If you need customised dimensions -

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!



Contact us

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu



Direct access to our online shop

[PRS/BA]

www.premium-steel.eu/2709ESR-7

[RS]

www.premium-steel.eu/2709ESR-8



Technical properties

Ultra-high strength tool steel with excellent toughness, high yield point and high tensile strength. Easy heat treatment at low temperatures. Good dimensional stability and low distortion. Good machinability when hardened. Working hardness: 51-56 HRC.



Applications

Slides, gear cutting tools, cold heading tools, embossing tools, press dies, hot press molds and tools, tool holders, cutting punches, die casting moulds (for light metal alloys), plastic moulds, reinforcements, light metal processing, shear knives, nozzles, distributor pins, cores.



AISI / SAE 1.2709 ESR – all at a glance!

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2709ESR

via smartphone/tablet:



NAVIGATION/ STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13


1.2344 ESU
H13 ESR

PREMIUM 1.2550 – AISI / SAE S1 (60WCrV8)

€co-Präz® 500 [€co]

Length: 500 mm

	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values**

Delivery condition: maximum 229 HB
Chemical composition:

C	Si	Mn	P	S	Cr	V	W
0,55	0,7	0,15	0	0	0,9	0,1	1,7
0,65	1,0	0,45	0,03	0,03	1,2	0,2	2,2

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/S1-5

**Technical properties**

Steel grade with focus on cold work, with full hardenability, excellent toughness, dimensional stability and impact strength.
Working hardness: 56-60 HRC.

**Applications**

Blanking tools, dies, punches, forming dies, embossing tools, coining tools, tableting punches, plug-in tools, trimming tools, cold shear knives, riveting pins, hand chisels, pneumatic chisels, centre punches, ejectors, woodworking tools.

**AISI / SAE S1 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/S1

via smartphone / tablet:



PREMIUM 1.2550 – AISI / SAE S1 (60WCrV8)

Precision round steel with machining allowance [PRS/BA]

Specification: peeled / rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
Available dimensions [•]		
20,5	•	•
22,5	•	•
25,5	•	•
28,5	•	•
30,5	•	•
35,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
55,5	•	•
60,5	•	•
65,5		•
70,5		•
75,5		•
80,5		•
85,5		•
90,5		•
100,5		•


Larger diameters, up to 180,5 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Steel grade with focus on cold work, with full hardenability, excellent toughness, dimensional stability and impact strength.
Working hardness: 56-60 HRC.

**Applications**

Blanking tools, dies, punches, forming dies, embossing tools, coining tools, tableting punches, plug-in tools, trimming tools, cold shear knives, riveting pins, hand chisels, pneumatic chisels, centre punches, ejectors, woodworking tools.

**Tolerances****Standard values**

Delivery condition: maximum 229 HB
Chemical composition:

C	Si	Mn	P	S	Cr	V	W
0,55	0,7	0,15	0	0	0,9	0,1	1,7
0,65	1,0	0,45	0,03	0,03	1,2	0,2	2,2

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/S1-7

**AISI / SAE S1 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/S1

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2



1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13

1.2344 ESU
H13 ESR



ON REQUEST ...


... SAWN – MILLED – GROUND !

PREMIUM 1.2436 – AISI / SAE D6 (X210CrW12)

Precision flat steel without machining allowance, DIN 59350 [PFS]

Length: 500 mm

	THICKNESS [mm]									
	2,0	3,0	4,0	5,0	6,0	8,0	10,0	12,0	15,0	20,0
WIDTH	Available dimensions [mm]									
20,0	■	■	■	■	■	■	■	■	■	
25,0	■	■	■	■	■	■	■	■	■	■
30,0	■	■	■	■	■	■	■	■	■	■
40,0	■	■	■	■	■	■	■	■	■	■
50,0	■	■	■	■	■	■	■	■	■	■
60,0	■	■	■	■	■	■	■	■	■	■
80,0	■	■	■	■	■	■	■	■	■	■
100,0	■	■	■	■	■	■	■	■	■	■
125,0	■	■	■	■	■	■	■	■	■	■
150,0	■	■	■	■	■	■	■	■	■	■
200,0	■	■	■	■	■	■	■	■		

**Tolerances****Standard values**

Delivery condition: maximum 255 HB

Chemical composition:

C	Si	Mn	P	S	Cr	W
2,0	0,1	0,3	0	0	11,0	0,6
2,3	0,4	0,6	0,03	0,03	13,0	0,8

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**www.premium-steel.eu/D6-1**Technical properties**

Cold work steel with maximum wear resistance and cutting power (for plates: thickness up to 4 mm). Full hardenability, good dimensional stability, but medium toughness. Due to its tungsten content this steel grade has a higher tempering resistance and higher wear permanence compared to AISI / SAE 3 mod. Working hardness: 59-63 HRC.

**Applications**

Blanking tools, stamping tools, embossing tools, scraping tools, trimming tools, woodworking tools, drawing tools, press tools, stone moulds, sintered tools, machine knives, hammer cores, ring rollers, thread rolling dies, plastic moulds.

NAVIGATION/
STEEL GRADES1.2990 mod.
1.2990 mod.1.2842
O2/O11.2826
1.28261.2767
6F71.2767 ESU
6F7 ESR1.2738
P20+Ni1.2714
L61.2714+QT
L6+QT1.2709 ESU
1.2709 ESR1.2550
S1**1.2436
D6**1.2379
D21.2367
1.23671.2365
H101.2363
A21.2361
1.23611.2360
~ Chipper1.2358
1.23581.2344
H131.2344 ESU
H13 ESR**AISI / SAE D6 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/D6

via smartphone/tablet:




PREMIUM 1.2436 – AISI / SAE D6 (X210CrW12)

Precision flat steel with machining allowance [PFS/BA]

Length: 500 mm

	THICKNESS [mm]													
	2,2	3,2	4,2	5,2	6,2	8,2	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3
WIDTH	Available dimensions [mm]													
8,2						■								
10,3	■	■	■	■	■	■	■							
12,3								■						
15,3	■	■	■	■	■	■	■	■	■					
20,3	■	■	■	■	■	■	■	■	■	■				
25,3	■	■	■	■	■	■	■	■	■	■	■			
30,3	■	■	■	■	■	■	■	■	■	■	■	■		
40,3	■	■	■	■	■	■	■	■	■	■	■	■	■	
50,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■
60,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■
80,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■
100,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■
125,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■
150,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■
200,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■
250,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■
300,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values**

Delivery condition: maximum 255 HB
Chemical composition:

C	Si	Mn	P	S	Cr	W
2,0	0,1	0,3	0	0	11,0	0,6
2,3	0,4	0,6	0,03	0,03	13,0	0,8

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/D6-3

**Technical properties**

Cold work steel with maximum wear resistance and cutting power (for plates: thickness up to 4 mm). Full hardenability, good dimensional stability, but medium toughness. Due to its tungsten content this steel grade has a higher tempering resistance and higher wear permanence compared to AISI / SAE 3 mod. Working hardness: 59-63 HRC

**Applications**

Blanking tools, stamping tools, embossing tools, scraping tools, trimming tools, woodworking tools, drawing tools, press tools, stone moulds, sintered tools, machine knives, hammer cores, ring rollers, thread rolling dies, plastic moulds.

**AISI / SAE D6 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/D6

via smartphone/tablet:



PREMIUM 1.2436 – AISI / SAE D6 (X210CrW12)

Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm


	THICKNESS [mm]															
	2,2	3,2	4,2	5,2	6,2	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	40,3	50,3
WIDTH	Available dimensions [mm]															
8,2																
10,3																
12,3																
15,3																
16,3																
20,3																
25,3																
30,3																
32,3																
40,3																
50,3																
60,3																
63,3																
80,3																
100,3																
125,3																
150,3																
160,3																
175,3																
200,3																
250,3																
300,3																
315,3																

**Technical properties**

Cold work steel with maximum wear resistance and cutting power (for plates: thickness up to 4 mm). Full hardenability, good dimensional stability, but medium toughness. Due to its tungsten content this steel grade has a higher tempering resistance and higher wear permanence compared to AISI / SAE 3 mod. Working hardness: 59-63 HRC

**Applications**

Blanking tools, stamping tools, embossing tools, scraping tools, trimming tools, woodworking tools, drawing tools, press tools, stone moulds, sintered tools, machine knives, hammer cores, ring rollers, thread rolling dies, plastic moulds.

**Tolerances****Standard values**

Delivery condition: maximum 255 HB
Chemical composition:

C	Si	Mn	P	S	Cr	W
2,0	0,1	0,3	0	0	11,0	0,6
2,3	0,4	0,6	0,03	0,03	13,0	0,8

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/D6-4

**AISI / SAE D6 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/D6

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

**1.2436
D6**

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13

1.2344 ESU
H13 ESR

PREMIUM 1.2436 – AISI / SAE D6 (X210CrW12)**Hart-Präz® 250 [Hart]**

Length: 250 mm


	THICKNESS [mm]												
	2,2	2,7	3,2	3,7	4,2	4,7	5,2	6,2	7,2	8,2	9,2	10,2	12,2
WIDTH	Available dimensions [mm]												
250	■	■	■	■	■	■	■	■	■	■	■	■	■

Hart-Präz® 500 [Hart]

Length: 500 mm

	THICKNESS [mm]												
	2,2	2,7	3,2	3,7	4,2	4,7	5,2	6,2	7,2	8,2	9,2	10,2	12,2
WIDTH	Available dimensions [mm]												
250	■	■	■	■	■	■	■	■	■	■	■	■	■


Hardened dimensions are delivered with approx. 59 HRC, at least 2x tempered.

**NEW: Hart-Präz®****ALREADY HARDENED DIMENSIONS IN LENGTH OF 250 mm AND 500 mm !****Technical properties**

Cold work steel with maximum wear resistance and cutting power (for plates: thickness up to 4 mm). Full hardenability, good dimensional stability, but medium toughness. Due to its tungsten content this steel grade has a higher tempering resistance and higher wear permanence compared to AISI / SAE 3 mod. Working hardness: 59-63 HRC

**Applications**

Blanking tools, stamping tools, embossing tools, scraping tools, trimming tools, woodworking tools, drawing tools, press tools, stone moulds, sintered tools, machine knives, hammer cores, ring rollers, thread rolling dies, plastic moulds.

**Tolerances****Standard values**

Lieferzustand: ca. 59 HRC

Chemical composition:

C	Si	Mn	P	S	Cr	W
2,0	0,1	0,3	0	0	11,0	0,6
2,3	0,4	0,6	0,03	0,03	13,0	0,8

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**
www.premium-steel.eu/D6-11-H
**AISI / SAE D6 – all at a glance!**

Datasheets, online shop, ABRAMS STEEL GUIDE® for alternatives:

www.premium-steel.eu/D6

via smartphone/tablet:



PREMIUM 1.2436 – AISI / SAE D6 (X210CrW12)

Precision round steel with machining allowance [PRS/BA]

Specification: peeled / rough-turned

	LENGTH [mm]	
	500	1.000
Ø [mm]	Available dimensions [•]	
10,5	•	•
15,5	•	•
20,5	•	•
25,5	•	•
30,5	•	•
35,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
55,5	•	•
60,5	•	•
65,5		•
70,5		•
75,5		•
80,5		•
85,5		•
90,5		•
95,5		•
100,5		•


Larger diameters, up to 400,5 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Cold work steel with maximum wear resistance and cutting power (for plates: thickness up to 4 mm). Full hardenability, good dimensional stability, but medium toughness. Due to its tungsten content this steel grade has a higher tempering resistance and higher wear permanence compared to AISI / SAE 3 mod. Working hardness: 59-63 HRC

**Applications**

Blanking tools, stamping tools, embossing tools, scraping tools, trimming tools, woodworking tools, drawing tools, press tools, stone moulds, sintered tools, machine knives, hammer cores, ring rollers, thread rolling dies, plastic moulds.

**Tolerances****Standard values**

Delivery condition: maximum 255 HB
Chemical composition:

C	Si	Mn	P	S	Cr	W
2,0	0,1	0,3	0	0	11,0	0,6
2,3	0,4	0,6	0,03	0,03	13,0	0,8

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/D6-7

**AISI / SAE D6 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/D6

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

**1.2436
D6**

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13

1.2344 ESU
H13 ESR

PREMIUM 1.2379 – AISI / SAE D2 (X153CrMoV12)

Precision flat steel with machining allowance [PFS/BA]

Length: 500 mm

	THICKNESS [mm]																			
	2,2	3,2	4,2	5,2	6,2	8,2	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	63,3	70,3	80,3	90,3	100,3
WIDTH	Available dimensions [mm]																			
6,2					■															
8,2						■														
10,3	■	■	■	■	■	■	■													
12,3								■												
15,3	■	■	■	■	■	■	■	■	■											
20,3	■	■	■	■	■	■	■	■	■	■										
25,3	■	■	■	■	■	■	■	■	■	■	■									
30,3	■	■	■	■	■	■	■	■	■	■	■	■								
40,3	■	■	■	■	■	■	■	■	■	■	■	■	■							
50,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■						
60,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■						
80,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
100,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
125,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
150,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
200,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
250,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
300,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
500 *							■	■	■	■	■	■	■	■	■					

* Width and length sawn/black with +tol./-0 mm


**Technical properties**

Secondary-hardening, ledeburitic cold work steel, can be used for a wide range of applications. Low distortion, excellent wear resistance and good toughness. Temper-resistant, even at high hardening temperatures. In addition it can be nitrated without any reduction in hardness even for a cold work steel.

Working hardness: 57-62 HRC.

**Applications**

Blanking tools, precision cutting tools, dies, punches, thread rolling dies, broaches, milling cutters, press tools, shear knives, deep drawing dies, cold rollings, measuring tools, woodworking tools, cold pilger mandrels, plastic moulds.

**Tolerances****Standard values**

Delivery condition: maximum 255 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
1,45	0,1	0,2	0	0	11,0	0,7	0,7
1,6	0,6	0,6	0,03	0,03	13,0	1,0	1,0

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**
www.premium-steel.eu/D2-3
**AISI / SAE D2 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/D2

via smartphone/tablet:



PREMIUM 1.2379 – AISI / SAE D2 (X153CrMoV12)

Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm

	THICKNESS [mm]																			
	2,2	3,2	4,2	5,2	6,2	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	40,3	50,3	60,3	63,3	70,3	80,3
WIDTH	Available dimensions [mm]																			
6,2					■															
8,2						■														
10,3	■	■	■	■	■	■	■													
12,3								■												
15,3	■	■	■	■	■	■	■	■	■											
16,3										■										
20,3	■	■	■	■	■	■	■	■	■	■	■									
25,3	■	■	■	■	■	■	■	■	■	■	■	■								
30,3	■	■	■	■	■	■	■	■	■	■	■	■	■							
32,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■						
40,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■					
50,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
60,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
63,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
70,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
80,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
90,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
100,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
125,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
150,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
160,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
175,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
180,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
200,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
250,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
300,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
350,3								■	■	■	■	■	■	■	■	■	■			
400,3								■	■	■	■	■	■	■	■	■				
500 *								■	■	■		■	■	■	■	■	■			

* Width and length sawn/black with +tol./-0 mm


**Technical properties**

Secondary-hardening, ledeburitic cold work steel, can be used for a wide range of applications. Low distortion, excellent wear resistance and good toughness. Temper-resistant, even at high hardening temperatures. In addition it can be nitrated without any reduction in hardness even for a cold work steel.

Working hardness: 57-62 HRC.

**Applications**

Blanking tools, precision cutting tools, dies, punches, thread rolling dies, broaches, milling cutters, press tools, shear knives, deep drawing dies, cold rollings, measuring tools, woodworking tools, cold pilger mandrels, plastic moulds.

**Tolerances****Standard values**

Delivery condition: maximum 255 HB

Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
1,45	0,1	0,2	0	0	11,0	0,7	0,7
1,6	0,6	0,6	0,03	0,03	13,0	1,0	1,0

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**www.premium-steel.eu/D2-4**AISI / SAE D2 – all at a glance!**

Datasheets, online shop, ABRAMS STEEL GUIDE® for alternatives: www.premium-steel.eu/D2

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2990 mod.
1.2990 mod.1.2842
O2/O11.2826
1.28261.2767
6F71.2767 ESU
6F7 ESR1.2738
P20+Ni1.2714
L61.2714+QT
L6+QT1.2709 ESU
1.2709 ESR1.2550
S11.2436
D6**1.2379
D2**1.2367
1.23671.2365
H101.2363
A21.2361
1.23611.2360
~ Chipper1.2358
1.23581.2344
H131.2344 ESU
H13 ESR

PREMIUM 1.2379 – AISI / SAE D2 (X153CrMoV12)

Precision flat steel with machining allowance [PFS/BA]
Length: 200 mm

	THICKNESS [mm]							
	20,3	25,3	30,3	40,3	50,3	60,3	80,3	100,3
WIDTH	Available dimensions [mm]							
100,3	■	■	■	■	■	■	■	■
150,3	■	■	■	■	■	■	■	■
200,3	■	■	■	■	■	■	■	■

Precision flat steel with machining allowance [PFS/BA]
Length: 300 mm

	THICKNESS [mm]							
	20,3	25,3	30,3	40,3	50,3	60,3	80,3	100,3
WIDTH	Available dimensions [mm]							
100,3	47,90	57,90	67,90	85,90	105,90	120,90	166,90	187,90
150,3	75,90	85,90	100,90	125,90	153,90	182,90	243,90	283,90
200,3	104,90	122,90	141,90	166,90	210,90	250,90	333,90	366,90
250,3	127,90	147,90	170,90	204,90	258,90	302,90	356,90	406,90
300,3	147,90	177,90	197,90	244,90	307,90	364,90	474,90	520,90

SHORTER LENGTH: 200 mm, 300 mm, 400 mm and 600 mm !

Precision flat steel with machining allowance [PFS/BA]
Length: 400 mm

	THICKNESS [mm]							
	20,3	25,3	30,3	40,3	50,3	60,3	80,3	100,3
WIDTH	Available dimensions [mm]							
100,3	■	■	■	■	■	■	■	■
150,3	■	■	■	■	■	■	■	■
200,3	■	■	■	■	■	■	■	■
250,3	■	■	■	■	■	■	■	■
300,3	■	■	■	■	■	■	■	■
400,3	■	■	■	■	■	■		

Precision flat steel with machining allowance [PFS/BA]
Length: 600 mm


	THICKNESS [mm]							
	20,3	25,3	30,3	40,3	50,3	60,3	80,3	100,3
WIDTH	Available dimensions [mm]							
100,3	■	■	■	■	■	■	■	■
150,3	■	■	■	■	■	■	■	■
200,3	■	■	■	■	■	■	■	■
250,3	■	■	■	■	■	■	■	■
300,3	■	■	■	■	■	■	■	■
400,3	■	■	■	■	■	■		

**Technical properties**

Secondary-hardening, ledeburitic cold work steel, can be used for a wide range of applications. Low distortion, excellent wear resistance and good toughness. Temper-resistant, even at high hardening temperatures. In addition it can be nitrated without any reduction in hardness even for a cold work steel.
Working hardness: 57-62 HRC.

**Applications**

Blanking tools, precision cutting tools, dies, punches, thread rolling dies, broaches, milling cutters, press tools, shear knives, deep drawing dies, cold rollings, measuring tools, woodworking tools, cold pilger mandrels, plastic moulds.

**Tolerances****Standard values**

Delivery condition: maximum 255 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
1,45	0,1	0,2	0	0	11,0	0,7	0,7
1,6	0,6	0,6	0,03	0,03	13,0	1,0	1,0

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/D2-200
www.premium-steel.eu/D2-300
www.premium-steel.eu/D2-400
www.premium-steel.eu/D2-600

**AISI / SAE D2 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/D2

via smartphone / tablet:



PREMIUM 1.2379 – AISI / SAE D2 (X153CrMoV12)

€co-Präz® 500 [€co]

Length: 500 mm

	THICKNESS [mm]										
	10,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	
WIDTH	Available dimensions [mm]										
103	■	■	■	■	■	■	■	■	■	■	■
123	■	■	■	■	■	■	■	■	■	■	■
143	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■
323	■	■	■	■	■	■	■	■	■	■	■
343	■	■	■	■	■	■	■	■	■	■	■
353	■	■	■	■	■	■	■	■	■	■	■
363	■	■	■	■	■	■	■	■	■	■	■
383	■	■	■	■	■	■	■	■	■	■	■
403	■	■	■	■	■	■	■	■	■	■	■
423	■	■	■	■	■	■	■	■	■	■	■
443	■	■	■	■	■	■	■	■	■	■	■
453	■	■	■	■	■	■	■	■	■	■	■
463	■	■	■	■	■	■	■	■	■	■	■
483	■	■	■	■	■	■	■	■	■	■	■
503	■	■	■	■	■	■	■	■	■	■	■


**Technical properties**

Secondary-hardening, ledeburitic cold work steel, can be used for a wide range of applications. Low distortion, excellent wear resistance and good toughness. Temper-resistant, even at high hardening temperatures. In addition it can be nitrated without any reduction in hardness even for a cold work steel.

Working hardness: 57-62 HRC.

**Applications**

Blanking tools, precision cutting tools, dies, punches, thread rolling dies, broaches, milling cutters, press tools, shear knives, deep drawing dies, cold rollings, measuring tools, woodworking tools, cold pilger mandrels, plastic moulds.

**Tolerances****Standard values**

Delivery condition: maximum 255 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
1,45	0,1	0,2	0	0	11,0	0,7	0,7
1,6	0,6	0,6	0,03	0,03	13,0	1,0	1,0

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/D2-5

**AISI / SAE D2 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/D2

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

**1.2379
D2**

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13

1.2344 ESU
H13 ESR

PREMIUM 1.2379 – AISI / SAE D2 (X153CrMoV12)**Hart-Präz® 250 [Hart]**

Length: 250 mm


	THICKNESS [mm]													
	2,2	2,7	3,2	3,7	4,2	4,7	5,2	6,2	7,2	8,2	9,2	10,2	12,2	14,2
WIDTH	Available dimensions [mm]													
250	■	■	■	■	■	■	■	■	■	■	■	■	■	■

Hart-Präz® 500 [Hart]

Length: 500 mm

	THICKNESS [mm]													
	2,2	2,7	3,2	3,7	4,2	4,7	5,2	6,2	7,2	8,2	9,2	10,2	12,2	14,2
WIDTH	Available dimensions [mm]													
250	■	■	■	■	■	■	■	■	■	■	■	■	■	■

Hardened dimensions are delivered with approx. 57 HRC, at least 2x tempered.


**NEW: Hart-Präz®****ALREADY HARDENED DIMENSIONS IN LENGTH OF 250 mm AND 500 mm !****Technical properties**

Secondary-hardening, ledeburitic cold work steel, can be used for a wide range of applications. Low distortion, excellent wear resistance and good toughness. Temper-resistant, even at high hardening temperatures. In addition it can be nitrated without any reduction in hardness even for a cold work steel.

Working hardness: 57-62 HRC.

**Applications**

Blanking tools, precision cutting tools, dies, punches, thread rolling dies, broaches, milling cutters, press tools, shear knives, deep drawing dies, cold rollings, measuring tools, woodworking tools, cold pilger mandrels, plastic moulds.

**Tolerances****Standard values**

Delivery condition: approx. 57 HRC

Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
1,45	0,1	0,2	0	0	11,0	0,7	0,7
1,6	0,6	0,6	0,03	0,03	13,0	1,0	1,0

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**www.premium-steel.eu/D2-11-H**AISI / SAE D2 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/D2

via smartphone/tablet:



PREMIUM 1.2379 – AISI / SAE D2 (X153CrMoV12)


Precision round steel without machining allowance [PRS]
Specification: bright ground, ISO h8

Ø [mm]	LENGTH [mm]
	1.000
Available dimensions [•]	
6,0	•
8,0	•
10,0	•
12,0	•
15,0	•
20,0	•
25,0	•

Precision round steel with machining allowance [PRS/BA]
Specification: peeled /rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
Available dimensions [•]		
10,5	•	•
15,5	•	•
20,5	•	•
25,5	•	•
30,5	•	•
35,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
55,5	•	•
60,5	•	•
65,5		•
70,5		•
75,5		•
80,5		•
85,5		•
90,5		•
95,5		•
100,5		•

Larger diameters, up to 755,5 mm, and different lengths (e.g. round blanks) available on request!

**Tolerances****Standard values**

Delivery condition: maximum 255 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
1,45	0,1	0,2	0	0	11,0	0,7	0,7
1,6	0,6	0,6	0,03	0,03	13,0	1,0	1,0

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

[PRS]

www.premium-steel.eu/D2-6

[PRS/BA]

www.premium-steel.eu/D2-7

**Technical properties**

Secondary-hardening, ledeburitic cold work steel, can be used for a wide range of applications. Low distortion, excellent wear resistance and good toughness. Temper-resistant, even at high hardening temperatures. In addition it can be nitrated without any reduction in hardness even for a cold work steel.

Working hardness: 57-62 HRC.

**Applications**

Blanking tools, precision cutting tools, dies, punches, thread rolling dies, broaches, milling cutters, press tools, shear knives, deep drawing dies, cold rollings, measuring tools, woodworking tools, cold pilger mandrels, plastic moulds.

**AISI / SAE D2 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/D2

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

**1.2379
D2**

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13

1.2344 ESU
H13 ESR


PREMIUM 1.2379 – AISI / SAE D2 (X153CrMoV12)Erosion block/EDM block/annealed [EB]

Specification: all-sides machined (milled/ground)/grain structure is vertically directed in relation to base surface

		THICKNESS [mm]												
		15,0	20,0	25,0	30,0	40,0	50,0	60,0	70,0	80,0	90,0	100,0	120,0	150,0
	SQUARE	Available dimensions [mm]												
	80,3	■	■	■	■	■	■	■	■	■	■	■	■	■
	100,3	■	■	■	■	■	■	■	■	■	■	■	■	■
	120,3	■	■	■	■	■	■	■	■	■	■	■	■	■
	150,3	■	■	■	■	■	■	■	■	■	■	■	■	■
	200,3	■	■	■	■	■	■	■	■	■	■	■	■	■
	250,3	■	■	■	■	■	■	■	■	■	■	■	■	■
	300,3	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances**

T +0,25 / -0 mm

**Standard values**

Delivery condition: maximum 255 HB

Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
1,45	0,1	0,2	0	0	11,0	0,7	0,7
1,6	0,6	0,6	0,03	0,03	13,0	1,0	1,0

**If you need customised dimensions -**


Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**www.premium-steel.eu/D2-9-G**Technical properties**

Secondary-hardening, ledeburitic cold work steel, can be used for a wide range of applications. Low distortion, excellent wear resistance and good toughness. Temper-resistant, even at high hardening temperatures. In addition it can be nitrated without any reduction in hardness even for a cold work steel.

Working hardness: 57-62 HRC.

**Applications**

Blanking tools, precision cutting tools, dies, punches, thread rolling dies, broaches, milling cutters, press tools, shear knives, deep drawing dies, cold rollings, measuring tools, woodworking tools, cold pilger mandrels, plastic moulds.

**AISI / SAE D2 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/D2

via smartphone/tablet:




PREMIUM 1.2379 – AISI / SAE D2 (X153CrMoV12)

Erosion block/EDM block/hardened [EB]

Specification: all-sides machined (milled/ground)/grain structure is vertically directed in relation to base surface

	THICKNESS [mm]													
	15,0	20,0	25,0	30,0	40,0	50,0	60,0	70,0	80,0	90,0	100,0	120,0	150,0	
SQUARE	Available dimensions [■]													
80,3	■	■	■	■	■	■	■	■	■	■	■	■	■	
100,3	■	■	■	■	■	■	■	■	■	■	■	■	■	
120,3	■	■	■	■	■	■	■	■	■	■	■	■	■	
150,3	■	■	■	■	■	■	■	■	■	■	■	■	■	
200,3	■	■	■	■	■	■	■	■	■	■	■	■	■	
250,3	■	■	■	■	■	■	■	■	■	■	■	■	■	
300,3	■	■	■	■	■	■	■	■	■	■	■	■	■	

Hardened erosion blocks are tempered at least three times at approx. 61 HRC.

**Technical properties**


Secondary-hardening, ledeburitic cold work steel, can be used for a wide range of applications. Low distortion, excellent wear resistance and good toughness. Temper-resistant, even at high hardening temperatures. In addition it can be nitrated without any reduction in hardness even for a cold work steel. Working hardness: 57-62 HRC.

**Applications**

Blanking tools, precision cutting tools, dies, punches, thread rolling dies, broaches, milling cutters, press tools, shear knives, deep drawing dies, cold rollings, measuring tools, woodworking tools, cold pilger mandrels, plastic moulds.

**Tolerances**

T +0,25 / -0 mm

**Standard values**

Delivery condition: approx. 61 HRC

Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
1,45	0,1	0,2	0	0	11,0	0,7	0,7
1,6	0,6	0,6	0,03	0,03	13,0	1,0	1,0

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**
www.premium-steel.eu/D2-9-H
**AISI / SAE D2 – all at a glance!**

Datasheets, online shop, ABRAMS STEEL GUIDE® for alternatives: www.premium-steel.eu/D2

via smartphone/tablet:


NAVIGATION/
STEEL GRADES1.2990 mod.
1.2990 mod.1.2842
O2/O11.2826
1.28261.2767
6F71.2767 ESU
6F7 ESR1.2738
P20+Ni1.2714
L61.2714+QT
L6+QT1.2709 ESU
1.2709 ESR1.2550
S11.2436
D6**1.2379
D2**1.2367
1.23671.2365
H101.2363
A21.2361
1.23611.2360
~ Chipper1.2358
1.23581.2344
H131.2344 ESU
H13 ESR

PREMIUM 1.2367 – AISI / SAE 1.2367 (X38CrMoV5-3)

€co-Präz® 500 [€co]

Length: 500 mm

	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values**

Delivery condition: maximum 229 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,35	0,3	0,3	0	0	4,8	2,7	0,4
0,4	0,5	0,5	0,03	0,02	5,2	3,2	0,6

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/2367-5

**Technical properties**

Hot work steel with excellent toughness, excellent heat resistance and excellent tempering resistance. Good hardenability with high warp-resistance. Can be cooled with water.
Working hardness: 50-54 HRC.

**Applications**

Dies, die inserts, extrusion presses, hot extrusion tools, die casting tools, slides, press mandrels, intermediate sleeves, die holders, profiling dies, profile mandrels, block receivers, hot shear knives, light metal processing, plastic moulds.

**AISI / SAE 1.2367 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2367

via smartphone / tablet:



PREMIUM 1.2367 – AISI / SAE 1.2367 (X38CrMoV5-3)

Precision round steel with machining allowance [PRS/BA]

Specification: peeled / rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
25,5	●	●
30,5	●	●
35,5	●	●
40,5	●	●
45,5	●	●
50,5	●	●
55,5	●	●
60,5	●	●
65,5		●
70,5		●
75,5		●
80,5		●
90,5		●
95,5		●
100,5		●


Larger diameters, up to 450,5 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Hot work steel with excellent toughness, excellent heat resistance and excellent tempering resistance. Good hardenability with high warp-resistance. Can be cooled with water.
Working hardness: 50-54 HRC.

**Applications**

Dies, die inserts, extrusion presses, hot extrusion tools, die casting tools, slides, press mandrels, intermediate sleeves, die holders, profiling dies, profile mandrels, block receivers, hot shear knives, light metal processing, plastic moulds.

**Tolerances****Standard values**

Delivery condition: maximum 229 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,35	0,3	0,3	0	0	4,8	2,7	0,4
0,4	0,5	0,5	0,03	0,02	5,2	3,2	0,6

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/2367-7

**AISI / SAE 1.2367 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2367

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13


1.2344 ESU
H13 ESR

PREMIUM 1.2365 – AISI / SAE H10 (32CrMoV12-28)

€co-Präz® 500 [€co]

Length: 500 mm

	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values**

Delivery condition: maximum 229 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,28	0,1	0,15	0	0	2,7	2,5	0,4
0,35	0,4	0,45	0,03	0,02	3,2	3,0	0,7

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/H10-5

**Technical properties**

Hot work steel with high toughness, heat resistance and tempering resistance. Air-hardening steel grade with good thermal conductivity. Can be cooled with water. Working hardness: 50-52 HRC.

**Applications**

Extrusion presses, brass casting, press tools, die inserts, die casting moulds, plastic moulds, recipient bushes, pressure dies, press mandrels, tube extrusion mandrels, piecer plugs, press dies, block receivers, screw production, nut production, rivet production, bolts production, hot shear knives.

**AISI / SAE H10 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/H10

via smartphone/tablet:



PREMIUM 1.2365 – AISI / SAE H10 (32CrMoV12-28)

Precision round steel with machining allowance [PRS/BA]

Specification: peeled / rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
	Available dimensions [•]	
25,5	•	•
30,5	•	•
35,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
55,5	•	•
60,5	•	•
65,5		•
70,5		•
75,5		•
80,5		•
85,5		•
90,5		•
95,5		•
100,5		•


Larger diameters, up to 350,5 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Hot work steel with high toughness, heat resistance and tempering resistance. Air-hardening steel grade with good thermal conductivity. Can be cooled with water. Working hardness: 50-52 HRC.

**Applications**

Extrusion presses, brass casting, press tools, die inserts, die casting moulds, plastic moulds, recipient bushes, pressure dies, press mandrels, tube extrusion mandrels, piecer plugs, press dies, block receivers, screw production, nut production, rivet production, bolts production, hot shear knives.

**Tolerances****Standard values**

Delivery condition: maximum 229 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,28	0,1	0,15	0	0	2,7	2,5	0,4
0,35	0,4	0,45	0,03	0,02	3,2	3,0	0,7

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/H10-7

**AISI / SAE H10 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/H10

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

**1.2365
H10**

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13


1.2344 ESU
H13 ESR

PREMIUM 1.2363 – AISI / SAE A2 (X100CrMoV5-1)

Precision flat steel with machining allowance [PFS/BA]

Length: 500 mm

	THICKNESS [mm]																	
	4,2	6,2	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	40,3	50,3	60,3	63,3	70,3	80,3	100,3
WIDTH	Available dimensions [mm]																	
10,3				■														
12,3					■													
16,3							■											
20,3								■										
25,3	■	■	■	■	■	■	■	■	■									
30,3	■	■	■	■	■	■	■	■		■								
32,3	■	■	■	■	■		■	■	■		■							
40,3	■	■	■	■	■	■	■	■	■	■	■	■						
50,3	■	■	■	■	■	■	■	■	■	■	■	■	■					
60,3		■	■	■	■	■		■	■	■		■		■				
63,3		■	■	■	■		■	■	■		■	■	■		■			
80,3		■	■	■	■	■	■	■	■	■	■	■	■		■		■	
100,3		■	■	■	■	■	■	■	■	■	■	■	■		■	■	■	■
125,3			■	■	■	■	■	■	■	■	■	■	■		■	■	■	
150,3			■	■	■	■		■	■	■		■			■	■		
160,3			■	■	■		■	■	■		■	■	■		■	■		
200,3				■	■	■	■	■	■	■	■	■	■		■	■		
250,3							■	■	■	■	■	■	■		■	■		
315,3								■	■		■	■	■					
400,3									■		■	■	■					

**Tolerances****Standard values**

Delivery condition: maximum 241 HB

Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,95	0,1	0,4	0	0	4,8	0,9	0,15
1,05	0,4	0,8	0,03	0,03	5,5	1,2	0,35

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**www.premium-steel.eu/A2-3**Technical properties**

Air hardening cold work steel, good machinability, high wear resistance and improved toughness (reduced occurrence of hard carbides with about 5% chromium compared to 12% chromium in ledeburites AISI / SAE D2, AISI / SAE D6, AISI / SAE D3 mod.). Good dimensional stability during heat treatment and easily repairable through welding. Working hardness: 58-62 HRC.

**Applications**

Blanking tools, stamping tools, dies, punches, trimming tools, cutting tools, thread rolling tools, thread rolling dies, shear knives, circular shear knives, cold pilger mandrels, cold stamping tools, plastic moulds.

**AISI / SAE A2 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/A2

via smartphone / tablet:



PREMIUM 1.2363 – AISI / SAE A2 (X100CrMoV5-1)

Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm


	THICKNESS [mm]																	
	4,2	6,2	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	40,3	50,3	60,3	63,3	70,3	80,3	100,3
WIDTH	Available dimensions [mm]																	
10,3				■														
12,3					■													
16,3							■											
20,3								■										
25,3	■	■	■	■	■	■	■	■	■									
30,3	■	■	■	■	■	■	■	■		■								
32,3	■	■	■	■	■		■	■	■		■							
40,3	■	■	■	■	■	■	■	■	■	■	■	■						
50,3	■	■	■	■	■	■	■	■	■	■	■	■	■					
60,3		■	■	■	■	■		■	■	■		■		■				
63,3		■	■	■	■		■	■	■		■	■	■		■			
80,3		■	■	■	■	■	■	■	■	■	■	■	■		■		■	
100,3		■	■	■	■	■	■	■	■	■	■	■	■		■	■	■	■
125,3			■	■	■	■	■	■	■	■	■	■	■		■	■	■	
150,3			■	■	■	■		■	■	■		■			■	■		
160,3			■	■	■		■	■	■		■	■	■		■	■		
200,3				■	■	■	■	■	■	■	■	■	■		■	■		
250,3							■	■	■	■	■	■	■		■	■		
315,3								■	■		■	■	■					
400,3									■		■	■	■					
600,3				■	■													

**Technical properties**

Air hardening cold work steel, good machinability, high wear resistance and improved toughness (reduced occurrence of hard carbides with about 5% chromium compared to 12% chromium in ledeburites AISI / SAE D2, AISI / SAE D6, AISI / SAE D3 mod.). Good dimensional stability during heat treatment and easily repairable through welding. Working hardness: 58-62 HRC.

**Applications**

Blanking tools, stamping tools, dies, punches, trimming tools, cutting tools, thread rolling tools, thread rolling dies, shear knives, circular shear knives, cold pilger mandrels, cold stamping tools, plastic moulds.

**Tolerances****Standard values**

Delivery condition: maximum 241 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,95	0,1	0,4	0	0	4,8	0,9	0,15
1,05	0,4	0,8	0,03	0,03	5,5	1,2	0,35

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/A2-4

**AISI / SAE A2 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/A2

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13

1.2344 ESU
H13 ESR

ABRAMS®

TOOL STEEL I

TOOL STEEL II

HIGH SPEED STEEL

STAINLESS STEEL
corrosion resistant / acid resistant

HEAT-TREATABLE STEEL,
CASE HARDENING- &
NITRIDING STEEL

INFORMATION



PRECISION ROUND STEEL WITH MACHINING ALLOWANCE – PEELED / ROUGH TURNED!

ABRAMS![®]
PREMIUM STEEL

PREMIUM 1.2363 – AISI / SAE A2 (X100CrMoV5-1)

Precision round steel with machining allowance [PRS/BA]

Specification: peeled / rough-turned

	LENGTH [mm]	
	500	1.000
Ø [mm]	Available dimensions [•]	
20,5	•	•
30,5	•	•
35,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
55,5	•	•
60,5	•	•
65,5		•
70,5		•
75,5		•
80,5		•
85,5		•
90,5		•
95,5		•
100,5		•


Larger diameters, up to 350,5 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Air hardening cold work steel, good machinability, high wear resistance and improved toughness (reduced occurrence of hard carbides with about 5% chromium compared to 12% chromium in ledeburites AISI / SAE D2, AISI / SAE D6, AISI / SAE D3 mod.). Good dimensional stability during heat treatment and easily repairable through welding. Working hardness: 58-62 HRC.

**Applications**

Blanking tools, stamping tools, dies, punches, trimming tools, cutting tools, thread rolling tools, thread rolling dies, shear knives, circular shear knives, cold pilger mandrels, cold stamping tools, plastic moulds.

**Tolerances****Standard values**

Delivery condition: maximum 241 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,95	0,1	0,4	0	0	4,8	0,9	0,15
1,05	0,4	0,8	0,03	0,03	5,5	1,2	0,35

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/A2-7

**AISI / SAE A2 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/A2

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

**1.2363
A2**

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13

1.2344 ESU
H13 ESR



FASTEST POSSIBLE DELIVERY !



ABRAMS!
PREMIUM STEEL

PREMIUM 1.2361 – AISI / SAE 1.2361 (X91CrMoV18)

Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm

	THICKNESS [mm]																	
	3,2	4,2	5,2	6,2	8,2	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3
WIDTH	Available dimensions [mm]																	
10,3						■												
12,3							■											
15,3								■										
20,3	■	■	■	■	■	■	■	■	■									
25,3	■	■	■	■	■	■	■	■	■	■								
30,3	■	■	■	■	■	■	■	■	■	■	■							
40,3	■	■	■	■	■	■	■	■	■	■	■	■						
50,3	■	■	■	■	■	■	■	■	■	■	■	■	■					
60,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
70,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
80,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
90,3					■	■	■	■	■	■	■	■	■	■	■	■	■	
100,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
120,3						■	■	■	■	■	■	■	■	■	■	■		■
150,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
200,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		■
250,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■		■		■
300,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■		■		■
500*					■	■	■	■	■	■	■	■	■	■	■	■		■


* Width and length sawn/black with +tol./-0 mm

**Technical properties**

Corrosion resistant martensitic chromium steel (approx. 18% Cr) for cold work. Achieves, through heat treatment, an unusually high degree of hardness and wear resistance. Polishable to a long lasting high gloss. Working hardness: 53-58 HRC.

**Applications**

Cutting tools, knives, knife blades, cutlery, guide rails, wear parts, perforated discs, screw elements, pump shafts, scale pans, horizontal cutting, surgical instruments, plastic moulds, injection nozzles, roller bearings, ball bearings, mechanical engineering, food industry, building industry.

**Tolerances****Standard values**

Delivery condition: maximum 265 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni	V	Cu
0,86	0	0	0	0	17,0	0,9	0	0,07	0
0,96	1,0	1,0	0,045	0,03	19,0	1,3	0,3	0,12	0,3

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/2361-4

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13

1.2344 ESU
H13 ESR

**AISI / SAE 1.2361 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2361


via smartphone/tablet:



PREMIUM 1.2361 – AISI / SAE 1.2361 (X91CrMoV18)**€co-Präz® 300 [€co]**

Length: 300 mm

	THICKNESS [mm]																		
	2,3	3,3	4,3	5,3	6,3	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3
WIDTH	Available dimensions [mm]																		
33	■	■	■	■	■	■	■	■	■	■	■	■							
43	■	■	■	■	■	■	■	■	■	■	■	■	■						
53	■	■	■	■	■	■	■	■	■	■	■	■	■	■					
63	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
73	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
83	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
93	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values**

Delivery condition: maximum 265 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni	V	Cu
0,86	0	0	0	0	17,0	0,9	0	0,07	0
0,96	1,0	1,0	0,045	0,03	19,0	1,3	0,3	0,12	0,3

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/2361-3-5

**Technical properties**

Corrosion resistant martensitic chromium steel (approx. 18% Cr) for cold work. Achieves, through heat treatment, an unusually high degree of hardness and wear resistance. Polishable to a long lasting high gloss. Working hardness: 53-58 HRC.

**Applications**

Cutting tools, knives, knife blades, cutlery, guide rails, wear parts, perforated discs, screw elements, pump shafts, scale pans, horizontal cutting, surgical instruments, plastic moulds, injection nozzles, roller bearings, ball bearings, mechanical engineering, food industry, building industry.

**AISI / SAE 1.2361 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2361

via smartphone/tablet:



PREMIUM 1.2361 – AISI / SAE 1.2361 (X91CrMoV18)

€co-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]																		
	2,3	3,3	4,3	5,3	6,3	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3
WIDTH	Available dimensions [mm]																		
33	■	■	■	■	■	■	■	■	■	■	■	■							
43	■	■	■	■	■	■	■	■	■	■	■	■	■						
53	■	■	■	■	■	■	■	■	■	■	■	■	■	■					
63	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
73	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
83	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
93	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
323	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
343	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
353	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
363	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
383	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
403	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
423	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
443	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
453	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
463	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
483	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
503	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Corrosion resistant martensitic chromium steel (approx. 18% Cr) for cold work. Achieves, through heat treatment, an unusually high degree of hardness and wear resistance. Polishable to a long lasting high gloss. Working hardness: 53-58 HRC.

**Applications**

Cutting tools, knives, knife blades, cutlery, guide rails, wear parts, perforated discs, screw elements, pump shafts, scale pans, horizontal cutting, surgical instruments, plastic moulds, injection nozzles, roller bearings, ball bearings, mechanical engineering, food industry, building industry.

**Tolerances****Standard values**

Delivery condition: maximum 265 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni	V	Cu
0,86	0	0	0	0	17,0	0,9	0	0,07	0
0,96	1,0	1,0	0,045	0,03	19,0	1,3	0,3	0,12	0,3

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/2361-5-5

**AISI / SAE 1.2361 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2361

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13

1.2344 ESU
H13 ESR

PREMIUM 1.2361 – AISI / SAE 1.2361 (X91CrMoV18)**Hart-Präz® 250 [Hart]**

Length: 250 mm


	THICKNESS [mm]												
	2,2	2,7	3,2	3,7	4,2	4,7	5,2	6,2	7,2	8,2	9,2	10,2	12,2
WIDTH	Available dimensions [mm]												
250	■	■	■	■	■	■	■	■	■	■	■	■	■

Hart-Präz® 500 [Hart]

Length: 500 mm

	THICKNESS [mm]												
	2,2	2,7	3,2	3,7	4,2	4,7	5,2	6,2	7,2	8,2	9,2	10,2	12,2
WIDTH	Available dimensions [mm]												
250	■	■	■	■	■	■	■	■	■	■	■	■	■


Hardened dimensions are delivered with approx. 53 HRC, at least 2x tempered.

**Technical properties**

Corrosion resistant martensitic chromium steel (approx. 18% Cr) for cold work. Achieves, through heat treatment, an unusually high degree of hardness and wear resistance. Polishable to a long lasting high gloss. Working hardness: 53-58 HRC.

**Applications**

Cutting tools, knives, knife blades, cutlery, guide rails, wear parts, perforated discs, screw elements, pump shafts, scale pans, horizontal cutting, surgical instruments, plastic moulds, injection nozzles, roller bearings, ball bearings, mechanical engineering, food industry, building industry.

**Tolerances****Standard values**

Delivery condition: approx. 53 HRC
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni	V	Cu
0,86	0	0	0	0	17,0	0,9	0	0,07	0
0,96	1,0	1,0	0,045	0,03	19,0	1,3	0,3	0,12	0,3

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/2361-11-H

**AISI / SAE 1.2361 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2361

via smartphone/tablet:



PREMIUM 1.2361 – AISI / SAE 1.2361 (X91CrMoV18)


Precision round steel without machining allowance [PRS]
Specification: bright drawn/ground, ISO h9

Ø [mm]	LENGTH [mm]
	1.000
Available dimensions [•]	
10,0	•
12,0	•
14,0	•
15,0	•
16,0	•
18,0	•
20,0	•
25,0	•
30,0	•
35,0	•
40,0	•
45,0	•
50,0	•

Precision round steel with machining allowance [PRS/BA]
Specification: peeled / rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
Available dimensions [•]		
20,0	•	•
25,0	•	•
30,0	•	•
35,0	•	•
40,0	•	•
45,0	•	•
50,0	•	•
55,0	•	•
60,0	•	•
65,0		•
70,0		•
75,0		•
80,0		•
85,0		•
90,0		•
95,0		•
100,0		•

Larger diameters, up to 405,5 mm, and different lengths (e.g. round blanks) available on request!

**Tolerances****Standard values**

Delivery condition: maximum 265 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni	V	Cu
0,86	0	0	0	0	17,0	0,9	0	0,07	0
0,96	1,0	1,0	0,045	0,03	19,0	1,3	0,3	0,12	0,3

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop [PRS]**

www.premium-steel.eu/2361-6

[PRS/BA]

www.premium-steel.eu/2361-7

**Technical properties**

Corrosion resistant martensitic chromium steel (approx. 18% Cr) for cold work. Achieves, through heat treatment, an unusually high degree of hardness and wear resistance. Polishable to a long lasting high gloss. Working hardness: 53-58 HRC.

**Applications**

Cutting tools, knives, knife blades, cutlery, guide rails, wear parts, perforated discs, screw elements, pump shafts, scale pans, horizontal cutting, surgical instruments, plastic moulds, injection nozzles, roller bearings, ball bearings, mechanical engineering, food industry, building industry.

**AISI / SAE 1.2361 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2361

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13

1.2344 ESU
H13 ESR

PREMIUM 1.2360/1.2360 mod. – AISI / SAE ~ CHIPPER/~ CHIPPER mod. (X48CrMoV8-1-1/X48CrMoV8-1)**€co-Präz® 500 [€co]**

Length: 500 mm

		THICKNESS [mm]																			
		2,3	3,3	4,3	5,3	6,3	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	
WIDTH	Available dimensions [mm]																				
33	■	■	■	■	■	■	■	■	■	■	■	■	■								
43	■	■	■	■	■	■	■	■	■	■	■	■	■	■							
53	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■						
63	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■					
73	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
83	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
93	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
323	■	■	■	■	■																
343	■	■	■	■	■																
353	■	■	■	■	■																
363	■	■	■	■	■																
383	■	■	■	■	■																
403	■	■	■	■	■																
423	■	■	■	■	■																
443	■	■	■	■	■																
453	■	■	■	■	■																
463	■	■	■	■	■																
483	■	■	■	■	■																
503	■	■	■	■	■																

Thickness 2,3 up to 6,3 mm will be delivered as
Chipper-Knife-Steel (reduced content of vanadium - ap-
prox. 0,5 % V - in order to increase the toughness
for your application).


Thickness 2,3 up to 6,3 mm will be delivered as
Chipper-Knife-Steel (reduced content of vanadium - approx. 0,5 % V - in order to increase the toughness for your application).

**Technical properties**

Very robust cold work steel which can be used for a wide range of applications. Has a good through-hardening and high toughness (reduced occurrence of hard carbides with about 8% chromium compared to 12% chromium in AISI / SAE D2, AISI / SAE D6, AISI / SAE D3 mod.). High cutting power, high wear resistance as well as excellent tempering resistance. Working hardness: 50-60 HRC.

**Applications**

Blanking tools, stamping tools, embossing tools, forming dies, press dies, die inserts, extrusion dies, reinforcements, cold extrusion tools, tube tools, cutting tools, industrial knives, wood chipping knives, veneer knives.

**Tolerances****Standard values (1.2360/~Chipper)**

Delivery condition: maximum 250 HB
 Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,45	0,7	0,35	0	0	7,3	1,3	1,3
0,5	0,9	0,45	0,02	0,005	7,8	1,5	1,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
 On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
 E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/Chipper-5

**AISI / SAE ~Chipper – all at a glance!**

Datasheets, online shop,
 ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/Chipper

via smartphone/tablet:



PREMIUM 1.2360/1.2360 mod. – AISI / SAE ~ CHIPPER/~ CHIPPER mod. (X48CrMoV8-1-1/X48CrMoV8-1)

Precision round steel [PRS/BA] 1.2360/~Chipper
Specification: peeled / rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
	Available dimensions [•]	
26,0	•	•
31,0	•	•
36,0	•	•
40,0	•	•
55,0	•	•
65,0		•
75,0		•
90,0		•
95,0		•
100,0		•


Larger diameters, up to 285,0 mm, and different lengths (e.g. round blanks) available on request!

Precision round steel with machining allowance [PRS/BA] 1.2360 mod./~Chipper mod.
Specification: peeled / rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
	Available dimensions [•]	
32,4	•	•
40,4	•	•
50,4	•	•
63,5	•	•
70,5		•
80,5		•
90,5		•
100,5		•

Larger diameters, up to 322,5 mm, and different lengths (e.g. round blanks) available on request!

This specification will be delivered as Chipper-Knife-Steel (reduced content of vanadium - approx. 0,5% V - in order to increase the toughness for your application).

**Tolerances****Standard values (1.2360/~Chipper)**

Delivery condition: maximum 250 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,45	0,7	0,35	0	0	7,3	1,3	1,3
0,5	0,9	0,45	0,02	0,005	7,8	1,5	1,5

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

[PRS/BA] 1.2360/~Chipper

www.premium-steel.eu/Chipper-7

[PRS/BA] 1.2360 mod./~Chipper mod.

www.premium-steel.eu/Chippermod-7

**Technical properties**

Very robust cold work steel which can be used for a wide range of applications. Has a good through-hardenability and high toughness (reduced occurrence of hard carbides with about 8% chromium compared to 12% chromium in AISI / SAE D2, AISI / SAE D6, AISI / SAE D3 mod.). High cutting power, high wear resistance as well as excellent tempering resistance. Working hardness: 50-60 HRC.

**Applications**

Blanking tools, stamping tools, embossing tools, forming dies, press dies, die inserts, extrusion dies, reinforcements, cold extrusion tools, tube tools, cutting tools, industrial knives, wood chipping knives, veneer knives.

**AISI / SAE ~Chipper – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/Chipper

via smartphone/tablet:



1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13


1.2344 ESU
H13 ESR

PREMIUM 1.2358 – AISI / SAE 1.2358 (60CrMoV18-5)

€co-Präz® 300 [€co]

Length: 300 mm

	THICKNESS [mm]																	
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3	150,3	
WIDTH	Available dimensions [mm]																	
33	■	■	■	■	■	■	■											
43	■	■	■	■	■	■	■	■										
53	■	■	■	■	■	■	■	■	■									
63	■	■	■	■	■	■	■	■	■	■								
73	■	■	■	■	■	■	■	■	■	■	■							
83	■	■	■	■	■	■	■	■	■	■	■	■						
93	■	■	■	■	■	■	■	■	■	■	■	■	■					
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	

**Tolerances****Standard values**

Delivery condition: maximum 325 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,58	0,2	0,7	0	0	4,3	0,4	0,2
0,62	0,5	0,9	0,03	0,03	4,7	0,6	0,3

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/2358-3-5

**Technical properties**

Tempered tool steel (with focus on cold work). High impact toughness and wear resistance, excellent surface hardenability and through-hardenability. High degree of dimensional stability, Good polishability and weldability. AISI / SAE 1.2358 can be a substitute for AISI / SAE D2, AISI / SAE D6, AISI / SAE D3 mod. Working hardness: approx. 33 HRC (delivery condition) up to 60 HRC.

**Applications**

Segmented cutting tools, shear knives, forming dies, cold forming tools, deep drawing dies, cold extrusion tools, bending tools, rollers, embossing tools, mould tools, plastic moulds, hot working tools at low temperature stress.

**AISI / SAE 1.2358 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2358

via smartphone/tablet:



PREMIUM 1.2358 – AISI / SAE 1.2358 (60CrMoV18-5)

Eco-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]																
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3	150,3
WIDTH	Available dimensions [mm]																
33	■	■	■	■	■	■	■										
43	■	■	■	■	■	■	■	■									
53	■	■	■	■	■	■	■	■	■								
63	■	■	■	■	■	■	■	■	■	■							
73	■	■	■	■	■	■	■	■	■	■	■						
83	■	■	■	■	■	■	■	■	■	■	■	■					
93	■	■	■	■	■	■	■	■	■	■	■	■	■				
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Tempered tool steel (with focus on cold work). High impact toughness and wear resistance, excellent surface hardenability and through-hardenability. High degree of dimensional stability, Good polishability and weldability. AISI / SAE 1.2358 can be a substitute for AISI / SAE D2, AISI / SAE D6, AISI / SAE D3 mod. Working hardness: approx. 33 HRC (delivery condition) up to 60 HRC.

**Applications**

Segmented cutting tools, shear knives, forming dies, cold forming tools, deep drawing dies, cold extrusion tools, bending tools, rollers, embossing tools, mould tools, plastic moulds, hot working tools at low temperature stress.

**Tolerances****Standard values**

Delivery condition: maximum 325 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,58	0,2	0,7	0	0	4,3	0,4	0,2
0,62	0,5	0,9	0,03	0,03	4,7	0,6	0,3

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/2358-5-5

**AISI / SAE 1.2358 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2358

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13

1.2344 ESU
H13 ESR

ABRAMS®

TOOL STEEL I



TOOL STEEL II

HIGH SPEED STEEL

STAINLESS STEEL
corrosion resistant / acid resistant

HEAT-TREATABLE STEEL,
CASE HARDENING- &
NITRIDING STEEL

INFORMATION



BECOME EVEN BETTER WITH **ABRAMS PREMIUM STEEL®** THAN YOUR COMPETITORS SUSPECT!

ABRAMS!
PREMIUM STEEL®


PREMIUM 1.2344 – AISI / SAE H13 (X40CrMoV5-1)

Precision round steel with machining allowance [PRS/BA]

Specification: peeled / rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
Available dimensions [•]		
15,5	•	•
20,5	•	•
25,5	•	•
30,5	•	•
35,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
55,5	•	•
60,5	•	•
65,5		•
70,5		•
75,5		•
80,5		•
85,5		•
90,5		•
95,5		•
100,5		•

Larger diameters, up to 635,5 mm, and different lengths (e.g. round blanks) available on request!

**Tolerances****Standard values**

Delivery condition: maximum 229 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,35	0,8	0,25	0	0	4,8	1,2	0,85
0,42	1,2	0,5	0,03	0,02	5,5	1,5	1,15

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/H13-7

**Technical properties**

Hot work steel with excellent heat resistance and high wear resistance (slightly higher than AISI / SAE H11). Good toughness and thermal conductivity. Can be cooled with water and is resistant to thermal shock. Working hardness: 50-56 HRC.

**Applications**

Forging tools and dies, hot shear knives, hot extrusion tools, extrusion press tools, press tools, block receivers, die casting tools, light metal die casting, press mandrels, press dies, piecer plugs, screw production, rivet production, bolts production, ejectors, plastic moulds.

**AISI / SAE H13 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/H13

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13


1.2344 ESU
H13 ESR

PREMIUM 1.2344 ESU – AISI / SAE H13 ESR (X40CrMoV5-1)

€co-Präz® 300 [€co]

Length: 300 mm

	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values**

Delivery condition: maximum 229 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,35	0,8	0,25	0	0	4,8	1,2	0,85
0,42	1,2	0,5	0,03	0,02	5,5	1,5	1,15

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/H13ESR-3-5

**Technical properties**

Hot work steel with excellent heat resistance and wear resistance (slightly higher than AISI / SAE H11). Good toughness and thermal conductivity. Can be cooled with water and is resistant to thermal shock. The ESR production (Electro Slag Remelted Steel) guarantees pureness and homogeneity, as well as improved toughness. Working hardness: 50-56 HRC.

**Applications**

Forging tools and dies, hot shear knives, hot extrusion tools, extrusion press tools, press tools, block receivers, die casting tools, light metal die casting, press mandrels, press dies, piecer plugs, screw production, rivet production, bolts production, ejectors, plastic moulds.



AISI / SAE H13 ESR – all at a glance!
Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/H13ESR

via smartphone/tablet:



PREMIUM 1.2344 ESU – AISI / SAE H13 ESR (X40CrMoV5-1)

Eco-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Hot work steel with excellent heat resistance and wear resistance (slightly higher than AISI / SAE H11). Good toughness and thermal conductivity. Can be cooled with water and is resistant to thermal shock. The ESR production (Electro Slag Remelted Steel) guarantees pureness and homogeneousness, as well as improved toughness. Working hardness: 50-56 HRC.

**Applications**

Forging tools and dies, hot shear knives, hot extrusion tools, extrusion press tools, press tools, block receivers, die casting tools, light metal die casting, press mandrels, press dies, piercer plugs, screw production, rivet production, bolts production, ejectors, plastic moulds.

**Tolerances****Standard values**

Delivery condition: maximum 229 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,35	0,8	0,25	0	0	4,8	1,2	0,85
0,42	1,2	0,5	0,03	0,02	5,5	1,5	1,15

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/H13ESR-5-5

**AISI / SAE H13 ESR – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/H13ESR

via smartphone / tablet:

NAVIGATION/
STEEL GRADES

1.2990 mod.
1.2990 mod.

1.2842
O2/O1

1.2826
1.2826

1.2767
6F7

1.2767 ESU
6F7 ESR

1.2738
P20+Ni

1.2714
L6

1.2714+QT
L6+QT

1.2709 ESU
1.2709 ESR

1.2550
S1

1.2436
D6

1.2379
D2

1.2367
1.2367

1.2365
H10

1.2363
A2

1.2361
1.2361

1.2360
~ Chipper

1.2358
1.2358

1.2344
H13

1.2344 ESU
H13 ESR

SPECIFICATIONS !

Our delivery program contains 32.629 different specification / standard dimensions.

Any dimension is available in different **heights**, **widths** and **lengths**. On request – according to your needs!



Precision flat steel without machining allowance [PFS] acc. to DIN 59350

For example: 100,0 x 20,0 x 1.000 mm

- **W** ground/milled, tol. +0,2 /-0 mm
- **T** coplanar ground, tol. +0,05 /-0 mm
- **L** milled/sawn, tol. +35 /-0 mm
- **Exception: PREMIUM 1.1730 – AISI / SAE 1045: W** +0,4 /-0 mm, **T** +0,25 /-0 mm



Precision round steel without machining allowance [PRS]

- bright ground, tol.: Ø ISO h8, **L** +10 /-10 mm
- bright drawn/finely peeled /ground, tol.: Ø ISO h9, **L** +10 /-10 mm
- bright finely peeled, tol.: Ø ISO h11, **L** +10 /-10 mm



Precision flat steel with machining allowance [PRS/BA]

For example: 100,3 x 20,3 x 1.000 mm

- **W** ground/milled, tol. +0,4 /-0 mm
- **T** coplanar ground/finely milled, tol. +0, /-0 mm
- **L** milled/sawn, tol. +35 /-0 mm



Precision round steel with machining allowance [PRS/BA]

- peeled / rough-turned, tol.: Ø +tol./-0 mm, **L** +tol./-0 mm
- **Exception PREMIUM 1.3343 – AISI / SAE M2:**
L 1.000 mm, tol. **L** +10 /-10 mm
- **Particularity: PREMIUM 1.2826 – AISI / SAE 1.2826, PREMIUM 1.2360 – AISI / SAE –Chipper, PREMIUM 1.2067 – AISI / SAE L3:**
Ø are metric full values (for example 30,0 mm), therefore there is no basic machining allowance (for example 30,5 mm)



Eco-Präz® [Eco]

For example: 103 x 20,3 x 500 mm

- **W** sawn/black, tol. +3 /-0 mm
- **T** finely milled, tol. +0, /-0 mm
- **L** sawn/black, tol. +15 /-0 mm



Round steel [RS]

- black, tol.: Ø +1 /-1 mm (aspired), **L** +tol./-0 mm



Hart-Präz® [Hart]

For example: 250 x 10,2 x 500 mm

- **W** sawn/black, Tol. +10/-0 mm
- **T** coplanar ground, Tol. +0,2/-0 mm
- **L** sawn/black, Tol. +10/-0 mm

Planeness: +0,2/-0 mm of the entire surface (aspired)



Erosion block/EDM block – annealed or hardened [EB]

For example: 200,3 x 200,3 x 40,0 mm

- **Square dimension** milled/ground, tol. +2 /-0 mm
- **T** finely milled /ground, tol. +0,25/-0 mm
- Grain structure is vertically directed in relation to base surface

STEEL CLASSIFICATIONS !

Steel grades are classified by their technical **properties** and/or by their intended use.

For example:

Cold work steel, hot work steel, plastic mould steel, high speed steel, corrosion resistant steel or case hardening steel.

Steel grades are often assigned to several classification groups.

For more details on classification see www.steel-guide.eu/glossary



ABRAMS®		TOOL STEEL I				TOOL STEEL II				HIGH SPEED STEEL				STAINLESS STEEL corrosion resistant / acid resistant				HEAT-TREATABLE STEEL, CASE HARDENING- & NITRIDING STEEL				INFORMATION																														
TOOL STEEL II		Description	PPS 500 mm		PPS 1.000 mm		PPS / BA 500 mm		PPS / BA 1.000 mm		Eco-Präz® 200, 300, 400, 800 mm		Hart-Präz® 250, 500, 1.000 mm		Erosion block (annealed, hardened)		PPS ISO H8 / H9 / H11 1.000 mm		PPS / BA 500 mm		PPS / BA 1.000 mm		RS 500 mm		RS 1.000 mm		Delivery hardness (annealed/tempered) max. [HB]		Delivery hardness (hardened) approx. [HRC]		Approx. tensile strength [N/mm²] (deliv. cond.)		Max. working hardness [N/mm²]		Cold work steel		Hot work steel		Plastic mould steel		High speed steel		Corrosion resistant steel		Acid resistant steel		Heat-treatable steel		Case hardening steel		Nitriding steel	
			STEEL GRADE																																																	
PREMIUM 1.2343 AISI / SAE H11		X37CrMoV5-1			✓	✓						✓	✓	✓						229	770	54		✓	✓																								1.2343 H11			
PREMIUM 1.2343 ESU AISI / SAE H11 ESR		X37CrMoV5-1				✓		✓												229	770	54		✓	✓																									1.2343 ESU H11 ESR		
PREMIUM 1.2316 AISI / SAE 1.2316		X38CrMo16						✓				✓	✓	✓						325	1100	48			✓			✓	✓																					1.2316 1.2316		
PREMIUM 1.2312 AISI / SAE P20+S		40CrMnMoS8-6			✓	✓						✓	✓	✓						325	1100	50	✓		✓																									1.2312 P20+S		
PREMIUM 1.2311 AISI / SAE P20		40CrMnMo7			✓	✓							✓	✓						325	1100	50	✓		✓																									1.2311 P20		
PREMIUM 1.2294 AISI / SAE 1.2294		~X5CrS12			✓			✓					✓	✓						330	1125	35			✓			✓			✓																			1.2294 1.2294		
PREMIUM 1.2210 AISI / SAE L2		115CrV3										✓								220	750	62	✓																										1.2210 L2			
PREMIUM 1.2162 AISI / SAE 1.2162		21MnCr5				✓		✓									✓	✓		217	720	60	✓		✓																✓								1.2162 1.2162			
PREMIUM 1.2099 AISI / SAE 1.2099		~X5CrS12			✓			✓					✓	✓						330	1125	35			✓			✓																						1.2099 1.2099		
PREMIUM 1.2085/1.2099 AISI / SAE 420FM/1.2099		X33CrS16 / ~X5CrS12			✓	✓		✓					✓	✓						330	1125	48			✓			✓																						1.2085 420FM		
PREMIUM 1.2083 AISI / SAE 420		X40Cr14				✓		✓	✓			✓	✓	✓						241	50	815	55			✓			✓	✓																				1.2083 420		
PREMIUM 1.2083 ESU AISI / SAE 420 ESR		X40Cr14						✓												241		815	55			✓			✓	✓																				1.2083 ESU 420 ESR		
PREMIUM 1.2080 AISI / SAE D3		~X210Cr12	✓		✓	✓			✓				✓	✓						255	58	860	62	✓		✓																								1.2080 D3		
PREMIUM 1.2067/1.3505 AISI / SAE L3/L1		102Cr6 / 100Cr6						✓				✓		✓						223		750	64	✓																										1.2067 L3/ L1		
PREMIUM 1.1730 AISI / SAE 1045		C45U	✓	✓								✓					✓	✓		190		650	54	✓																										1.1730 1045		
PREMIUM 1.0570 AISI / SAE 1.0570		St 52-3 / ~S355J2+N			✓	✓						✓					✓	✓		180		625	< 20	✓																										1.0570 1.0570		
PREMIUM Toolox 33 AISI / SAE Toolox 33		Toolox 33						✓												330		1125	36	✓		✓																								Toolox 33 Toolox 33		
PREMIUM Toolox 44 AISI / SAE Toolox 44		Toolox 44						✓					✓	✓						418		1420	45	✓		✓																								Toolox 44 Toolox 44		

PREMIUM 1.2343 – AISI / SAE H11 (X37CrMoV5-1)

Precision flat steel with machining allowance [PFS/BA]

Length: 500 mm


	THICKNESS [mm]																			
	4,2	5,2	6,2	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	40,3	50,3	60,3	63,3	70,3	80,3	100,3	
WIDTH	Available dimensions [mm]																			
10,3	■	■	■	■	■															
12,3	■	■	■	■	■	■														
15,3	■	■	■	■	■	■	■													
16,3	■	■	■	■	■	■		■												
20,3	■	■	■	■	■	■	■	■	■											
25,3	■	■	■	■	■	■	■	■	■	■										
30,3	■	■	■	■	■	■	■	■	■	■	■									
32,3	■	■	■	■	■	■	■	■	■	■	■	■								
40,3	■	■	■	■	■	■	■	■	■	■	■	■	■							
50,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■						
60,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■					
63,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
70,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
80,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
100,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
125,3				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
150,3				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
160,3				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
200,3				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
250,3				■	■	■	■	■	■	■	■	■	■	■	■					
300,3				■	■	■	■	■	■	■	■	■	■	■	■					

**Technical properties**

Hot work steel with excellent heat resistance and wear resistance. Good toughness and thermal conductivity. Can be cooled with water and is resistant to thermal shock. The ESR production (Electro Slag Remelted Steel) guarantees pureness and homogeneity, as well as improved toughness. Working hardness: 50-54 HRC.

**Applications**

Forging tools and dies, hot shear knives, hot extrusion tools, extrusion press tools, press tools, block receivers, die casting tools, light metal die casting, press mandrels, press dies, piecer plugs, screw production, rivet production, bolts production, ejectors, plastic moulds.

**Tolerances****Standard values**

Delivery condition: maximum 229 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,33	0,8	0,25	0	0	4,8	1,1	0,3
0,41	1,2	0,5	0,03	0,02	5,5	1,5	0,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/H11-3

**AISI / SAE H11 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/H11

via smartphone/tablet:




PREMIUM 1.2343 – AISI / SAE H11 (X37CrMoV5-1)

Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm

	THICKNESS [mm]																		
	4,2	5,2	6,2	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	40,3	50,3	60,3	63,3	70,3	80,3	100,3
WIDTH	Available dimensions [mm]																		
10,3	■	■	■	■	■														
12,3	■	■	■	■	■	■													
15,3	■	■	■	■	■	■	■												
16,3	■	■	■	■	■	■		■											
20,3	■	■	■	■	■	■	■	■	■										
25,3	■	■	■	■	■	■	■	■	■	■									
30,3	■	■	■	■	■	■	■	■	■	■	■								
32,3	■	■	■	■	■	■	■	■	■	■	■	■							
40,3	■	■	■	■	■	■	■	■	■	■	■	■	■						
50,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■					
60,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
63,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
70,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
80,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
100,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
125,3				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
150,3				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
160,3				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
200,3				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
250,3				■	■	■	■	■	■	■	■	■	■	■	■				
300,3				■	■	■	■	■	■	■	■	■	■	■	■				

**Tolerances****Standard values**

Delivery condition: maximum 229 HB

Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,33	0,8	0,25	0	0	4,8	1,1	0,3
0,41	1,2	0,5	0,03	0,02	5,5	1,5	0,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**www.premium-steel.eu/H11-4**Technical properties**

Hot work steel with excellent heat resistance and wear resistance. Good toughness and thermal conductivity. Can be cooled with water and is resistant to thermal shock. The ESR production (Electro Slag Remelted Steel) guarantees pureness and homogeneity, as well as improved toughness. Working hardness: 50-54 HRC.

**Applications**

Forging tools and dies, hot shear knives, hot extrusion tools, extrusion press tools, press tools, block receivers, die casting tools, light metal die casting, press mandrels, press dies, piecer plugs, screw production, rivet production, bolts production, ejectors, plastic moulds.

**AISI / SAE H11 – all at a glance!**

Datasheets, online shop, ABRAMS STEEL GUIDE® for alternatives: www.premium-steel.eu/H11

via smartphone/tablet:

NAVIGATION/
STEEL GRADES**1.2343
H11**1.2343 ESU
H11 ESR1.2316
1.23161.2312
P20+S1.2311
P201.2294
1.22941.2210
L21.2162
1.21621.2099
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR1.2080 mod.
D3 mod.1.2067
L3 / L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

ABRAMS®

TOOL STEEL I


TOOL STEEL II

HIGH SPEED STEEL

STAINLESS STEEL
corrosion resistant / acid resistant

HEAT-TREATABLE STEEL,
CASE HARDENING- &
NITRIDING STEEL

INFORMATION



PERFECTION!

ABRAMS!
PREMIUM STEEL

PREMIUM 1.2343 – AISI / SAE H11 (X37CrMoV5-1)

Precision round steel without machining allowance [PRS]
Specification: bright ground, ISO h8

	LENGTH [mm]
	1.000
Ø [mm]	Available dimensions [•]
10,0	•
12,0	•
15,0	•
20,0	•
25,0	•

Precision round steel with machining allowance [PRS/BA]
Specification: peeled / rough-turned

	LENGTH [mm]	
	500	1.000
Ø [mm]	Available dimensions [•]	
15,5	•	•
20,5	•	•
25,5	•	•
30,5	•	•
35,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
55,5	•	•
60,5	•	•
65,5		•
70,5		•
75,5		•
80,5		•
85,5		•
90,5		•
95,5		•
100,5		•


Larger diameters, up to 680,5 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Hot work steel with excellent heat resistance and wear resistance. Good toughness and thermal conductivity. Can be cooled with water and is resistant to thermal shock. The ESR production (Electro Slag Remelted Steel) guarantees pureness and homogeneousness, as well as improved toughness. Working hardness: 50-54 HRC.

**Applications**

Forging tools and dies, hot shear knives, hot extrusion tools, extrusion press tools, press tools, block receivers, die casting tools, light metal die casting, press mandrels, press dies, piecer plugs, screw production, rivet production, bolts production, ejectors, plastic moulds.

**Tolerances****Standard values**

Delivery condition: maximum 229 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,33	0,8	0,25	0	0	4,8	1,1	0,3
0,41	1,2	0,5	0,03	0,02	5,5	1,5	0,5

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

[PRS]

www.premium-steel.eu/H11-6

[PRS/BA]

www.premium-steel.eu/H11-7

**AISI / SAE H11 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/H11

via smartphone / tablet:

NAVIGATION/
STEEL GRADES

1.2343
H11

1.2343 ESU
H11 ESR

1.2316
1.2316

1.2312
P20+S

1.2311
P20

1.2294
1.2294

1.2210
L2

1.2162
1.2162

1.2099
1.2099

1.2085
420FM

1.2083
420

1.2083 ESU
420 ESR

1.2080 mod.
D3 mod.

1.2067
L3 / L1

1.1730
1045

1.0570
1.0570

Toolox 33
Toolox 33

Toolox 44
Toolox 44



THE PERFECT FINISH ...

... OUR COMMITMENT FOR YOUR MOULD AND DIE PRODUCTION!

ABRAMS!
PREMIUM STEEL

PREMIUM 1.2343 ESU – AISI / SAE H11 ESR (X37CrMoV5-1)


Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm

	THICKNESS [mm]															
	4,2	5,2	6,2	8,2	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	80,3	100,3	
WIDTH	Available dimensions [mm]															
8,3	■	■	■													
10,3	■	■	■	■	■											
12,3	■	■	■	■	■	■										
15,3	■	■	■	■	■	■	■									
20,3	■	■	■	■	■	■	■	■								
25,3	■	■	■	■	■	■	■	■	■							
30,3	■	■	■	■	■	■	■	■	■	■						
40,3	■	■	■	■	■	■	■	■	■	■	■					
50,3	■	■	■	■	■	■	■	■	■	■	■	■				
60,3	■	■	■	■	■	■	■	■	■	■	■	■	■			
80,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
100,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
120,3				■	■	■	■	■	■	■	■	■	■	■	■	
150,3				■	■	■	■	■	■	■	■	■	■	■	■	
200,3				■	■	■	■	■	■	■	■	■	■	■	■	
250,3				■	■	■	■	■	■	■	■	■	■	■	■	
300,3				■	■	■	■	■	■	■	■	■	■	■	■	



Tolerances



Standard values

Delivery condition: maximum 229 HB

Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,33	0,8	0,25	0	0	4,8	1,1	0,3
0,41	1,2	0,5	0,03	0,02	5,5	1,5	0,5



If you need customised dimensions -

Any dimension available in different heights, widths and lengths.

On request - according to your needs!



Contact us

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu



Direct access to our online shop

www.premium-steel.eu/H11ESR-4



Technical properties

Hot work steel with excellent heat resistance and wear resistance. Good toughness and thermal conductivity. Can be cooled with water and is resistant to thermal shock. The ESR production (Electro Slag Remelted Steel) guarantees pureness and homogeneity, as well as improved toughness. Working hardness: 50-54 HRC.



Applications

Forging tools and dies, hot shear knives, hot extrusion tools, extrusion press tools, press tools, block receivers, die casting tools, light metal die casting, press mandrels, press dies, piecer plugs, screw production, rivet production, bolts production, ejectors, plastic moulds.



AISI / SAE H11 ESR – all at a glance!

Datasheets, online shop, ABRAMS STEEL GUIDE® for alternatives: www.premium-steel.eu/H11ESR

via smartphone/tablet:



NAVIGATION/ STEEL GRADES

1.2343
H11

1.2343 ESU
H11 ESR

1.2316
1.2316

1.2312
P20+S

1.2311
P20

1.2294
1.2294

1.2210
L2

1.2162
1.2162

1.2099
1.2099

1.2085
420FM

1.2083
420

1.2083 ESU
420 ESR

1.2080 mod.
D3 mod.

1.2067
L3 / L1

1.1730
1045

1.0570
1.0570

Toolox 33
Toolox 33

Toolox 44
Toolox 44

PREMIUM 1.2343 ESU – AISI / SAE H11 ESR (X37CrMoV5-1)


€co-Präz® 300 [€co]

Length: 300 mm

		THICKNESS [mm]															
		8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH		Available dimensions [mm]															
1.2316	33	■	■	■	■	■	■	■									
1.2316	43	■	■	■	■	■	■	■	■								
1.2312	53	■	■	■	■	■	■	■	■	■							
P20+S	63	■	■	■	■	■	■	■	■	■	■						
1.2311	73	■	■	■	■	■	■	■	■	■	■	■					
P20	83	■	■	■	■	■	■	■	■	■	■	■	■				
1.2294	93	■	■	■	■	■	■	■	■	■	■	■	■	■			
1.2294	103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
1.2210	123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
L2	143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1.2162	153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1.2162	163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1.2099	183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1.2099	203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1.2085	223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
420FM	243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1.2083	253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
420	263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1.2083 ESU	283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
420 ESR	303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■



Tolerances



Standard values

Delivery condition: maximum 229 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,33	0,8	0,25	0	0	4,8	1,1	0,3
0,41	1,2	0,5	0,03	0,02	5,5	1,5	0,5



If you need customised dimensions -

Any dimension available in different heights, widths and lengths.

On request - according to your needs!



Contact us

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu



Direct access to our online shop

www.premium-steel.eu/H11ESR-3-5



Technical properties

Hot work steel with excellent heat resistance and wear resistance. Good toughness and thermal conductivity. Can be cooled with water and is resistant to thermal shock. The ESR production (Electro Slag Remelted Steel) guarantees pureness and homogeneousness, as well as improved toughness. Working hardness: 50-54 HRC.



Applications

Forging tools and dies, hot shear knives, hot extrusion tools, extrusion press tools, press tools, block receivers, die casting tools, light metal die casting, press mandrels, press dies, piecer plugs, screw production, rivet production, bolts production, ejectors, plastic moulds.



AISI / SAE H11 ESR – all at a glance!
Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/H11ESR

via smartphone/tablet:



PREMIUM 1.2343 ESU – AISI / SAE H11 ESR (X37CrMoV5-1)

€co-Präz® 500 [€co]

Length: 500 mm

	THICKNESS [mm]													
	10,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	
WIDTH	Available dimensions [mm]													
53	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	
153	■	■	■	■	■	■	■	■	■	■	■	■	■	
163	■	■	■	■	■	■	■	■	■	■	■	■	■	
183	■	■	■	■	■	■	■	■	■	■	■	■	■	
203	■	■	■	■	■	■	■	■	■	■	■	■	■	
223	■	■	■	■	■	■	■	■	■	■	■	■	■	
243	■	■	■	■	■	■	■	■	■	■	■	■	■	
253	■	■	■	■	■	■	■	■	■	■	■	■	■	
263	■	■	■	■	■	■	■	■	■	■	■	■	■	
283	■	■	■	■	■	■	■	■	■	■	■	■	■	
303	■	■	■	■	■	■	■	■	■	■	■	■	■	
323	■	■	■	■	■	■	■	■	■	■	■	■	■	
343	■	■	■	■	■	■	■	■	■	■	■	■	■	
353	■	■	■	■	■	■	■	■	■	■	■	■	■	
363	■	■	■	■	■	■	■	■	■	■	■	■	■	
383	■	■	■	■	■	■	■	■	■	■	■	■	■	
403	■	■	■	■	■	■	■	■	■	■	■	■	■	
423	■	■	■	■	■	■	■	■	■	■	■	■	■	
443	■	■	■	■	■	■	■	■	■	■	■	■	■	
453	■	■	■	■	■	■	■	■	■	■	■	■	■	
463	■	■	■	■	■	■	■	■	■	■	■	■	■	
483	■	■	■	■	■	■	■	■	■	■	■	■	■	
503	■	■	■	■	■	■	■	■	■	■	■	■	■	



Technical properties

Hot work steel with excellent heat resistance and wear resistance. Good toughness and thermal conductivity. Can be cooled with water and is resistant to thermal shock. The ESR production (Electro Slag Remelted Steel) guarantees purity and homogeneity, as well as improved toughness. Working hardness: 50-54 HRC.




Applications

Forging tools and dies, hot shear knives, hot extrusion tools, extrusion press tools, press tools, block receivers, die casting tools, light metal die casting, press mandrels, press dies, piecer plugs, screw production, rivet production, bolts production, ejectors, plastic moulds.



Tolerances



Standard values

Delivery condition: maximum 229 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,33	0,8	0,25	0	0	4,8	1,1	0,3
0,41	1,2	0,5	0,03	0,02	5,5	1,5	0,5



If you need customised dimensions -

Any dimension available in different heights, widths and lengths.

On request - according to your needs!



Contact us

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu



Direct access to our online shop

www.premium-steel.eu/H11ESR-5-5



AISI / SAE H11 ESR – all at a glance!

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/H11ESR

via smartphone/tablet:



NAVIGATION/ STEEL GRADES

1.2343
H11

1.2343 ESU
H11 ESR

1.2316
1.2316

1.2312
P20+S

1.2311
P20

1.2294
1.2294

1.2210
L2

1.2162
1.2162

1.2099
1.2099

1.2085
420FM

1.2083
420

1.2083 ESU
420 ESR

1.2080 mod.
D3 mod.

1.2067
L3 / L1

1.1730
1045

1.0570
1.0570

Toolox 33
Toolox 33

Toolox 44
Toolox 44

PREMIUM 1.2316 – AISI / SAE 1.2316 (X38CrMo16)

€co-Präz® 300 [€co]

Length: 300 mm


	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Tempered, corrosion resistant, polishable chromium steel. Heat and wear resistant. Often used for tools for processing chemically aggressive plastic materials (e.g. PVC). Working hardness: approx. 30 HRC (delivery condition) up to 48 HRC.

**Applications**

Mechanical engineering, marine engineering, apparatus engineering, plastic processing, plastic moulds, extrusion tools, press moulds, fitting tools, shafts, spindles, bolts, pistons, valves, steam valves, water valves, beater bars, fittings parts, pump construction, pump rods, compressor construction, compressor parts, surgical instruments.

**Tolerances****Standard values**

Delivery condition: maximum 325 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni
0,33	0	0	0	0	15,5	0,8	0
0,45	1,0	1,5	0,03	0,03	17,5	1,3	1,0

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/2316-3-5

**AISI / SAE 1.2316 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2316

via smartphone/tablet:



PREMIUM 1.2316 – AISI / SAE 1.2316 (X38CrMo16)

€co-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Tempered, corrosion resistant, polishable chromium steel. Heat and wear resistant. Often used for tools for processing chemically aggressive plastic materials (e.g. PVC). Working hardness: approx. 30 HRC (delivery condition) up to 48 HRC.

**Applications**

Mechanical engineering, marine engineering, apparatus engineering, plastic processing, plastic moulds, extrusion tools, press moulds, fitting tools, shafts, spindles, bolts, pistons, valves, steam valves, water valves, beater bars, fittings parts, pump construction, pump rods, compressor construction, compressor parts, surgical instruments.

**Tolerances****Standard values**

Delivery condition: maximum 325 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni
0,33	0	0	0	0	15,5	0,8	0
0,45	1,0	1,5	0,03	0,03	17,5	1,3	1,0

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/1.2316-5-5

**AISI / SAE 1.2316 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2316

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR**1.2316**
1.23161.2312
P20+S1.2311
P201.2294
1.22941.2210
L21.2162
1.21621.2099
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR1.2080 mod.
D3 mod.1.2067
L3/ L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

ABRAMS®

TOOL STEEL I

TOOL STEEL II

HIGH SPEED STEEL

STAINLESS STEEL
corrosion resistant / acid resistant

HEAT-TREATABLE STEEL,
CASE HARDENING- &
NITRIDING STEEL

INFORMATION

PRECISION!

ABRAMS®
PREMIUM STEEL

PREMIUM 1.2316 – AISI / SAE 1.2316 (X38CrMo16)

Precision round steel without machining allowance [PRS]
Specification: bright drawn / ground, ISO h9

Ø [mm]	LENGTH [mm]
	1.000
Available dimensions [•]	
16,0	•
18,0	•
20,0	•
22,0	•
25,0	•
28,0	•
30,0	•
35,0	•
40,0	•
45,0	•
50,0	•

Precision round steel with machining allowance [PRS/BA]
Specification: peeled / rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
Available dimensions [•]		
20,5	•	•
25,5	•	•
30,5	•	•
35,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
55,5	•	•
60,5	•	•
65,5		•
70,5		•
75,5		•
80,5		•
85,5		•
90,5		•
95,5		•
100,5		•

Larger diameters, up to 550,5 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Tempered, corrosion resistant, polishable chromium steel. Heat and wear resistant. Often used for tools for processing chemically aggressive plastic materials (e.g. PVC). Working hardness: approx. 30 HRC (delivery condition) up to 48 HRC.

**Applications**

Mechanical engineering, marine engineering, apparatus engineering, plastic processing, plastic moulds, extrusion tools, press moulds, fitting tools, shafts, spindles, bolts, pistons, valves, steam valves, water valves, beater bars, fittings parts, pump construction, pump rods, compressor construction, compressor parts, surgical instruments.

**Tolerances**

PRS: Ø ISO h9
PRS/BA: Ø +tol. / -0 mm
PRS: L +10 / -10 mm
PRS/BA: L +tol. / -0 mm

**Standard values**

Delivery condition: maximum 325 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni
0,33	0	0	0	0	15,5	0,8	0
0,45	1,0	1,5	0,03	0,03	17,5	1,3	1,0

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop [PRS]**

www.premium-steel.eu/2316-6
[PRS/BA]
www.premium-steel.eu/2316-7

**AISI / SAE 1.2316 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2316

via smartphone / tablet:

NAVIGATION/
STEEL GRADES

1.2343
H11

1.2343 ESU
H11 ESR

1.2316
1.2316

1.2312
P20+S

1.2311
P20

1.2294
1.2294

1.2210
L2

1.2162
1.2162

1.2099
1.2099

1.2085
420FM

1.2083
420

1.2083 ESU
420 ESR

1.2080 mod.
D3 mod.

1.2067
L3 / L1

1.1730
1045

1.0570
1.0570

Toolox 33
Toolox 33

Toolox 44
Toolox 44

PREMIUM 1.2312 – AISI / SAE P20+S (40CrMnMoS8-6)

Precision flat steel with machining allowance [PFS/BA]

Length: 500 mm

	THICKNES [mm]																			
	4,2	5,2	6,2	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	
WIDTH	Available dimensions [mm]																			
10,3					■															
12,3						■														
15,3							■													
16,3								■												
20,3			■	■	■	■	■		■											
25,3			■	■	■	■	■	■	■	■										
30,3			■	■	■	■	■	■	■	■	■									
32,3			■	■	■	■	■	■	■	■		■								
40,3	■	■	■	■	■	■	■	■	■	■	■		■							
50,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■						
60,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■					
63,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■					
70,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
80,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
100,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
125,3			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
150,3			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
175,3			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
180,3			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
200,3			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
220,3					■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
250,3					■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
300,3					■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
400,3					■	■	■	■	■	■	■	■	■	■	■					
500 *					■	■	■	■	■	■	■	■	■	■	■					


* Width and length sawn/raw with +tol./-0 mm

**Technical properties**

Pre-hardened cold work steel and plastic mould steel.
Good machinability, although less polishable and more difficult to etch, due to added sulphur. High through-hardening and uniform component strength. Working hardness: approx. 32 HRC (delivery condition) up to 50 HRC.

**Applications**

Mechanical engineering, jigs, base plates, assembling parts, moulding frames, plastic moulds, plastic processing, die casting moulds, hydroforming tools, recipient sleeves, folding bars, tool holders.

**Tolerances****Standard values**

Delivery condition: maximum 325 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo
0,35	0,3	1,4	0	0,05	1,8	0,15
0,45	0,5	1,6	0,03	0,1	2,0	0,25

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/P20S-3

**AISI / SAE P20+S – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/P20S

via smartphone / tablet:



PREMIUM 1.2312 – AISI / SAE P20+S (40CrMnMoS8-6)

Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm

	THICKNESS [mm]																		
	4,2	5,2	6,2	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3
WIDTH	Available dimensions [mm]																		
10,3					■														
12,3						■													
15,3							■												
16,3								■											
20,3			■	■	■	■	■		■										
25,3			■	■	■	■	■	■	■	■									
30,3			■	■	■	■	■	■	■	■	■								
32,3			■	■	■	■	■	■	■	■		■							
40,3	■	■	■	■	■	■	■	■	■	■	■		■						
50,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■					
60,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
63,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■					
70,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
80,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
100,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		■
125,3			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
150,3			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
160,3					■	■		■	■										
175,3			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
180,3			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
200,3			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
220,3					■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
250,3					■	■	■	■	■	■	■	■	■	■	■	■	■		
300,3					■	■	■	■	■	■	■	■	■	■	■	■	■		
400,3					■	■	■	■	■	■	■	■	■	■	■				
500 *					■	■	■	■	■	■	■	■	■	■	■				


* Width and length sawn/raw with +tol./-0 mm

**Technical properties**

Pre-hardened cold work steel and plastic mould steel. Good machinability, although less polishable and more difficult to etch, due to added sulphur. High through-hardenedness and uniform component strength. Working hardness: approx. 32 HRC (delivery condition) up to 50 HRC.

**Applications**

Mechanical engineering, jigs, base plates, assembling parts, moulding frames, plastic moulds, plastic processing, die casting moulds, hydroforming tools, recipient sleeves, folding bars, tool holders.

**Tolerances****Standard values**

Delivery condition: maximum 325 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo
0,35	0,3	1,4	0	0,05	1,8	0,15
0,45	0,5	1,6	0,03	0,1	2,0	0,25

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/P20S-4

**AISI / SAE P20+S – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/P20S

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.2316**1.2312**
P20+S1.2311
P201.2294
1.22941.2210
L21.2162
1.21621.2099
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR1.2080 mod.
D3 mod.1.2067
L3 / L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

ABRAMS®

TOOL STEEL I

TOOL STEEL II

HIGH SPEED STEEL

STAINLESS STEEL
corrosion resistant / acid resistant

HEAT-TREATABLE STEEL,
CASE HARDENING- &
NITRIDING STEEL

INFORMATION

PREMIUM QUALITY – OUR HIGHEST STANDARD!

ABRAMS![®]
PREMIUM STEEL

PREMIUM 1.2312 – AISI / SAE P20+S (40CrMnMoS8-6)

Precision round steel without machining allowance [PRS]
Specification: bright ground, ISO h8

Ø [mm]	LENGTH [mm]
	1.000
Available dimensions [•]	
6,0	•
8,0	•
10,0	•
12,0	•
14,0	•
15,0	•
16,0	•
18,0	•
20,0	•

Precision round steel with machining allowance [PRS/BA]
Specification: peeled /rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
Available dimensions [•]		
20,5	•	•
25,5	•	•
30,5	•	•
35,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
55,5	•	•
60,5	•	•
65,5		•
70,5		•
75,5		•
80,5		•
85,5		•
90,5		•
95,5		•
100,5		•


Larger diameters, up to 400,5 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Pre-hardened cold work steel and plastic mould steel. Good machinability, although less polishable and more difficult to etch, due to added sulphur. High through-hardening and uniform component strength. Working hardness: approx. 32 HRC (delivery condition) up to 50 HRC.

**Applications**

Mechanical engineering, jigs, base plates, assembling parts, moulding frames, plastic moulds, plastic processing, die casting moulds, hydroforming tools, recipient sleeves, folding bars, tool holders.

**Tolerances****Standard values**

Delivery condition: maximum 325 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo
0,35	0,3	1,4	0	0,05	1,8	0,15
0,45	0,5	1,6	0,03	0,1	2,0	0,25

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop [PRS]**

www.premium-steel.eu/P20S-6
[PRS/BA]
www.premium-steel.eu/P20S-7

**AISI / SAE P20+S – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/P20S

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.2316**1.2312**
P20+S1.2311
P201.2294
1.22941.2210
L21.2162
1.21621.2099
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR1.2080 mod.
D3 mod.1.2067
L3 / L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

PREMIUM 1.2311 – AISI / SAE P20 (40CrMnMo7)

Precision flat steel with machining allowance [PFS/BA]

Length: 500 mm


	THICKNESS [mm]											
	6,2	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	40,3	50,3
WIDTH	Available dimensions [mm]											
1.2316												
1.2316												
1.2312												
P20+S												
1.2311												
P20												
1.2294												
1.2294												
1.2210												
L2												
1.2162												
1.2162												
1.2099												
1.2099												
1.2085												
420FM												
1.2083												
420												
1.2083 ESU												
420 ESR												
1.2080 mod.												
D3 mod.												
1.2067												
L3/L1												
1.1730												
1045												
1.0570												
1.0570												

**Technical properties**

Pre-hardened cold work steel and plastic mould steel.
Good polishability and etchability. High through-hardening and uniform component strength. Working hardness: approx. 32 HRC (delivery condition) up to 50 HRC.

**Applications**

Mechanical engineering, jigs, base plates, assembling parts, moulding frames, plastic moulds, plastic processing, injection moulds, die casting moulds, hydroforming tools, recipient sleeves, intermediate sleeves, folding bars, tool holders, extrusion presses, tube presses, die holders, die insert.

**Tolerances****Standard values**

Delivery condition: maximum 325 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo
0,35	0,2	1,3	0	0	1,8	0,15
0,45	0,4	1,6	0,035	0,035	2,1	0,25

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/P20-3

**AISI / SAE P20 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/P20

via smartphone / tablet:



PREMIUM 1.2311 – AISI / SAE P20 (40CrMnMo7)

Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm


	THICKNESS [mm]											
	6,2	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	40,3	50,3
WIDTH	Available dimensions [mm]											
12,3				■								
16,3						■						
20,3		■	■	■	■		■					
25,3		■	■	■	■	■	■	■				
30,3		■	■	■	■	■	■	■				
32,3	■	■	■	■	■	■	■	■		■		
40,3	■	■	■	■	■	■	■	■	■			
50,3	■	■	■	■	■	■	■	■	■	■	■	
60,3	■	■	■	■	■	■	■	■	■	■	■	■
63,3	■	■	■	■	■	■	■	■	■	■	■	■
70,3	■	■	■	■	■	■	■	■	■	■	■	■
80,3	■	■	■	■	■	■	■	■	■	■	■	■
100,3	■	■	■	■	■	■	■	■	■	■	■	■
125,3		■	■	■	■	■	■	■	■	■	■	■
150,3		■	■	■	■	■	■	■	■	■	■	■
175,3		■	■	■	■	■	■	■	■	■	■	■
200,3		■	■	■	■	■	■	■	■	■	■	■
220,3			■	■	■	■	■	■	■	■	■	■
250,3			■	■	■	■	■	■	■	■	■	■
300,3			■	■	■	■	■	■	■	■	■	■

**Technical properties**

Pre-hardened cold work steel and plastic mould steel. Good polishability and etchability. High through-hardening and uniform component strength. Working hardness: approx. 32 HRC (delivery condition) up to 50 HRC.

**Applications**

Mechanical engineering, jigs, base plates, assembling parts, moulding frames, plastic moulds, plastic processing, injection moulds, die casting moulds, hydroforming tools, recipient sleeves, intermediate sleeves, folding bars, tool holders, extrusion presses, tube presses, die holders, die insert.

**Tolerances****Standard values**

Delivery condition: maximum 325 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo
0,35	0,2	1,3	0	0	1,8	0,15
0,45	0,4	1,6	0,035	0,035	2,1	0,25

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/P20-4

**AISI / SAE P20 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/P20

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2343
H11

1.2343 ESU
H11 ESR

1.2316
1.2316

1.2312
P20+S

1.2311
P20

1.2294
1.2294

1.2210
L2

1.2162
1.2162

1.2099
1.2099

1.2085
420FM

1.2083
420

1.2083 ESU
420 ESR

1.2080 mod.
D3 mod.

1.2067
L3 / L1

1.1730
1045

1.0570
1.0570

Toolox 33
Toolox 33

Toolox 44
Toolox 44



PREMIUM 1.2311 – AISI / SAE P20 (40CrMnMo7)

Precision round steel with machining allowance [PRS/BA]

Specification: peeled / rough-turned

	LENGTH [mm]	
	500	1.000
Ø [mm]	Available dimensions [•]	
20,5	•	•
25,5	•	•
30,5	•	•
35,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
55,5	•	•
60,5	•	•
65,5		•
70,5		•
75,5		•
80,5		•
85,5		•
90,5		•
95,5		•
100,5		•


Larger diameters, up to 400,5 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Pre-hardened cold work steel and plastic mould steel. Good polishability and etchability. High through-hardenedability and uniform component strength. Working hardness: approx. 32 HRC (delivery condition) up to 50 HRC.

**Applications**

Mechanical engineering, jigs, base plates, assembling parts, moulding frames, plastic moulds, plastic processing, injection moulds, die casting moulds, hydroforming tools, recipient sleeves, intermediate sleeves, folding bars, tool holders, extrusion presses, tube presses, die holders, die insert.

**Tolerances****Standard values**

Delivery condition: maximum 325 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo
0,35	0,2	1,3	0	0	1,8	0,15
0,45	0,4	1,6	0,035	0,035	2,1	0,25

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/P20-7

**AISI / SAE P20 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/P20

via smartphone/tablet:


NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.23161.2312
P20+S**1.2311**
P201.2294
1.22941.2210
L21.2162
1.21621.2099
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR1.2080 mod.
D3 mod.1.2067
L3 / L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

PREMIUM 1.2294 – AISI / SAE 1.2294 (~X5CrS12)

Precision flat steel with machining allowance [PFS/BA]

Length: 500 mm

		THICKNESS [mm]								
		6,2	8,2	10,3	15,3	20,3	25,3	30,3	40,3	50,3
WIDTH		Available dimensions [mm]								
1.2316	20,3	■	■	■						
1.2316	25,3	■	■	■	■					
1.2312	30,3	■	■	■	■	■				
P20+S	40,3	■	■	■	■	■	■			
1.2311	50,3	■	■	■	■	■	■	■		
P20	60,3	■	■	■	■	■	■	■	■	
1.2294	80,3	■	■	■	■	■	■	■	■	■
1.2294	100,3	■	■	■	■	■	■	■	■	■
1.2210	125,3	■	■	■	■	■	■	■	■	■
L2	150,3	■	■	■	■	■	■	■	■	■
1.2162	200,3	■	■	■	■	■	■	■	■	■
1.2162	250,3	■	■	■	■	■	■	■	■	■
1.2099	300,3	■	■	■	■	■	■	■	■	■
1.2099										

**Tolerances****Standard values**

Delivery condition: maximum 330 HB
Chemical composition: (+additives):

C	Mn	S	Cr
0,05	1,3	0,15	12,5
0,05	1,3	0,15	12,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/2294-3

**Technical properties**

Pre-hardened, corrosion resistant plastic mould steel. Magnetisable, excellent machinability and good weldability. Resistant to aggressive plastics and humid conditions. Further heat treatment is not intended. Working hardness: approx. 33 HRC (reference value for delivery condition).

**Applications**

Mechanical engineering, apparatus engineering, plastic processing, injection tools, base plates, assembling parts, moulding frames, plastic moulds, extrusion tools, valves, steam valves, water valves, fittings parts, pump construction, pump rods, compressor construction, compressor parts, surgical instruments.

**AISI / SAE 1.2294 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2294

via smartphone / tablet:



PREMIUM 1.2294 – AISI / SAE 1.2294 (~X5CrS12)

€co-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]																
	2,3	3,3	4,3	5,3	6,3	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3
WIDTH	Available dimensions [mm]																
33	■	■	■	■	■	■											
43	■	■	■	■	■	■											
53	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
63	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
73	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
83	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
93	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
323	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
343	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
353	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
363	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
383	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
403	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
423	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
443	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
453	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
463	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
483	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
503	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Pre-hardened, corrosion resistant plastic mould steel. Magnetisable, excellent machinability and good weldability. Resistant to aggressive plastics and humid conditions. Further heat treatment is not intended. Working hardness: approx. 33 HRC (reference value for delivery condition).

**Applications**

Mechanical engineering, apparatus engineering, plastic processing, injection tools, base plates, assembling parts, moulding frames, plastic moulds, extrusion tools, valves, steam valves, water valves, fittings parts, pump construction, pump rods, compressor construction, compressor parts, surgical instruments.

**Tolerances****Standard values**

Delivery condition: maximum 330 HB
Chemical composition: (+ additives):

C	Mn	S	Cr
0,05	1,3	0,15	12,5
0,05	1,3	0,15	12,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/2294-5

**AISI / SAE 1.2294 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2294

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.23161.2312
P20+S1.2311
P20**1.2294**
1.22941.2210
L21.2162
1.21621.2099
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR1.2080 mod.
D3 mod.1.2067
L3 / L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

ABRAMS®

TOOL STEEL I

TOOL STEEL II

HIGH SPEED STEEL

STAINLESS STEEL
corrosion resistant / acid resistant

HEAT-TREATABLE STEEL,
CASE HARDENING- &
NITRIDING STEEL

INFORMATION



CORROSION RESISTANT STEEL!

ABRAMS!®
PREMIUM STEEL

PREMIUM 1.2294 – AISI / SAE 1.2294 (~X5CrS12)

Precision round steel with machining allowance [PRS/BA]

Specification: peeled / rough-turned

	LENGTH [mm]	
	500	1.000
Ø [mm]	Available dimensions [•]	
35,5	•	•
45,5	•	•
55,5	•	•
65,5	•	•
85,5		•
90,5		•
100,5		•


Larger diameters, up to 180,5 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Pre-hardened, corrosion resistant plastic mould steel. Magnetisable, excellent machinability and good weldability. Resistant to aggressive plastics and humid conditions. Further heat treatment is not intended. Working hardness: approx. 33 HRC (reference value for delivery condition).

**Applications**

Mechanical engineering, apparatus engineering, plastic processing, injection tools, base plates, assembling parts, moulding frames, plastic moulds, extrusion tools, valves, steam valves, water valves, fittings parts, pump construction, pump rods, compressor construction, compressor parts, surgical instruments.

**Tolerances****Standard values**

Delivery condition: maximum 330 HB
Chemical composition: (+ additives):

C	Mn	S	Cr
0,05	1,3	0,15	12,5
0,05	1,3	0,15	12,5

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/2294-7

**AISI / SAE 1.2294 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2294

via smartphone / tablet:

NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.23161.2312
P20+S1.2311
P20**1.2294**
1.22941.2210
L21.2162
1.21621.2099
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR1.2080 mod.
D3 mod.1.2067
L3 / L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

ABRAMS®

TOOL STEEL I

TOOL STEEL II

HIGH SPEED STEEL

STAINLESS STEEL
corrosion resistant / acid resistant

HEAT-TREATABLE STEEL,
CASE HARDENING- &
NITRIDING STEEL

INFORMATION



PRECISION ROUND STEEL WITHOUT MACHINING ALLOWANCE – ISO h8, h9, h11

ABRAMS®
PREMIUM STEEL

PREMIUM 1.2210 – AISI / SAE L2 (115CrV3)

Precision round steel without machining allowance/Silver Steel [PRS]

Specification: bright ground, ISO h8


Ø [mm]	LENGTH [mm]					
	1.000					
	Available dimensions [•]					
1,0	•	»		»		»
1,2	•	6,2	•	11,2	•	19,5
1,5	•	6,5	•	11,5	•	20,0
1,7	•	6,7	•	11,7	•	21,0
2,0	•	7,0	•	12,0	•	22,0
2,2	•	7,2	•	12,2	•	23,0
2,5	•	7,5	•	12,5	•	24,0
2,7	•	7,7	•	12,7	•	25,0
3,0	•	8,0	•	13,0	•	26,0
3,2	•	8,2	•	13,5	•	27,0
3,5	•	8,5	•	14,0	•	28,0
3,7	•	8,7	•	14,5	•	29,0
4,0	•	9,0	•	15,0	•	30,0
4,2	•	9,2	•	15,5	•	35,0
4,5	•	9,5	•	16,0	•	40,0
4,7	•	9,7	•	16,5	•	45,0
5,0	•	10,0	•	17,0	•	50,0
5,2	•	10,2	•	17,5	•	55,0
5,5	•	10,5	•	18,0	•	60,0
5,7	•	10,7	•	18,5	•	
6,0	•	11,0	•	19,0	•	
»		»		»		

**Technical properties**

Cold work steel that can be used for a wide range of applications. Good machinability, high hardenability and wear resistance. Generally used for round dies. Working hardness: 58-62 HRC.

**Applications**

Twist drills, screw taps, reamers, milling cutters, countersinks, centre drills, scrapers, engraving tools, punches, ejectors, guide pins, wood chisels, bushes, gauges, jigs, construction parts.

**Tolerances****Standard values**

Delivery condition: maximum 220 HB
Chemical composition:

C	Si	Mn	P	S	Cr	V
1,1	0,15	0,2	0	0	0,5	0,07
1,25	0,3	0,4	0,03	0,03	0,8	0,12

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/L2-6

**AISI / SAE L2 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/L2

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.23161.2312
P20+S1.2311
P201.2294
1.2294**1.2210
L2**1.2162
1.21621.2099
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR1.2080 mod.
D3 mod.1.2067
L3 / L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

PERFECTION !



PREMIUM 1.2162 – AISI / SAE 1.2162 (21MnCr5)

Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm

	THICKNESS [mm]															
	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	36,3	40,3	50,3	60,3	70,3	80,3	100,3
WIDTH	Available dimensions [mm]															
15,3				■												
20,3	■	■	■	■	■	■										
25,3	■	■	■	■	■	■	■									
30,3	■	■	■	■	■	■	■	■								
32,3	■	■	■	■	■	■	■	■	■							
40,3	■	■	■	■	■	■	■	■		■	■					
50,3	■	■	■	■	■	■	■	■		■	■	■				
60,3	■	■	■	■	■	■	■	■		■	■	■	■			
70,3	■	■	■	■	■	■	■	■		■	■	■	■	■		
80,3	■	■	■	■	■	■	■	■		■	■	■	■	■	■	
100,3	■	■	■	■	■	■	■	■		■	■	■	■	■		■
120,3	■	■	■	■	■	■	■	■		■	■	■	■			
150,3	■	■	■	■	■	■	■	■		■	■	■	■			
180,3	■	■	■	■	■	■	■	■		■	■	■	■			
200,3	■	■	■	■	■	■	■	■		■	■	■	■			
250,3	■	■	■	■	■	■	■	■		■	■	■	■			
300,3	■	■	■	■	■	■	■	■		■	■	■	■			
500 *		■	■	■	■	■	■	■		■	■	■	■			


* Width and length sawn/raw with +tol./-0 mm

**Technical properties**

Cold work steel and plastic mould steel. High surface hardness with high core toughness. Excellent machinability, good cold hobbing and polishing properties. The even component strength is a result of the combination of hardened surface and high core toughness. Surface working hardness: 58-60 HRC.

**Applications**

Mechanical engineering, jig construction, plant engineering, apparatus engineering, plastic processing, plastic moulds, synthetic resin mould tools, base plates, bending bars, guide columns, gear parts, joint parts, shafts, gears, rods, bevel gears, crown wheels, piston pins, camshafts, bolts, pins, cardan joints.

**Tolerances****Standard values**

Delivery condition: maximum 217 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,18	0,15	1,1	0	0	1,0
0,24	0,35	1,4	0,03	0,03	1,3

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/2162-4

**AISI / SAE 1.2162 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2162

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.23161.2312
P20+S1.2311
P201.2294
1.22941.2210
L2**1.2162**
1.21621.2099
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR1.2080 mod.
D31.2067
L3/ L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

PREMIUM 1.2162 – AISI / SAE 1.2162 (21MnCr5)

€co-Präz® 500 [€co]

Length: 500 mm


		THICKNESS [mm]									
		6,3	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3
WIDTH		Available dimensions [mm]									
1.2343 H11	33	■	■	■	■	■	■	■	■		
1.2343 ESU H11 ESR	43	■	■	■	■	■	■	■	■		
1.2316	53	■	■	■	■	■	■	■	■	■	■
1.2312 P20+S	63	■	■	■	■	■	■	■	■	■	■
1.2311 P20	73	■	■	■	■	■	■	■	■	■	■
1.2294	83	■	■	■	■	■	■	■	■	■	■
1.2294	93	■	■	■	■	■	■	■	■	■	■
1.2210 L2	103	■	■	■	■	■	■	■	■	■	■
1.2162	123	■	■	■	■	■	■	■	■	■	■
1.2162	143	■	■	■	■	■	■	■	■	■	■
1.2099	153	■	■	■	■	■	■	■	■	■	■
1.2099	163	■	■	■	■	■	■	■	■	■	■
1.2085 420FM	183	■	■	■	■	■	■	■	■	■	■
1.2083 420	203	■	■	■	■	■	■	■	■	■	■
1.2083 ESU 420 ESR	223	■	■	■	■	■	■	■	■	■	■
1.2080 mod. D3 mod.	243	■	■	■	■	■	■	■	■	■	■
1.2067 L3/L1	253	■	■	■	■	■	■	■	■	■	■
1.1730 1045	263	■	■	■	■	■	■	■	■	■	■
1.0570 1.0570	283	■	■	■	■	■	■	■	■	■	■
Toolox 33	303	■	■	■	■	■	■	■	■	■	■
Toolox 33	323	■	■	■	■	■	■	■	■	■	■
Toolox 44	343	■	■	■	■	■	■	■	■	■	■
Toolox 44	353	■	■	■	■	■	■	■	■	■	■
	363	■	■	■	■	■	■	■	■	■	■
	383	■	■	■	■	■	■	■	■	■	■
	403	■	■	■	■	■	■	■	■	■	■
	423	■	■	■	■	■	■	■	■	■	■
	443	■	■	■	■	■	■	■	■	■	■
	453	■	■	■	■	■	■	■	■	■	■
	463	■	■	■	■	■	■	■	■	■	■
	483	■	■	■	■	■	■	■	■	■	■
	503	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Cold work steel and plastic mould steel. High surface hardness with high core toughness. Excellent machinability, good cold hobbing and polishing properties. The even component strength is a result of the combination of hardened surface and high core toughness. Surface working hardness: 58-60 HRC.

**Applications**

Mechanical engineering, jig construction, plant engineering, apparatus engineering, plastic processing, plastic moulds, synthetic resin mould tools, base plates, bending bars, guide columns, gear parts, joint parts, shafts, gears, rods, bevel gears, crown wheels, piston pins, camshafts, bolts, pins, cardan joints.

**Tolerances****Standard values**

Delivery condition: maximum 217 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,18	0,15	1,1	0	0	1,0
0,24	0,35	1,4	0,03	0,03	1,3

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/2162-5

**AISI / SAE 1.2162 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2162

via smartphone / tablet:



PREMIUM 1.2162 – AISI / SAE 1.2162 (21MnCr5)

Round steel [RS]

Specification: black

Ø [mm]	LENGTH [mm]	
	500	1.000
	Available dimensions [•]	
20	•	•
22	•	•
25	•	•
30	•	•
35	•	•
40	•	•
45	•	•
50	•	•
55	•	•
60	•	•
65		•
70		•
75		•
80		•
85		•
90		•
100		•


Larger diameters, up to 200 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Cold work steel and plastic mould steel. High surface hardness with high core toughness. Excellent machinability, good cold hobbing and polishing properties. The even component strength is a result of the combination of hardened surface and high core toughness. Surface working hardness: 58-60 HRC.

**Applications**

Mechanical engineering, jig construction, plant engineering, apparatus engineering, plastic processing, plastic moulds, synthetic resin mould tools, base plates, bending bars, guide columns, gear parts, joint parts, shafts, gears, rods, bevel gears, crown wheels, piston pins, camshafts, bolts, pins, cardan joints.

**Tolerances****Standard values**

Delivery condition: maximum 217 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,18	0,15	1,1	0	0	1,0
0,24	0,35	1,4	0,03	0,03	1,3

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/2162-8

**AISI / SAE 1.2162 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2162

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.23161.2312
P20+S1.2311
P201.2294
1.22941.2210
L2**1.2162**
1.21621.2099
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR1.2080 mod.
D3 mod.1.2067
L3 / L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44



PREMIUM 1.2099 – AISI / SAE 1.2099 (~X5CrS12)

Precision flat steel with machining allowance [PFS/BA]

Length: 500 mm


	THICKNESS [mm]									
	6,2	8,2	10,3	15,3	20,3	25,3	30,3	40,3	50,3	
WIDTH	Available dimensions [mm]									
20,3	■	■	■							
25,3	■	■	■	■						
30,3	■	■	■	■	■					
40,3	■	■	■	■	■	■				
50,3	■	■	■	■	■	■	■			
60,3	■	■	■	■	■	■	■	■		
80,3	■	■	■	■	■	■	■	■	■	
100,3	■	■	■	■	■	■	■	■	■	■
125,3	■	■	■	■	■	■	■	■	■	■
150,3	■	■	■	■	■	■	■	■	■	■
200,3	■	■	■	■	■	■	■	■	■	■
250,3	■	■	■	■	■	■	■	■	■	■
300,3	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Pre-hardened, corrosion resistant plastic mould steel. Magnetisable, excellent machinability and good weldability. Resistant to aggressive plastics and humid conditions. Further heat treatment is not intended. Working hardness: approx. 33 HRC (reference value for delivery condition).

**Applications**

Mechanical engineering, apparatus engineering, plastic processing, injection tools, base plates, assembling parts, moulding frames, plastic moulds, extrusion tools, valves, steam valves, water valves, fittings parts, pump construction, pump rods, compressor construction, compressor parts, surgical instruments.

**Tolerances****Standard values**

Delivery condition: maximum 330 HB

Chemical composition (+additives):

C	Mn	S	Cr
0,05	1,0	0,12	12,5
0,05	1,0	0,12	12,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**
www.premium-steel.eu/2099-3
**AISI / SAE 1.2099 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2099

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.23161.2312
P20+S1.2311
P201.2294
1.22941.2210
L21.2162
1.2162**1.2099**
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR1.2080 mod.
D3 mod.1.2067
L3 / L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

PREMIUM 1.2099 – AISI / SAE 1.2099 (~X5CrS12)

€co-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]																
	2,3	3,3	4,3	5,3	6,3	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3
WIDTH	Available dimensions [mm]																
33	■	■	■	■	■	■											
43	■	■	■	■	■	■											
53	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
63	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
73	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
83	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
93	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
323	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
343	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
353	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
363	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
383	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
403	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
423	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
443	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
453	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
463	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
483	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
503	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Pre-hardened, corrosion resistant plastic mould steel. Magnetisable, excellent machinability and good weldability. Resistant to aggressive plastics and humid conditions. Further heat treatment is not intended. Working hardness: approx. 33 HRC (reference value for delivery condition).

**Applications**

Mechanical engineering, apparatus engineering, plastic processing, injection tools, base plates, assembling parts, moulding frames, plastic moulds, extrusion tools, valves, steam valves, water valves, fittings parts, pump construction, pump rods, compressor construction, compressor parts, surgical instruments.

**Tolerances****Standard values**

Delivery condition: maximum 330 HB
Chemical composition (+additives):

C	Mn	S	Cr
0,05	1,0	0,12	12,5
0,05	1,0	0,12	12,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/2099-5

**AISI / SAE 1.2099 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2099

via smartphone/tablet:



PREMIUM 1.2099 – AISI / SAE 1.2099 (~X5CrS12)

Precision round steel with machining allowance [PRS/BA]

Specification: peeled / rough-turned

	LENGTH [mm]	
	500	1.000
Ø [mm]	Available dimensions [•]	
35,5	•	•
45,5	•	•
55,5	•	•
65,5	•	•
85,5		•
90,5		•
100,5		•


Larger diameters, up to 180,5 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Pre-hardened, corrosion resistant plastic mould steel. Magnetisable, excellent machinability and good weldability. Resistant to aggressive plastics and humid conditions. Further heat treatment is not intended. Working hardness: approx. 33 HRC (reference value for delivery condition).

**Applications**

Mechanical engineering, apparatus engineering, plastic processing, injection tools, base plates, assembling parts, moulding frames, plastic moulds, extrusion tools, valves, steam valves, water valves, fittings parts, pump construction, pump rods, compressor construction, compressor parts, surgical instruments.

**Tolerances****Standard values**

Delivery condition: maximum 330 HB
Chemical composition (+additives):

C	Mn	S	Cr
0,05	1,0	0,12	12,5
0,05	1,0	0,12	12,5

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/2099-7

**AISI / SAE 1.2099 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2099

via smartphone / tablet:

NAVIGATION/
STEEL GRADES

1.2343
H11

1.2343 ESU
H11 ESR

1.2316
1.2316

1.2312
P20+S

1.2311
P20

1.2294
1.2294

1.2210
L2

1.2162
1.2162

1.2099
1.2099

1.2085
420FM

1.2083
420

1.2083 ESU
420 ESR

1.2080 mod.
D3 mod.

1.2067
L3 / L1

1.1730
1045

1.0570
1.0570

Toolox 33
Toolox 33

Toolox 44
Toolox 44

PREMIUM 1.2085/1.2099 – AISI / SAE 420FM/1.2099 (X33CrS16/~X5CrS12)

Precision flat steel with machining allowance [PFS/BA]

Length: 500 mm

		THICKNESS [mm]										
		6,2	8,2	10,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	80,3
WIDTH		Available dimensions [mm]										
20,3	1.2316 H11	■	■	■	■	■						
25,3	1.2316 H11 ESR	■	■	■	■	■	■					
30,3	1.2312 P20+S	■	■	■	■	■	■	■				
40,3	1.2311 P20	■	■	■	■	■	■	■	■			
50,3	1.2294	■	■	■	■	■	■	■	■	■		
60,3	1.2294	■	■	■	■	■	■	■	■	■	■	
80,3	1.2210 L2	■	■	■	■	■	■	■	■	■	■	■
100,3	1.2162	■	■	■	■	■	■	■	■	■	■	■
125,3	1.2162	■	■	■	■	■	■	■	■	■	■	■
150,3	1.2099	■	■	■	■	■	■	■	■	■	■	■
200,3	1.2099	■	■	■	■	■	■	■	■	■	■	■
250,3		■	■	■	■	■	■	■	■	■	■	■
300,3		■	■	■	■	■	■	■	■	■	■	■

* **Note:** AISI / SAE 420FM will be delivered in tempered condition (approx. 33 HRC). Therefore it can be easily substituted with AISI / SAE 1.2099.


If a higher working hardness is needed, please contact us!

**Technical properties**

Pre-hardened, corrosion-resistant plastic mould steel. Magnetisable with good machinability. Resistant to aggressive plastics and humid conditions. Because of the added sulphur it is easier to machine than steel grade AISI / SAE 1.2316. Further heat treatment is not intended. Working hardness: approx. 33 HRC (delivery condition) up to 48 HRC*.

**Applications**

Mechanical engineering, apparatus engineering, plastic processing, injection tools, base plates, assembling parts, moulding frames, plastic moulds, extrusion tools, valves, steam valves, water valves, fittings parts, pump construction, pump rods, compressor construction, compressor parts, surgical instruments.

**Tolerances****Standard values (AISI / SAE 420FM)**

Delivery condition: maximum 330 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Ni
0,28	0	0	0	0,05	15,0	0
0,38	1,0	1,4	0,03	0,1	17,0	1,0

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/420FM-3

**AISI / SAE 420FM – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/420FM

via smartphone/tablet:




PREMIUM 1.2085/1.2099 – AISI / SAE 420FM/1.2099 (X33CrS16/~X5CrS12)

Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm

	THICKNESS [mm]										
	8,2	10,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	80,3	
WIDTH	Available dimensions [mm]										
20,3	■	■	■	■							
25,3	■	■	■	■	■						
30,3	■	■	■	■	■	■					
40,3	■	■	■	■	■	■	■				
50,3	■	■	■	■	■	■	■	■			
60,3	■	■	■	■	■	■	■	■	■		
80,3	■	■	■	■	■	■	■	■	■	■	
100,3	■	■	■	■	■	■	■	■	■	■	■
125,3	■	■	■	■	■	■	■	■	■	■	■
150,3	■	■	■	■	■	■	■	■	■	■	■
200,3	■	■	■	■	■	■	■	■	■	■	■
250,3	■	■	■	■	■	■	■	■	■	■	■
300,3	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values (AISI / SAE 420FM)**

Delivery condition: maximum 330 HB

Chemical composition:

C	Si	Mn	P	S	Cr	Ni
0,28	0	0	0	0,05	15,0	0
0,38	1,0	1,4	0,03	0,1	17,0	1,0

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**www.premium-steel.eu/420FM-4**Technical properties**

Pre-hardened, corrosion-resistant plastic mould steel. Magnetisable with good machinability. Resistant to aggressive plastics and humid conditions. Because of the added sulphur it is easier to machine than steel grade AISI / SAE 1.2316. Further heat treatment is not intended. Working hardness: approx. 33 HRC (delivery condition) up to 48 HRC*.

**Applications**

Mechanical engineering, apparatus engineering, plastic processing, injection tools, base plates, assembling parts, moulding frames, plastic moulds, extrusion tools, valves, steam valves, water valves, fittings parts, pump construction, pump rods, compressor construction, compressor parts, surgical instruments.

**AISI / SAE 420FM – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/420FM

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.23161.2312
P20+S1.2311
P201.2294
1.22941.2210
L21.2162
1.21621.2099
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR1.2080 mod.
D3 mod.1.2067
L3 / L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

PREMIUM 1.2085/1.2099 – AISI / SAE 420FM/1.2099 (X33CrS16/~X5CrS12)

€co-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]																
	2,3	3,3	4,3	5,3	6,3	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3
WIDTH	Available dimensions [mm]																
33	■	■	■	■	■	■	■	■	■	■	■	■					
43	■	■	■	■	■	■	■	■	■	■	■	■	■				
53	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
63	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
73	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
83	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
93	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
323	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
343	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
353	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
363	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
383	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
403	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
423	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
443	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
453	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
463	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
483	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
503	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Pre-hardened, corrosion-resistant plastic mould steel. Magnetisable with good machinability. Resistant to aggressive plastics and humid conditions. Because of the added sulphur it is easier to machine than steel grade AISI / SAE 1.2316. Further heat treatment is not intended. Working hardness: approx. 33 HRC (delivery condition) up to 48 HRC*.

**Applications**

Mechanical engineering, apparatus engineering, plastic processing, injection tools, base plates, assembling parts, moulding frames, plastic moulds, extrusion tools, valves, steam valves, water valves, fittings parts, pump construction, pump rods, compressor construction, compressor parts, surgical instruments.

**Tolerances****Standard values (AISI / SAE 420FM)**

Delivery condition: maximum 330 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Ni
0,28	0	0	0	0,05	15,0	0
0,38	1,0	1,4	0,03	0,1	17,0	1,0

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/420FM-5

**AISI / SAE 420FM – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/420FM

via smartphone/tablet:




PREMIUM 1.2085/1.2099 – AISI / SAE 420FM/1.2099 (X33CrS16/~X5CrS12)

Precision round steel with machining allowance [PRS/BA]

Specification: peeled / rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
Available dimensions [•]		
35,5	•	•
45,5	•	•
55,5	•	•
65,5	•	•
85,5		•
90,5		•
100,5		•


Larger diameters, up to 180,5 mm, and different lengths (e.g. round blanks) available on request!

*** Note:** AISI / SAE 420FM will bedelivered in tempered condition
(approx. 33 HRC).Therefore it can be easily substituted
with AISI / SAE 1.2099.If a higher working hardness is
needed, please contact us!**Technical properties**

Pre-hardened, corrosion-resistant plastic mould steel. Magnetisable with good machinability. Resistant to aggressive plastics and humid conditions. Because of the added sulphur it is easier to machine than steel grade AISI / SAE 1.2316. Further heat treatment is not intended. Working hardness: approx. 33 HRC (delivery condition) up to 48 HRC*.

**Applications**

Mechanical engineering, apparatus engineering, plastic processing, injection tools, base plates, assembling parts, moulding frames, plastic moulds, extrusion tools, valves, steam valves, water valves, fittings parts, pump construction, pump rods, compressor construction, compressor parts, surgical instruments.

**Tolerances****Standard values (AISI / SAE 420FM)**

Delivery condition: maximum 330 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Ni
0,28	0	0	0	0,05	15,0	0
0,38	1,0	1,4	0,03	0,1	17,0	1,0

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/420FM-7

**AISI / SAE 420FM – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/420FM

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.23161.2312
P20+S1.2311
P201.2294
1.22941.2210
L21.2162
1.21621.2099
1.2099**1.2085**
420FM1.2083
4201.2083 ESU
420 ESR1.2080 mod.
D3 mod.1.2067
L3 / L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

PREMIUM 1.2083 – AISI / SAE ~420 (X40Cr14)

Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm

	THICKNESS [mm]															
	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	40,3	50,3	60,3	70,3	80,3	100,3	
WIDTH	Available dimensions [mm]															
15,3				■												
20,3	■	■	■	■	■	■										
25,3	■	■	■	■	■	■	■									
30,3	■	■	■	■	■	■	■	■								
32,3		■		■	■	■	■		■							
40,3	■	■	■	■	■	■	■	■	■	■						
50,3	■	■	■	■	■	■	■	■	■	■	■					
60,3	■	■	■	■	■	■	■	■	■	■	■	■				
70,3	■	■	■	■	■	■	■	■	■	■	■	■	■			
80,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
90,3	■	■	■	■		■	■	■	■	■	■	■	■	■		
100,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
120,3		■	■	■	■	■	■	■	■	■	■	■	■	■	■	
130,3		■	■	■	■	■	■	■	■	■	■	■	■	■	■	
140,3		■	■	■		■	■	■	■	■	■	■	■	■	■	
150,3		■	■	■	■	■	■	■	■	■	■	■	■	■	■	
200,3		■	■	■	■	■	■	■	■	■	■	■	■	■	■	
250,3		■	■	■	■	■	■	■	■	■						
300,3		■	■	■	■	■	■	■	■							
500 *		■	■	■	■	■	■	■	■	■	■					

* Width and length sawn/raw with +tol./-0 mm


**Technical properties**

Corrosion-resistant cold work steel and plastic mould steel, good machinability. Can be hardened and polished. Low distortion through-hardening steel with high hardness and high wear resistance. For maximum required polishability use the ESR (Electro Slag Remelted Steel) production.

Working hardness: 50-55 HRC.

**Applications**

Mechanical engineering, medical technology, plastic moulds, synthetic resin mould tools, die casting tools, light metal die casting, cutting tools, machine knives, kitchen knives, razors, shears, scraper blades, surgical instruments, measuring tools, roller bearings, ball bearings, ice-skates, pump parts, valves.

**Tolerances****Standard values**

Delivery condition: maximum 241 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,36	0	0	0	0	12,5
0,42	1,0	1,0	0,03	0,03	14,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/420-4

**AISI / SAE 420 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/420

via smartphone/tablet:



PREMIUM 1.2083 – AISI / SAE ~420 (X40Cr14)

Eco-Präz® 500 [€co]

Length: 500 mm


WIDTH	THICKNESS [mm]													
	2,3	3,3	4,3	5,3	6,3	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3
	Available dimensions [mm]													
33	■	■	■	■	■	■	■	■	■	■	■	■	■	■
43	■	■	■	■	■	■	■	■	■	■	■	■	■	■
53	■	■	■	■	■	■	■	■	■	■	■	■	■	■
63	■	■	■	■	■	■	■	■	■	■	■	■	■	■
73	■	■	■	■	■	■	■	■	■	■	■	■	■	■
83	■	■	■	■	■	■	■	■	■	■	■	■	■	■
93	■	■	■	■	■	■	■	■	■	■	■	■	■	■
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■
323	■	■	■	■	■	■	■	■	■	■	■	■	■	■
343	■	■	■	■	■	■	■	■	■	■	■	■	■	■
353	■	■	■	■	■	■	■	■	■	■	■	■	■	■
363	■	■	■	■	■	■	■	■	■	■	■	■	■	■
383	■	■	■	■	■	■	■	■	■	■	■	■	■	■
403	■	■	■	■	■	■	■	■	■	■	■	■	■	■
423	■	■	■	■	■	■	■	■	■	■	■	■	■	■
443	■	■	■	■	■	■	■	■	■	■	■	■	■	■
453	■	■	■	■	■	■	■	■	■	■	■	■	■	■
463	■	■	■	■	■	■	■	■	■	■	■	■	■	■
483	■	■	■	■	■	■	■	■	■	■	■	■	■	■
503	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Corrosion-resistant cold work steel and plastic mould steel, good machinability. Can be hardened and polished. Low distortion through-hardening steel with high hardness and high wear resistance. For maximum required polishability use the ESR (Electro Slag Remelted Steel) production.
Working hardness: 50-55 HRC.

**Applications**

Mechanical engineering, medical technology, plastic moulds, synthetic resin mould tools, die casting tools, light metal die casting, cutting tools, machine knives, kitchen knives, razors, shears, scraper blades, surgical instruments, measuring tools, roller bearings, ball bearings, ice-skates, pump parts, valves.

**Tolerances****Standard values**

Delivery condition: maximum 241 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,36	0	0	0	0	12,5
0,42	1,0	1,0	0,03	0,03	14,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/420-5

**AISI / SAE 420 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/420

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.23161.2312
P20+S1.2311
P201.2294
1.22941.2210
L21.2162
1.21621.2099
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR1.2080 mod.
D3 mod.1.2067
L3 / L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

PREMIUM 1.2083 – AISI / SAE ~420 (X40Cr14)**Hart-Präz® 250 [Hart]**

Length: 250 mm


	THICKNESS [mm]												
	2,2	2,7	3,2	3,7	4,2	4,7	5,2	6,2	7,2	8,2	9,2	10,2	12,2
WIDTH	Available dimensions [mm]												
250	■	■	■	■	■	■	■	■	■	■	■	■	■

Hart-Präz® 500 [Hart]

Length: 500 mm

	THICKNESS [mm]												
	2,2	2,7	3,2	3,7	4,2	4,7	5,2	6,2	7,2	8,2	9,2	10,2	12,2
WIDTH	Available dimensions [mm]												
250	■	■	■	■	■	■	■	■	■	■	■	■	■

Hardened dimensions are delivered with approx. 50 HRC, at least 2x tempered.


**NEW: Hart-Präz®****ALREADY HARDENED DIMENSIONS IN LENGTH OF 250 mm AND 500 mm !****Technical properties**

Corrosion-resistant cold work steel and plastic mould steel, good machinability. Can be hardened and polished. Low distortion through-hardening steel with high hardness and high wear resistance. For maximum required polishability use the ESR (Electro Slag Remelted Steel) production.

Working hardness: 50-55 HRC.

**Applications**

Mechanical engineering, medical technology, plastic moulds, synthetic resin mould tools, die casting tools, light metal die casting, cutting tools, machine knives, kitchen knives, razors, shears, scraper blades, surgical instruments, measuring tools, roller bearings, ball bearings, ice-skates, pump parts, valves.

**Tolerances****Standard values**

Lieferzustand: ca. 50 HRC

Chemical composition:

C	Si	Mn	P	S	Cr
0,36	0	0	0	0	12,5
0,42	1,0	1,0	0,03	0,03	14,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**
www.premium-steel.eu/420-11-H
**AISI / SAE 420 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/420

via smartphone/tablet:



PREMIUM 1.2083 – AISI / SAE ~420 (X40Cr14)


Precision round steel without machining allowance [PRS]
Specification: bright drawn/ground, ISO h9

Ø [mm]	LENGTH [mm]
	1.000
Available dimensions [•]	
15,0	•
16,0	•
18,0	•
20,0	•
25,0	•
30,0	•
35,0	•
40,0	•
45,0	•
50,0	•

Precision round steel with machining allowance [PRS/BA]
Specification: peeled / rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
Available dimensions [•]		
20,5	•	•
25,5	•	•
30,5	•	•
35,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
55,5	•	•
60,5	•	•
65,5		•
70,5		•
80,5		•
85,5		•
90,5		•
100,5		•

Larger diameters, up to 400,5 mm, and different lengths (e.g. round blanks) available on request!

**Tolerances****Standard values**

Delivery condition: maximum 241 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,36	0	0	0	0	12,5
0,42	1,0	1,0	0,03	0,03	14,5

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

[PRS]
www.premium-steel.eu/420-6
[PRS/BA]
www.premium-steel.eu/420-7

**Technical properties**

Corrosion-resistant cold work steel and plastic mould steel, good machinability. Can be hardened and polished. Low distortion through-hardening steel with high hardness and high wear resistance. For maximum required polishability use the ESR (Electro Slag Remelted Steel) production.
Working hardness: 50-55 HRC.

**Applications**

Mechanical engineering, medical technology, plastic moulds, synthetic resin mould tools, die casting tools, light metal die casting, cutting tools, machine knives, kitchen knives, razors, shears, scraper blades, surgical instruments, measuring tools, roller bearings, ball bearings, ice-skates, pump parts, valves.

**AISI / SAE 420 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/420

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2343
H11

1.2343 ESU
H11 ESR

1.2316
1.2316

1.2312
P20+S

1.2311
P20

1.2294
1.2294

1.2210
L2

1.2162
1.2162

1.2099
1.2099

1.2085
420FM

1.2083
420

1.2083 ESU
420 ESR

1.2080 mod.
D3 mod.

1.2067
L3 / L1

1.1730
1045

1.0570
1.0570

Toolox 33
Toolox 33


Toolox 44
Toolox 44

PREMIUM 1.2083 ESU – AISI / SAE 420 ESR (X40Cr14)

Eco-Präz® 300 [€co]

Length: 300 mm

	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values**

Delivery condition: maximum 241 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,36	0	0	0	0	12,5
0,42	1,0	1,0	0,03	0,03	14,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/420ESR-3-5

**Technical properties**

Corrosion-resistant cold work steel and plastic mould steel, good machinability, good hardenability and excellent polishing properties. Low distortion through-hardening steel with high hardness and high wear resistance. For maximum required polishability use the ESR (Electro Slag Remelted Steel) production.
Working hardness: 50-55 HRC.

**Applications**

Mechanical engineering, medical technology, plastic moulds, synthetic resin mould tools, die casting tools, light metal die casting, cutting tools, machine knives, kitchen knives, razors, shears, scraper blades, surgical instruments, measuring tools, roller bearings, ball bearings, ice-skates, pump parts, valves.



AISI / SAE 420 ESR – all at a glance!
Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/420ESR

via smartphone/tablet:



PREMIUM 1.2083 ESU – AISI / SAE 420 ESR (X40Cr14)

Eco-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Corrosion-resistant cold work steel and plastic mould steel, good machinability, good hardenability and excellent polishing properties. Low distortion through-hardening steel with high hardness and high wear resistance. For maximum required polishability use the ESR (Electro Slag Remelted Steel) production. Working hardness: 50-55 HRC.

**Applications**

Mechanical engineering, medical technology, plastic moulds, synthetic resin mould tools, die casting tools, light metal die casting, cutting tools, machine knives, kitchen knives, razors, shears, scraper blades, surgical instruments, measuring tools, roller bearings, ball bearings, ice-skates, pump parts, valves.

**Tolerances****Standard values**

Delivery condition: maximum 241 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,36	0	0	0	0	12,5
0,42	1,0	1,0	0,03	0,03	14,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/420ESR-5-5

AISI / SAE 420 ESR – all at a glance!
Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/420ESR

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.23161.2312
P20+S1.2311
P201.2294
1.22941.2210
L21.2162
1.21621.2099
1.20991.2085
420FM1.2083
420**1.2083 ESU
420 ESR**1.2080 mod.
D3 mod.1.2067
L3 / L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

ABRAMS®

TOOL STEEL I

TOOL STEEL II

HIGH SPEED STEEL

STAINLESS STEEL
corrosion resistant / acid resistant

HEAT-TREATABLE STEEL,
CASE HARDENING- &
NITRIDING STEEL

INFORMATION



365 DAYS A YEAR – WE ARE HERE FOR YOU – VISIT OUR ONLINE SHOP AT WWW.PREMIUM-STEEL.EU

ABRAMS![®]
PREMIUM STEEL

PREMIUM 1.2080 mod. – AISI / SAE D3 mod. (~X210Cr12)

Precision flat steel without machining allowance, DIN 59350 [PFS]

Length: 500 mm

	THICKNESS [mm]										
	2,0	3,0	4,0	5,0	6,0	8,0	10,0	12,0	15,0	20,0	
WIDTH	Available dimensions [mm]										
20,0	■	■	■	■	■	■	■	■	■	■	
25,0	■	■	■	■	■	■	■	■	■	■	■
30,0	■	■	■	■	■	■	■	■	■	■	■
40,0	■	■	■	■	■	■	■	■	■	■	■
50,0	■	■	■	■	■	■	■	■	■	■	■
60,0	■	■	■	■	■	■	■	■	■	■	■
80,0	■	■	■	■	■	■	■	■	■	■	■
100,0	■	■	■	■	■	■	■	■	■	■	■
125,0	■	■	■	■	■	■	■	■	■	■	■
150,0	■	■	■	■	■	■	■	■	■	■	■
200,0	■	■	■	■	■	■	■	■	■	■	■


**Technical properties**

Cold work steel with excellent wear resistance, due to its high chromium carbide content, and excellent cutting power (for laminations up to a thickness of 4 mm). Full hardenability, dimensional stability but medium toughness. The classic among the ledeburite 12% chromium steels.

Working hardness: 58-62 HRC.

**Applications**

Blanking tools, stamping tools, embossing tools, scraping tools, trimming tools, woodworking tools, drawing tools, press tools, stone moulds, sintered tools, machine knives, hammer cores, ring rollers, thread rolling dies, plastic moulds.

**Tolerances****Standard values**

Delivery condition: maximum 255 HB
Chemical composition:

C	Si	Mn	P	S	Cr	W
1,9	0,1	0,2	0	0	11,0	≤
2,2	0,6	0,6	0,03	0,03	13,0	0,8

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/D3mod-1

**AISI / SAE D3 mod.– all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for
alternatives:

www.premium-steel.eu/D3mod

via smartphone/tablet:


NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.23161.2312
P20+S1.2311
P201.2294
1.22941.2210
L21.2162
1.21621.2099
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR**1.2080 mod.
D3 mod.**1.2067
L3 / L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

PREMIUM 1.2080 mod. – AISI / SAE D3 mod. (~X210Cr12)

Precision flat steel with machining allowance [PFS/BA]

Length: 500 mm

WIDTH	THICKNESS [mm]													
	2,2	3,2	4,2	5,2	6,2	8,2	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3
Available dimensions [mm]														
8,2						■								
10,3	■	■	■	■	■	■	■							
12,3								■						
15,3	■	■	■	■	■	■	■	■	■					
20,3	■	■	■	■	■	■	■	■	■	■				
25,3	■	■	■	■	■	■	■	■	■	■	■			
30,3	■	■	■	■	■	■	■	■	■	■	■	■		
40,3	■	■	■	■	■	■	■	■	■	■	■	■	■	
50,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■
60,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■
80,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■
100,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■
125,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■
150,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■
200,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■
250,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■
300,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values**

Delivery condition: maximum 255 HB
Chemical composition:

C	Si	Mn	P	S	Cr	W
1,9	0,1	0,2	0	0	11,0	≤
2,2	0,6	0,6	0,03	0,03	13,0	0,8

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/D3mod-3

**Technical properties**

Cold work steel with excellent wear resistance, due to its high chromium carbide content, and excellent cutting power (for laminations up to a thickness of 4 mm). Full hardenability, dimensional stability but medium toughness. The classic among the ledeburite 12% chromium steels.

Working hardness: 58-62 HRC.

**Applications**

Blanking tools, stamping tools, embossing tools, scraping tools, trimming tools, woodworking tools, drawing tools, press tools, stone moulds, sintered tools, machine knives, hammer cores, ring rollers, thread rolling dies, plastic moulds.



AISI / SAE D3 mod.– all at a glance!
Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/D3mod

via smartphone / tablet:



PREMIUM 1.2080 mod. – AISI / SAE D3 mod. (~X210Cr12)

Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm

	THICKNESS [mm]															
	2,2	3,2	4,2	5,2	6,2	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	40,3	50,3
WIDTH	Available dimensions [mm]															
8,2																
10,3	■	■	■	■	■	■	■									
12,3								■								
15,3	■	■	■	■	■	■	■	■	■							
16,3										■						
20,3	■	■	■	■	■	■	■	■	■	■	■					
25,3	■	■	■	■	■	■	■	■	■	■	■	■				
30,3	■	■	■	■	■	■	■	■	■	■	■	■	■			
32,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
40,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
50,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
60,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
63,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
80,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
100,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
125,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
150,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
160,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
175,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
200,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
250,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
300,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
315,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■


**Technical properties**

Cold work steel with excellent wear resistance, due to its high chromium carbide content, and excellent cutting power (for laminations up to a thickness of 4 mm). Full hardenability, dimensional stability but medium toughness. The classic among the ledeburite 12% chromium steels.

Working hardness: 58-62 HRC.

**Applications**

Blanking tools, stamping tools, embossing tools, scraping tools, trimming tools, woodworking tools, drawing tools, press tools, stone moulds, sintered tools, machine knives, hammer cores, ring rollers, thread rolling dies, plastic moulds.

**Tolerances****Standard values**

Delivery condition: maximum 255 HB
Chemical composition:

C	Si	Mn	P	S	Cr	W
1,9	0,1	0,2	0	0	11,0	≤
2,2	0,6	0,6	0,03	0,03	13,0	0,8

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/D3mod-4

**AISI / SAE D3 mod.– all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/D3mod

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.23161.2312
P20+S1.2311
P201.2294
1.22941.2210
L21.2162
1.21621.2099
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR1.2080 mod.
D3 mod.1.2067
L3 / L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

PREMIUM 1.2080 mod. – AISI / SAE D3 mod. (~X210Cr12)

Hart-Präz® 250 [Hart]

Length: 250 mm


	THICKNESS [mm]												
	2,2	2,7	3,2	3,7	4,2	4,7	5,2	6,2	7,2	8,2	9,2	10,2	12,2
WIDTH	Available dimensions [mm]												
250	■	■	■	■	■	■	■	■	■	■	■	■	■

Hart-Präz® 500 [Hart]

Length: 500 mm

	THICKNESS [mm]												
	2,2	2,7	3,2	3,7	4,2	4,7	5,2	6,2	7,2	8,2	9,2	10,2	12,2
WIDTH	Available dimensions [mm]												
250	■	■	■	■	■	■	■	■	■	■	■	■	■

Hardened dimensions are delivered with approx. 59 HRC, at least 2x tempered.



NEW: Hart-Präz®

ALREADY HARDENED DIMENSIONS IN LENGTH OF 250 mm AND 500 mm !



Technical properties

Cold work steel with excellent wear resistance, due to its high chromium carbide content, and excellent cutting power (for laminations up to a thickness of 4 mm). Full hardenability, dimensional stability but medium toughness. The classic among the ledeburite 12% chromium steels.

Working hardness: 58-62 HRC.




Applications

Blanking tools, stamping tools, embossing tools, scraping tools, trimming tools, woodworking tools, drawing tools, press tools, stone moulds, sintered tools, machine knives, hammer cores, ring rollers, thread rolling dies, plastic moulds.



Tolerances



Standard values

Delivery condition: approx. 59 HRC

Chemical composition:

C	Si	Mn	P	S	Cr	W
1,9	0,1	0,2	0	0	11,0	≤
2,2	0,6	0,6	0,03	0,03	13,0	0,8



If you need customised dimensions -

Any dimension available in different heights, widths and lengths.

On request - according to your needs!



Contact us

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu



Direct access to our online shop

www.premium-steel.eu/D3mod-11-H



AISI / SAE D3 mod.– all at a glance!

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/D3mod

via smartphone/tablet:



PREMIUM 1.2080 mod. – AISI / SAE D3 mod. (~X210Cr12)

Precision round steel with machining allowance [PRS/BA]

Specification: peeled / rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
10,5	•	•
13,5	•	•
14,5	•	•
15,5	•	•
16,5	•	•
18,5	•	•
19,5	•	•
20,5	•	•
22,5	•	•
25,5	•	•
28,5	•	•
30,5	•	•
32,5	•	•
35,5	•	•
38,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
55,5	•	•
60,5	•	•
65,5		•
70,5		•
75,5		•
80,5		•
85,5		•
90,5		•
95,5		•
100,5		•

Larger diameters, up to 520,5 mm, and different lengths (e.g. round blanks) available on request!


**Technical properties**

Cold work steel with excellent wear resistance, due to its high chromium carbide content, and excellent cutting power (for laminations up to a thickness of 4 mm). Full hardenability, dimensional stability but medium toughness. The classic among the ledeburite 12% chromium steels.

Working hardness: 58-62 HRC.

**Applications**

Blanking tools, stamping tools, embossing tools, scraping tools, trimming tools, woodworking tools, drawing tools, press tools, stone moulds, sintered tools, machine knives, hammer cores, ring rollers, thread rolling dies, plastic moulds.

**Tolerances****Standard values**

Delivery condition: maximum 255 HB
Chemical composition:

C	Si	Mn	P	S	Cr	W
1,9	0,1	0,2	0	0	11,0	≤
2,2	0,6	0,6	0,03	0,03	13,0	0,8

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**www.premium-steel.eu/D3mod-7**AISI / SAE D3 mod. – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/D3mod

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.23161.2312
P20+S1.2311
P201.2294
1.22941.2210
L21.2162
1.21621.2099
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR**1.2080 mod.
D3 mod.**1.2067
L3 / L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

PREMIUM 1.2067/1.3505 – AISI / SAE L3/L1 (102Cr6/100Cr6)

€co-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]																			
	2,3	3,3	4,3	5,3	6,3	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3
WIDTH	Available dimensions [mm]																			
33	■	■	■	■	■	■	■	■	■	■	■	■								
43	■	■	■	■	■	■	■	■	■	■	■	■	■							
53	■	■	■	■	■	■	■	■	■	■	■	■	■	■						
63	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■					
73	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
83	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
93	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
323	■	■	■	■	■															
343	■	■	■	■	■															
353	■	■	■	■	■															
363	■	■	■	■	■															
383	■	■	■	■	■															
403	■	■	■	■	■															
423	■	■	■	■	■															
443	■	■	■	■	■															
453	■	■	■	■	■															
463	■	■	■	■	■															
483	■	■	■	■	■															
503	■	■	■	■	■															

**Technical properties**

An all-purpose medium alloyed cold work tool steel with high hardenability, but low depth of hardening, good wear resistance and toughness. This steel grade belongs to the group of AISI / SAE L1 (roller bearing and ball bearing steel). Working hardness: 60-64 HRC.

**Applications**

Drills, threading tools, centre lathes, milling cutters, reamers, small die plates, pressure rollers, cold rollings, measuring tools, cold pilger rollings, cold pilger jaws, gauges, mandrels, woodworking tools, cold extrusion tools, flanging rollers, shear knives, roller bearings, ball bearings (medium to large size).

**Tolerances****Standard values (AISI / SAE L3)**

Delivery condition: maximum 223 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni
0,95	0,15	0,2	0	0	1,35	0	0
1,1	0,35	0,4	0,025	0,025	1,6	0,1	0,4

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/L3-5

**AISI / SAE L3 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/L3

via smartphone/tablet:



PREMIUM 1.2067/1.3505 – AISI / SAE L3/L1 (102Cr6/100Cr6)


Precision round steel without machining allowance [PRS]
Specification: bright drawn/ground, ISO h9

	LENGTH [mm]
	1.000
Ø [mm]	Available dimensions [•]
8,0	•
10,0	•
12,0	•
13,0	•
14,0	•
15,0	•
16,0	•
17,0	•
18,0	•
19,0	•
20,0	•
25,0	•
30,0	•
32,0	•
35,0	•
38,0	•
40,0	•
45,0	•
50,0	•
55,0	•
60,0	•

Precision round steel [PRS/BA]
Specification: peeled /rough-turned

	LENGTH [mm]
	1.000
Ø [mm]	Available dimensions [•]
65,0	•
70,0	•
75,0	•
80,0	•
85,0	•
90,0	•
95,0	•
100,0	•

Larger diameters, up to 242,0 mm, and different lengths (e.g. round blanks) available on request!

**Tolerances****Standard values (AISI / SAE L3)**

Delivery condition: maximum 223 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni
0,95	0,15	0,2	0	0	1,35	0	0
1,1	0,35	0,4	0,025	0,025	1,6	0,1	0,4

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop [PRS]**

www.premium-steel.eu/L3-6
[PRS/BA]
www.premium-steel.eu/L3-7

**Technical properties**

An all-purpose medium alloyed cold work tool steel with high hardenability, but low depth of hardening, good wear resistance and toughness. This steel grade belongs to the group of AISI / SAE L1 (roller bearing and ball bearing steel). Working hardness: 60-64 HRC.

**Applications**

Drills, threading tools, centre lathes, milling cutters, reamers, small die plates, pressure rollers, cold rollings, measuring tools, cold pilger rollings, cold pilger jaws, gauges, mandrels, woodworking tools, cold extrusion tools, flanging rollers, shear knives, roller bearings, ball bearings (medium to large size).

**AISI / SAE L3/L1 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.2067

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.23161.2312
P20+S1.2311
P201.2294
1.22941.2210
L21.2162
1.21621.2099
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR1.2080 mod.
D3 mod.**1.2067**
L3 / L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

PREMIUM 1.1730 – AISI / SAE 1045 (C45U)

Precision flat steel without machining allowance [PFS]

Length: 500 mm

	THICKNESS [mm]																				
	4,0	5,0	6,0	8,0	10,0	12,0	15,0	16,0	20,0	25,0	30,0	32,0	40,0	50,0	60,0	63,0	70,0	80,0	100,0	120,0	150,0
WIDTH	Available dimensions [mm]																				
10,0					■																
12,0						■															
15,0							■														
16,0								■													
20,0	■	■	■	■	■	■	■		■												
25,0	■	■	■	■	■	■	■	■		■											
30,0	■	■	■	■	■	■	■		■	■	■										
32,0	■	■	■	■	■	■		■	■	■		■									
40,0	■	■	■	■	■	■	■	■	■	■	■		■								
50,0	■	■	■	■	■	■	■		■			■	■	■							
60,0	■	■	■	■	■	■	■		■	■	■		■	■	■						
63,0	■	■	■	■	■	■		■	■	■		■	■	■		■					
70,0	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		■				
80,0	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
90,0	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■			
100,0	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
120,0			■	■	■	■	■		■	■	■		■	■	■		■	■	■	■	■
125,0	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
140,0			■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	
150,0	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
160,0	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
175,0			■	■	■	■		■	■	■		■	■	■		■		■	■	■	
180,0			■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■
200,0			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
250,0			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
300,0			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
315,0			■	■	■	■		■	■	■		■	■	■		■		■	■	■	
350,0			■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	
400,0	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
450,0									■	■	■	■	■	■	■	■	■	■	■	■	
500 *					■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	


* Width and length sawn/raw with +tol./-0 mm

**Technical properties**

Unalloyed tool steel with excellent machining properties for unhardened parts e.g. fixture construction, due to its carbon proportion (0,45%) it can be hardened, but has a low depth of hardening. Shallow depth case-hardening steel with a hard surface and a tough core. Working hardness: approx. 190 HB (annealed) up to 54 HRC (surface hardness).

**Applications**

Mechanical engineering, construction materials, jigs, base plates, moulding frames, small dies, hand tools, simple knives, sledges, pliers, forks, hatchets, axes, shears, screwdrivers, chisels.

**Tolerances****Standard values**

Delivery condition: approx. 190 HB
Chemical composition:

C	Si	Mn	P	S
0,42	0,15	0,6	0	0
0,5	0,4	0,8	0,03	0,03

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/1045-1

**AISI / SAE 1045 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1045

via smartphone / tablet:



PREMIUM 1.1730 – AISI / SAE 1045 (C45U)

Precision flat steel without machining allowance [PFS]

Length: 1.000 mm

		THICKNESS [mm]																							
		4,0	5,0	6,0	8,0	10,0	12,0	15,0	16,0	20,0	25,0	30,0	32,0	40,0	50,0	60,0	63,0	70,0	80,0	100,0	120,0	150,0			
WIDTH		Available dimensions [mm]																							
10,0						■																			
12,0							■																		
15,0								■																	
16,0									■																
20,0	■	■	■	■	■	■	■	■	■	■															
25,0	■	■	■	■	■	■	■	■	■	■	■														
30,0	■	■	■	■	■	■	■	■	■	■	■	■													
32,0	■	■	■	■	■	■	■	■	■	■	■	■	■												
40,0	■	■	■	■	■	■	■	■	■	■	■	■	■	■											
50,0	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■										
60,0	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■									
63,0	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■								
70,0	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■							
80,0	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■						
90,0	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■					
100,0	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
120,0				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
125,0	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
140,0				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
150,0	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
160,0	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
175,0				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
180,0				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
200,0				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
225,0				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
250,0				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
300,0				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
315,0				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
350,0				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
400,0	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
450,0										■	■	■	■	■	■	■	■	■	■	■	■	■	■		
500 *					■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		


* Width and length sawn/raw with +tol./-0 mm

**Technical properties**

Unalloyed tool steel with excellent machining properties for unhardened parts e.g. fixture construction, due to its carbon proportion (0,45%) it can be hardened, but has a low depth of hardening. Shallow depth case-hardening steel with a hard surface and a tough core. Working hardness: approx. 190 HB (annealed) up to 54 HRC (surface hardness).

**Applications**

Mechanical engineering, construction materials, jigs, base plates, moulding frames, small dies, hand tools, simple knives, sledges, pliers, forks, hatchets, axes, shears, screwdrivers, chisels.

**Tolerances****Standard values**

Delivery condition: approx. 190 HB

Chemical composition:

C	Si	Mn	P	S
0,42	0,15	0,6	0	0
0,5	0,4	0,8	0,03	0,03

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**
www.premium-steel.eu/1045-2
**AISI / SAE 1045 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1045

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.23161.2312
P20+S1.2311
P201.2294
1.22941.2210
L21.2162
1.21621.2099
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR1.2080 mod.
D3 mod.1.2067
L3 / L1**1.1730**
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

ABRAMS®

TOOL STEEL I

TOOL STEEL II

HIGH SPEED STEEL

STAINLESS STEEL
corrosion resistant / acid resistant

HEAT-TREATABLE STEEL,
CASE HARDENING- &
NITRIDING STEEL

INFORMATION



SHARPLY CALCULATED PRICES FOR PREMIUM-CUSTOMERS!

ABRAMS![®]
PREMIUM STEEL

PREMIUM 1.1730 – AISI / SAE 1045 (C45U)


Precision round steel without machining allowance [PRS]
Specification: bright drawn/ground, ISO h9

	LENGTH [mm]
	1.000
Ø [mm]	Available dimensions [•]
6,0	•
8,0	•
10,0	•
12,0	•
14,0	•
15,0	•
16,0	•
18,0	•
20,0	•
22,0	•
24,0	•
25,0	•
26,0	•
28,0	•
30,0	•
35,0	•
40,0	•
45,0	•
50,0	•
55,0	•
60,0	•

Round steel [RS]
Specification: black

	LENGTH [mm]
	500 1.000
Ø [mm]	Available dimensions [•]
15	• •
20	• •
25	• •
30	• •
35	• •
40	• •
45	• •
50	• •
55	• •
60	• •
65	• •
70	• •
75	• •
80	• •
85	• •
90	• •
95	• •
100	• •

Larger diameters, up to 750,5 mm, and different lengths (partly peeled/rough-turned) on request!

**Tolerances****Standard values**

Delivery condition: approx. 190 HB
Chemical composition:

C	Si	Mn	P	S
0,42	0,15	0,6	0	0
0,5	0,4	0,8	0,03	0,03

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

[PRS]
www.premium-steel.eu/1045-6
[RS]
www.premium-steel.eu/1045-8

**Technical properties**

Unalloyed tool steel with excellent machining properties for unhardened parts e.g. fixture construction, due to its carbon proportion (0,45%) it can be hardened, but has a low depth of hardening. Shallow depth case-hardening steel with a hard surface and a tough core. Working hardness: approx. 190 HB (annealed) up to 54 HRC (surface hardness).

**Applications**

Mechanical engineering, construction materials, jigs, base plates, moulding frames, small dies, hand tools, simple knives, sledges, pliers, forks, hatchets, axes, shears, screwdrivers, chisels.

**AISI / SAE 1045 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1045

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.23161.2312
P20+S1.2311
P201.2294
1.22941.2210
L21.2162
1.21621.2099
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR1.2080 mod.
D3 mod.1.2067
L3 / L1**1.1730**
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

PREMIUM 1.0570 – AISI / SAE 1.0570 (St 52-3/-S355J2+N)

Precision flat steel with machining allowance [PFS/BA]

Length: 500 mm

	THICKNESS [mm]																		
	4,2	5,2	6,2	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	40,3	50,3	60,3	63,3	70,3	80,3	100,3
WIDTH	Available dimensions [mm]																		
1.2343 H11																			
1.2343 ESU H11 ESR																			
1.2316																			
1.2316																			
1.2312 P20+S																			
1.2311 P20																			
1.2294																			
1.2294																			
1.2210 L2																			
1.2162																			
1.2162																			
1.2099																			
1.2099																			
1.2085 420FM																			
1.2083 420																			
1.2083 ESU 420 ESR																			
1.2080 mod. D3 mod.																			
1.2067 L3/L1																			
1.1730 1045																			
1.0570 1.0570																			
Toolox 33																			
Toolox 33																			
Toolox 44																			
Toolox 44																			


* Width and length sawn/raw with +tol./-0 mm

**Technical properties**

Unalloyed structural steel with good machinability and dimensional stability, high toughness and good weldability because of its low carbon content ($C \leq 0,22\%$). This grade is only used for unhardened components. Working hardness: approx. 180 HB (annealed).

**Applications**

Mechanical engineering, base plates, moulding frames, construction materials, steel frames, hand tools, knives, sledge hammers, spanners.

**Tolerances****Standard values**

Delivery condition: maximum 180 HB
Chemical composition:

C	Si	Mn	P	S
0	0	0	0	0
0,22	0,55	1,6	0,035	0,035

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/0570-3

**AISI / SAE 1.0570 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.0570

via smartphone / tablet:



PREMIUM 1.0570 – AISI / SAE 1.0570 (St 52-3/-S355J2+N)

Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm

	THICKNESS [mm]																		
	4,2	5,2	6,2	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	40,3	50,3	60,3	63,3	70,3	80,3	100,3
WIDTH	Available dimensions [mm]																		
10,3					■														
12,3						■													
15,3							■												
16,3								■											
20,3			■	■	■	■	■		■										
25,3	■	■	■	■	■	■	■	■	■	■									
30,3	■	■	■	■	■	■	■		■	■	■								
32,3	■	■	■	■	■	■		■	■	■		■							
40,3	■	■	■	■	■	■	■	■	■	■	■	■	■						
50,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■					
60,3	■	■	■	■	■	■	■	■	■	■	■	■	■		■				
63,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
70,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		■		
80,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
100,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
120,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
125,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
140,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
150,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
160,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
175,3			■	■	■	■		■	■	■		■	■	■		■		■	■
180,3			■	■	■	■	■	■	■	■	■	■	■	■			■	■	■
200,3			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
250,3			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
300,3			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
315,3			■	■	■	■		■	■	■	■	■	■	■		■		■	■
350,3			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
400,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
450,3									■	■		■	■	■		■		■	■
500 *				■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

* Width and length sawn/raw with +tol./-0 mm



Technical properties

Unalloyed structural steel with good machinability and dimensional stability, high toughness and good weldability because of its low carbon content ($C \leq 0,22\%$). This grade is only used for unhardened components. Working hardness: approx. 180 HB (annealed).




Applications

Mechanical engineering, base plates, moulding frames, construction materials, steel frames, hand tools, knives, sledge hammers, spanners.



Tolerances



Standard values

Delivery condition: maximum 180 HB
Chemical composition:

C	Si	Mn	P	S
0 - 0,22	0 - 0,55	0 - 1,6	0 - 0,035	0 - 0,035



If you need customised dimensions -

Any dimension available in different heights, widths and lengths.
On request - according to your needs!



Contact us

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu



Direct access to our online shop

www.premium-steel.eu/0570-4



AISI / SAE 1.0570 – all at a glance!

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.0570

via smartphone/tablet:



NAVIGATION/ STEEL GRADES

1.2343
H11

1.2343 ESU
H11 ESR

1.2316
1.2316

1.2312
P20+S

1.2311
P20

1.2294
1.2294

1.2210
L2

1.2162
1.2162

1.2099
1.2099

1.2085
420FM

1.2083
420

1.2083 ESU
420 ESR

1.2080 mod.
D3 mod.

1.2067
L3 / L1

1.1730
1045

1.0570
1.0570

Toolox 33
Toolox 33

Toolox 44
Toolox 44



PIONEERING !

PREMIUM 1.0570 – AISI / SAE 1.0570 (St 52-3/-S355J2+N)


Precision round steel without machining allowance [PRS]
Specification: bright drawn/ground, ISO h9

	LENGTH [mm]
	1.000
Ø [mm]	Available dimensions [•]
6,0	•
8,0	•
10,0	•
12,0	•
14,0	•
15,0	•
16,0	•
18,0	•
20,0	•
22,0	•
24,0	•
25,0	•
26,0	•
28,0	•
30,0	•
35,0	•
40,0	•
45,0	•
50,0	•
55,0	•
60,0	•

Round steel [RS]
Specification: black

	LENGTH [mm]	
	500	1.000
Ø [mm]	Available dimensions [•]	
20	•	•
25	•	•
30	•	•
35	•	•
40	•	•
45	•	•
50	•	•
55	•	•
60	•	•
65		•
70		•
75		•
80		•
85		•
90		•
95		•
100		•

Larger diameters, up to 750 mm and different lengths (partly peeled/rough-turned) on request!

**Tolerances****Standard values**

Delivery condition: maximum 180 HB
Chemical composition:

C	Si	Mn	P	S
0 - 0,22	0 - 0,55	0 - 1,6	0 - 0,035	0 - 0,035

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop [PRS]**

www.premium-steel.eu/0570-6

[RS]

www.premium-steel.eu/0570-8

**Technical properties**

Unalloyed structural steel with good machinability and dimensional stability, high toughness and good weldability because of its low carbon content (C ≤ 0,22%).
This grade is only used for unhardened components.
Working hardness: approx. 180 HB (annealed).

**Applications**

Mechanical engineering, base plates, moulding frames, construction materials, steel frames, hand tools, knives, sledge hammers, spanners.

**AISI / SAE 1.0570 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.0570

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.2343
H11

1.2343 ESU
H11 ESR

1.2316
1.2316

1.2312
P20+S

1.2311
P20

1.2294
1.2294

1.2210
L2

1.2162
1.2162

1.2099
1.2099

1.2085
420FM

1.2083
420

1.2083 ESU
420 ESR

1.2080 mod.
D3 mod.

1.2067
L3 / L1

1.1730
1045

1.0570
1.0570

Toolox 33
Toolox 33

Toolox 44
Toolox 44

ABRAMS®

TOOL STEEL I



TOOL STEEL II

HIGH SPEED STEEL

STAINLESS STEEL
corrosion resistant / acid resistant

HEAT-TREATABLE STEEL,
CASE HARDENING- &
NITRIDING STEEL

INFORMATION



MAXIMUM FLEXIBILITY – THAT IS OUR **€co-Präz®**

ABRAMS![®]
PREMIUM STEEL

PREMIUM Toolox 33 – AISI / SAE Toolox 33 (Toolox 33)

€co-Präz® 500 [€co]

Length: 500 mm

	THICKNESS [mm]											
	4,3	5,3	6,3	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3
WIDTH	Available dimensions [mm]											
33	■	■	■	■	■	■	■	■	■	■		
43	■	■	■	■	■	■	■	■	■	■		
53	■	■	■	■	■	■	■	■	■	■		
63	■	■	■	■	■	■	■	■	■	■		
73	■	■	■	■	■	■	■	■	■	■		
83	■	■	■	■	■	■	■	■	■	■		
93	■	■	■	■	■	■	■	■	■	■		
103	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■		
143	■	■	■	■	■	■	■	■	■	■		
153	■	■	■	■	■	■	■	■	■	■		
163	■	■	■	■	■	■	■	■	■	■		
183	■	■	■	■	■	■	■	■	■	■		
203	■	■	■	■	■	■	■	■	■	■		
223	■	■	■	■	■	■	■	■	■	■		
243	■	■	■	■	■	■	■	■	■	■		
253	■	■	■	■	■	■	■	■	■	■		
263	■	■	■	■	■	■	■	■	■	■		
283	■	■	■	■	■	■	■	■	■	■		
303	■	■	■	■	■	■	■	■	■	■		
323	■	■	■	■	■	■	■	■	■	■		
343	■	■	■	■	■	■	■	■	■	■		
353	■	■	■	■	■	■	■	■	■	■		
363	■	■	■	■	■	■	■	■	■	■		
383	■	■	■	■	■	■	■	■	■	■		
403	■	■	■	■	■	■	■	■	■	■		
423	■	■	■	■	■	■	■	■	■	■		
443	■	■	■	■	■	■	■	■	■	■		
453	■	■	■	■	■	■	■	■	■	■		
463	■	■	■	■	■	■	■	■	■	■		
483	■	■	■	■	■	■	■	■	■	■		
503	■	■	■	■	■	■	■	■	■	■		



Technical properties

Quenched and tempered low alloy toolsteel with good machinability, high toughness and low residual stresses. Can easily be polished, grained, eroded, etched, sliced, welded, nitrided, and coated with PVD (Physical Vapour Deposition). Further heat treatment is not intended. Working hardness without nitriding: approx. 30-36 HRC (delivery condition).




Applications

Mechanical engineering, machine parts, guide rails, base plates, assembling parts, press brake tools, plate forming tools, wear parts, plastic moulds, moulding frames, forming tools, rubber moulds, die casting moulds.



Tolerances



Standard values

Delivery condition: maximum 330 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni	V
0,22	0,6	0,8	0	0	1,0	0,3	0	0,1
0,24	1,1	0,8	0,01	0,003	1,2	0,3	1,0	0,11



If you need customised dimensions -

Any dimension available in different heights, widths and lengths.
On request - according to your needs!



Contact us

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu



Direct access to our online shop

www.premium-steel.eu/T33-5



AISI / SAE Toolox 33 – all at a glance!

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/T33

via smartphone/tablet:



NAVIGATION/ STEEL GRADES

1.2343
H11

1.2343 ESU
H11 ESR

1.2316
1.2316

1.2312
P20+S

1.2311
P20

1.2294
1.2294

1.2210
L2

1.2162
1.2162

1.2099
1.2099

1.2085
420FM

1.2083
420

1.2083 ESU
420 ESR

1.2080 mod.
D3 mod.

1.2067
L3 / L1

1.1730
1045

1.0570
1.0570

Toolox 33
Toolox 33

Toolox 44
Toolox 44

PREMIUM Toolox 44 – AISI / SAE Toolox 44 (Toolox 44)

€co-Präz® 500 [€co]

Length: 500 mm


		THICKNESS [mm]											
		4,3	5,3	6,3	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3
WIDTH		Available dimensions [mm]											
		33	43	53	63	73	83	93	103	123	143	153	163
1.2343 H11	1.2343 ESU H11 ESR	■	■	■	■	■	■	■	■	■	■	■	■
1.2316	1.2316	■	■	■	■	■	■	■	■	■	■	■	■
1.2312 P20+S	1.2311 P20	■	■	■	■	■	■	■	■	■	■	■	■
1.2294	1.2294	■	■	■	■	■	■	■	■	■	■	■	■
1.2210 L2	1.2162	■	■	■	■	■	■	■	■	■	■	■	■
1.2099	1.2099	■	■	■	■	■	■	■	■	■	■	■	■
1.2085 420FM	1.2083 420	■	■	■	■	■	■	■	■	■	■	■	■
1.2083 ESU 420 ESR	1.2083 ESU 420 ESR	■	■	■	■	■	■	■	■	■	■	■	■
1.2080 mod. D3 mod.	1.2067 L3/L1	■	■	■	■	■	■	■	■	■	■	■	■
1.1730 1045	1.0570 1.0570	■	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Low-alloyed tool steel with high-impact toughness, quenched and tempered up to approx. 45 HRC. Machinable with suitable tools because of its low carbide content. Good dimensional and shape stability. Can easily be polished, grained, eroded, etched, sliced, welded, nitrided, and coated with PVD (Physical Vapour Deposition). Working hardness: approx. 45 HRC (delivery condition).

**Applications**

Mechanical engineering, machine parts, guide rails, base plates, assembling parts, press brake tools, plate forming tools, wear parts, plastic moulds, moulding frames, forming tools, rubber moulds, die casting moulds.

**Tolerances****Standard values**

Delivery condition: maximum 418 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni	V
0,32	0,6	0,8	0	0	1,35	0,8	0	0,14
0,32	1,1	0,8	0,01	0,003	1,35	0,8	1,0	0,14

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/T44-5

**AISI / SAE Toolox 44 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/T44

via smartphone/tablet:



PREMIUM Toolox 44 – AISI / SAE Toolox 44 (Toolox 44)

Precision round steel with machining allowance [PRS/BA]

Specification: peeled / rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
Available dimensions [•]		
20,5	•	•
30,5	•	•
40,5	•	•
50,5	•	•
60,5	•	•
70,5		•
80,5		•
90,5		•
100,5		•


Larger diameters, up to 300,5 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Low-alloyed tool steel with high-impact toughness, quenched and tempered up to approx. 45 HRC. Machinable with suitable tools because of its low carbide content. Good dimensional and shape stability. Can easily be polished, grained, eroded, etched, sliced, welded, nitrided, and coated with PVD (Physical Vapour Deposition). Working hardness: approx. 45 HRC (delivery condition).

**Applications**

Mechanical engineering, machine parts, guide rails, base plates, assembling parts, press brake tools, plate forming tools, wear parts, plastic moulds, moulding frames, forming tools, rubber moulds, die casting moulds.

**Tolerances****Standard values**

Delivery condition: maximum 418 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni	V
0,32	0,6	0,8	0	0	1,35	0,8	0	0,14
0,32	1,1	0,8	0,01	0,003	1,35	0,8	1,0	0,14

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/T44-7

**AISI / SAE Toolox 44 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/T44

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.2343
H111.2343 ESU
H11 ESR1.2316
1.23161.2312
P20+S1.2311
P201.2294
1.22941.2210
L21.2162
1.21621.2099
1.20991.2085
420FM1.2083
4201.2083 ESU
420 ESR1.2080 mod.
D3 mod.1.2067
L3 / L11.1730
10451.0570
1.0570Toolox 33
Toolox 33Toolox 44
Toolox 44

SPECIFICATIONS !

Our delivery program contains 32.629 different specification / standard dimensions.

Any dimension is available in different **heights**, **widths** and **lengths**. On request – according to your needs!



Precision flat steel without machining allowance [PFS] acc. to DIN 59350

For example: 100,0 x 20,0 x 1.000 mm

- **W** ground/milled, tol. +0,2 /-0 mm
- **T** coplanar ground, tol. +0,05 /-0 mm
- **L** milled/sawn, tol. +35 /-0 mm
- **Exception: PREMIUM 1.1730 – AISI / SAE 1045: W** +0,4 /-0 mm, **T** +0,25 /-0 mm



Precision round steel without machining allowance [PRS]

- bright ground, tol.: Ø ISO h8, **L** +10 /-10 mm
- bright drawn/finely peeled /ground, tol.: Ø ISO h9, **L** +10 /-10 mm
- bright finely peeled, tol.: Ø ISO h11, **L** +10 /-10 mm



Precision flat steel with machining allowance [PRS/BA]

For example: 100,3 x 20,3 x 1.000 mm

- **W** ground/milled, tol. +0,4 /-0 mm
- **T** coplanar ground/finely milled, tol. +0, /-0 mm
- **L** milled/sawn, tol. +35 /-0 mm



Precision round steel with machining allowance [PRS/BA]

- peeled / rough-turned, tol.: Ø +tol./-0 mm, **L** +tol./-0 mm
- **Exception PREMIUM 1.3343 – AISI / SAE M2:**
L 1.000 mm, tol. **L** +10 /-10 mm
- **Particularity: PREMIUM 1.2826 – AISI / SAE 1.2826, PREMIUM 1.2360 – AISI / SAE –Chipper, PREMIUM 1.2067 – AISI / SAE L3:**
Ø are metric full values (for example 30,0 mm), therefore there is no basic machining allowance (for example 30,5 mm)



Eco-Präz® [Eco]

For example: 103 x 20,3 x 500 mm

- **W** sawn/black, tol. +3 /-0 mm
- **T** finely milled, tol. +0, /-0 mm
- **L** sawn/black, tol. +15 /-0 mm



Round steel [RS]

- black, tol.: Ø +1 /-1 mm (aspired), **L** +tol./-0 mm



Hart-Präz® [Hart]

For example: 250 x 10,2 x 500 mm

- **W** sawn/black, Tol. +10/-0 mm
- **T** coplanar ground, Tol. +0,2/-0 mm
- **L** sawn/black, Tol. +10/-0 mm

Planeness: +0,2/-0 mm of the entire surface (aspired)



Erosion block/EDM block – annealed or hardened [EB]

For example: 200,3 x 200,3 x 40,0 mm

- **Square dimension** milled/ground, tol. +2 /-0 mm
- **T** finely milled /ground, tol. +0,25/-0 mm
- Grain structure is vertically directed in relation to base surface

STEEL CLASSIFICATIONS !

Steel grades are classified by their technical **properties** and/or by their intended use.

For example:

Cold work steel, hot work steel, plastic mould steel, high speed steel, corrosion resistant steel or case hardening steel.

Steel grades are often assigned to several classification groups.

For more details on classification see www.steel-guide.eu/glossary



INNOVATIONS !



PREMIUM HSS 1.3343 – AISI / SAE M2 (HS6-5-2C)

Eco-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]																
	2,3	3,3	4,3	5,3	6,3	8,3	10,3	12,3	15,3	16,3	20,3	25,3	30,3	35,3	40,3	45,3	50,3
WIDTH	Available dimensions 																
33	■	■	■	■	■	■	■	■	■	■	■	■	■				
43	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
53	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
63	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
73	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
83	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
93	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
323	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
343	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
353	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
363	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
383	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
403	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
423	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
443	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
453	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
463	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
483	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
503	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

This high speed steel is the most frequently used among the high speed steels. Its composition allows it to be used for a wide range of applications. High impact toughness, good compression strength, excellent wear resistance. Working hardness: 62-65 HRC.

**Applications**

Machining tools, milling cutters, twist drills, screw taps, reamers, broaching tools, rotary knives, planer knives, gear shaper cutters, circular saw segments, metal saws, woodworking tools, screw dies, countersinks, chasers, cold extrusion punches, precision cutting tools, dies, punches, plastic moulds with high wear resistance.

**Tolerances****Standard values**

Delivery condition: maximum 270 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V	W
0,86	0	0	0	0	3,8	4,7	1,7	5,9
0,94	0,45	0,4	0,03	0,03	4,5	5,2	2,1	6,7

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/M2-5

**AISI / SAE M2 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/M2

via smartphone/tablet:



ABRAMS®

TOOL STEEL I

TOOL STEEL II

HIGH SPEED STEEL

STAINLESS STEEL
corrosion resistant / acid resistant

HEAT-TREATABLE STEEL,
CASE HARDENING- &
NITRIDING STEEL

INFORMATION



ABRAMS PREMIUM STEEL® – QUALITY THAT WILL IMPRESS YOU!

ABRAMS!
PREMIUM STEEL

PREMIUM HSS 1.3343 – AISI / SAE M2 (HS6-5-2C)**Precision round steel [PRS]**

Specification: bright drawn/ground, ISO h9

Ø [mm]	LENGTH [mm]
	1.000
Available dimensions [•]	
1,2	•
1,7	•
2,2	•
2,7	•
3,2	•
3,7	•
4,2	•
4,7	•
5,2	•
5,7	•
6,2	•
6,7	•
7,2	•
7,7	•
8,2	•
8,7	•
9,2	•
9,7	•
10,2	•
10,7	•
11,2	•
11,7	•
12,2	•
12,7	•
13,2	•

Precision round steel with machining allowance [PRS/BA]

Specification: peeled /rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
Available dimensions [•]		
14,2	•	•
14,7	•	•
15,2	•	•
15,7	•	•
16,2	•	•
16,7	•	•
17,2	•	•
17,7	•	•
18,2	•	•
18,7	•	•
19,2	•	•
19,7	•	•
20,2	•	•
22,2	•	•
24,2	•	•
25,2	•	•
26,2	•	•
28,2	•	•
30,2	•	•
35,2	•	•
40,2	•	•
45,2	•	•
50,2	•	•
60,5		•
70,5		•
80,5		•
90,5		•
100,5		•


Larger diameters, up to 300,5 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

This high speed steel is the most frequently used among the high speed steels. Its composition allows it to be used for a wide range of applications. High impact toughness, good compression strength, excellent wear resistance. Working hardness: 62-65 HRC.

**Applications**

Machining tools, milling cutters, twist drills, screw taps, reamers, broaching tools, rotary knives, planer knives, gear shaper cutters, circular saw segments, metal saws, woodworking tools, screw dies, countersinks, chasers, cold extrusion punches, precision cutting tools, dies, punches, plastic moulds with high wear resistance.

**Tolerances****Standard values**

Delivery condition: maximum 270 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V	W
0,86	0	0	0	0	3,8	4,7	1,7	5,9
0,94	0,45	0,4	0,03	0,03	4,5	5,2	2,1	6,7

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

[PRS]
www.premium-steel.eu/M2-6
[PRS/BA]
www.premium-steel.eu/M2-7

**AISI / SAE M2 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/M2

via smartphone/tablet:





USE UP TO 40% LESS MATERIAL = LESS WASTE – THAT IS OUR **€co-Präz®!**


ABRAMS!
PREMIUM STEEL

PREMIUM HSS PM 30 – AISI / SAE PM30 (PMHS6-5-3-8)

Eco-Präz® 300 [Eco]

Length: 300 mm

	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values**

Delivery condition: maximum 300 HB
Chemical composition:

C	Cr	Mo	V	W	Co
1,3	4,2	5,0	3,1	6,4	8,5
1,3	4,2	5,0	3,1	6,4	8,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/PM30-5

**Technical properties**

Powder metallurgical manufactured high performance high-speed steel for cold work tools and cutting tools. It convinces with its high wear resistance, good toughness and best cutting edge retention. The addition of cobalt with approx. 8,5% has a positive effect on the high temperature strength or rather the red hardness, tempering resistance and modulus of elasticity. Working hardness: 60-66 HRC.

**Applications**

Machining tools, milling cutters, thread cutting tools for materials that are difficult to machine, fine-blanking tools, drills, broaches, cold forming tools, blanking tools, deep drawing tools, die set.

**AISI / SAE PM30 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/PM30

via smartphone/tablet:




PREMIUM HSS PM 23 – AISI / SAE M3 (PMHS6-5-3)

€co-Präz® 300 [€co]

Length: 300 mm

	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values**

Delivery condition: maximum 270 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V	W
1,15	0	0	0	0	3,8	4,7	2,7	5,9
1,25	0,45	0,4	0,03	0,03	4,5	5,2	3,2	6,7

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/M3-5

**Technical properties**

High speed steel based on powder metallurgy. Similar to AISI / SAE M2, due to a very clean and homogeneous microstructure with evenly spread carbides optimising wear resistance. Working hardness: 62-65 HRC.

**Applications**

Stamping tools, precision cutting tools, machining tools, broaching tools, rotary knives, woodworking tools, gear shaper cutters, circular saw segments, metal saws, screw dies, countersinks, chasers, cold extrusion punches, deep drawing dies, plastic moulds with high wear resistance.

**AISI / SAE M3 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/M3

via smartphone/tablet:




PREMIUM HSS PM 4 – AISI / SAE M4 (PMHS6-5-4)

Eco-Präz® 300 [€co]

Length: 300 mm

	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values**

Delivery condition: maximum 270 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V	W
1,25	0	0	0	0	3,8	4,2	3,7	5,2
1,4	0,45	0,4	0,03	0,03	4,5	5,0	4,2	6,0

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/M4-5

**Technical properties**

High speed steel based on powder metallurgy with better wear and pressure resistance than AISI / SAE M3 and AISI / SAE M2, due to a very clean and homogeneous microstructure with evenly spread carbides optimising wear resistance. Working hardness: 62-65 HRC.

**Applications**

Stamping tools, precision cutting tools, machining tools, broaching tools, rotary knives, woodworking tools, gear shaper cutters, circular saw segments, metal saws, screw dies, countersinks, chasers, cold extrusion punches, deep drawing dies, plastic moulds with high wear resistance.

**AISI / SAE M4 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/M4

via smartphone/tablet:



SPECIFICATIONS !

Our delivery program contains 32.629 different specification / standard dimensions.

Any dimension is available in different **heights**, **widths** and **lengths**. On request – according to your needs!



Precision flat steel without machining allowance [PFS]
acc. to DIN 59350

For example: 100,0 x 20,0 x 1.000 mm

- **W** ground/milled, tol. +0,2 /-0 mm
- **T** coplanar ground, tol. +0,05 /-0 mm
- **L** milled/sawn, tol. +35 /-0 mm
- **Exception: PREMIUM 1.1730 – AISI / SAE 1045: W** +0,4 /-0 mm, **T** +0,25 /-0 mm



Precision round steel without machining allowance [PRS]

- bright ground, tol.: Ø ISO h8, **L** +10 /-10 mm
- bright drawn/finely peeled /ground, tol.: Ø ISO h9, **L** +10 /-10 mm
- bright finely peeled, tol.: Ø ISO h11, **L** +10 /-10 mm



Precision flat steel with machining allowance [PRS/BA]

For example: 100,3 x 20,3 x 1.000 mm

- **W** ground/milled, tol. +0,4 /-0 mm
- **T** coplanar ground/finely milled, tol. +0, /-0 mm
- **L** milled/sawn, tol. +35 /-0 mm



Precision round steel with machining allowance [PRS/BA]

- peeled / rough-turned, tol.: Ø +tol./-0 mm, **L** +tol./-0 mm
- **Exception PREMIUM 1.3343 – AISI / SAE M2:**
L 1.000 mm, tol. **L** +10 /-10 mm
- **Particularity: PREMIUM 1.2826 – AISI / SAE 1.2826, PREMIUM 1.2360 – AISI / SAE –Chipper, PREMIUM 1.2067 – AISI / SAE L3:**
Ø are metric full values (for example 30,0 mm), therefore there is no basic machining allowance (for example 30,5 mm)



Eco-Präz® [Eco]

For example: 103 x 20,3 x 500 mm

- **W** sawn/black, tol. +3 /-0 mm
- **T** finely milled, tol. +0, /-0 mm
- **L** sawn/black, tol. +15 /-0 mm



Round steel [RS]

- black, tol.: Ø +1 /-1 mm (aspired), **L** +tol./-0 mm



Hart-Präz® [Hart]

For example: 250 x 10,2 x 500 mm

- **W** sawn/black, Tol. +10/-0 mm
- **T** coplanar ground, Tol. +0,2/-0 mm
- **L** sawn/black, Tol. +10/-0 mm

Planeness: +0,2/-0 mm of the entire surface (aspired)



Erosion block/EDM block – annealed or hardened [EB]

For example: 200,3 x 200,3 x 40,0 mm

- **Square dimension** milled/ground, tol. +2 /-0 mm
- **T** finely milled /ground, tol. +0,25/-0 mm
- Grain structure is vertically directed in relation to base surface

STEEL CLASSIFICATIONS !

Steel grades are classified by their technical **properties** and/or by their intended use.

For example:

Cold work steel, hot work steel, plastic mould steel, high speed steel, corrosion resistant steel or case hardening steel.

Steel grades are often assigned to several classification groups.

For more details on classification see www.steel-guide.eu/glossary





EXCELLENT CHEMICAL RESISTANCE EVEN AT HIGH TEMPERATURES OF UP TO 1100°C – AISI/SAE 314!

ABRAMS!
PREMIUM STEEL

PREMIUM 1.4841 – AISI / SAE 314 (X15CrNiSi25-21)

Eco-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Heat-resistant, austenitic chromium-nickel steel, that provides good resistance to oxidation at high temperatures. Good resistance properties as well as excellent chemical resistance at high temperatures up to 1100°C. Very good corrosion resistance. Working hardness: approx. 223 HB (delivery condition).

**Applications**

Apparatus engineering for high temperature application, automotive industry, chemical industry, oil industry, chains for the cement and concrete industry, mechanical engineering, furnace construction, annealing muffles, enamel grates, fire baskets, heat conductors.

**Tolerances****Standard values**

Delivery condition: maximum 223 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Ni	N
0	1,5	0	0	0	24,0	19,0	0
0,2	2,5	2,0	0,045	0,015	26,0	22,0	0,11

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/314-5

**AISI / SAE 314, all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/314

via smartphone/tablet:


NAVIGATION/
STEEL GRADES**1.4841
314**1.4571
316Ti1.4418
S 165 M1.4404/1.4401
316L/3161.4305
3031.4301
3041.4125
440C1.4122
1.41221.4112
440B1.4104
430F1.4057
4311.4034
1.40341.4031
4201.4021
4201.4006
410

PREMIUM 1.4571 – AISI / SAE 316Ti (X6CrNiMoTi17-12-2)

€co-Präz® 500 [€co]

Length: 500 mm

	THICKNESS [mm]																
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3	
WIDTH	Available dimensions [mm]																
33	■	■	■	■	■	■	■										
43	■	■	■	■	■	■	■	■									
53	■	■	■	■	■	■	■	■	■								
63	■	■	■	■	■	■	■	■	■	■							
73	■	■	■	■	■	■	■	■	■	■	■						
83	■	■	■	■	■	■	■	■	■	■	■	■					
93	■	■	■	■	■	■	■	■	■	■	■	■	■				
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	

**Tolerances****Standard values**

Delivery condition: maximum 215 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni	Ti
0	0	0	0	0	16,5	2,0	10,5	0
0,08	1,0	2,0	0,045	0,015	18,5	2,5	13,5	0,7

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/316Ti-5

**Technical properties**

Stainless steel, austenitic chromium-nickel-molybdenum steel, stabilized with titanium. Resistant to seawater, diluted sulphuric and hydrochloric acids, and to intergranular corrosion following welding processes. Has excellent cold working properties, very good weldability and temperature resistance up to 600 degrees Celsius, non-magnetisable.

Working hardness: approx. 215 HB (delivery condition).

**Applications**

Chemical industry, textile industry, oil industry, building industry, food industry, soap industry, paper industry, photographic industry, paint industry, rubber industry, mechanical engineering, apparatus engineering, pump construction, compressor construction, pipeline construction, shipbuilding, medical technology, pharmaceutical industry, nuclear engineering.

**AISI / SAE 316Ti – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/316Ti

via smartphone/tablet:



PREMIUM 1.4571 – AISI / SAE 316Ti (X6CrNiMoTi17-12-2)

Precision round steel without machining allowance [PRS]

Specification: bright drawn/ground, ISO h9

	LENGTH [mm]
	1.000
Ø [mm]	Price per piece [in Euro]
5,0	•
6,0	•
8,0	•
10,0	•
12,0	•
15,0	•
16,0	•
20,0	•
25,0	•
28,0	•
30,0	•
35,0	•
40,0	•
45,0	•
50,0	•
55,0	•
60,0	•
70,0	•
80,0	•
90,0	•
100,0	•

Further diameters on request.


**Technical properties**

Stainless steel, austenitic chromium-nickel-molybdenum steel, stabilized with titanium. Resistant to seawater, diluted sulphuric and hydrochloric acids, and to intergranular corrosion following welding processes. Has excellent cold working properties, very good weldability and temperature resistance up to 600 degrees Celsius, non-magnetisable.

Working hardness: approx. 215 HB (delivery condition).

**Applications**

Chemical industry, textile industry, oil industry, building industry, food industry, soap industry, paper industry, photographic industry, paint industry, rubber industry, mechanical engineering, apparatus engineering, pump construction, compressor construction, pipeline construction, shipbuilding, medical technology, pharmaceutical industry, nuclear engineering.

**Tolerances****Standard values**

Delivery condition: maximum 215 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni	Ti
0	0	0	0	0	16,5	2,0	10,5	0
0,08	1,0	2,0	0,045	0,015	18,5	2,5	13,5	0,7

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/316Ti-6

**AISI / SAE 316Ti – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/316Ti

via smartphone/tablet:

1.4841
314**1.4571
316Ti**1.4418
S 165 M1.4404/1.4401
316L/3161.4305
3031.4301
3041.4125
440C1.4122
1.41221.4112
440B1.4104
430F1.4057
4311.4034
1.40341.4031
4201.4021
4201.4006
410

ABRAMS®

TOOL STEEL I

TOOL STEEL II

HIGH SPEED STEEL

STAINLESS STEEL
corrosion resistant / acid resistant

**HEAT-TREATABLE STEEL,
CASE HARDENING- &
NITRIDING STEEL**

INFORMATION



365 DAYS A YEAR – WE ARE HERE FOR YOU – VISIT OUR ONLINE SHOP AT WWW.PREMIUM-STEEL.EU

ABRAMS!
PREMIUM STEEL

PREMIUM 1.4418 – AISI / SAE S 165 M (X4CrNiMo16-5-1)

Precision round steel [PRS]

Specification: bright drawn/ground

Ø [mm]	LENGTH [mm]	
	500	1.000
	Available dimensions [•]	
30,0	•	•
35,0	•	•
40,0	•	•
45,0	•	•
50,0	•	•
55,0	•	•
60,0	•	•
65,0		•
70,0		•
75,0		•
80,0		•
85,0		•
90,0		•
95,0		•
100,0		•


Larger diameters, up to 200 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Stainless, martensitic steel (tempered condition). Excellent combination of high strength, good toughness and a very good corrosion resistance in aggressive substances (acids). The material is polishable, has good weldability and is suitable to use at temperatures from -30 °C up to 300 °C. Working hardness: approx. 34 HRC (delivery condition) up to 39 HRC.

**Applications**

Automotive industry, chemical industry, aviation and aerospace industry, mechanical engineering, plant engineering, ship building industry, shafts, axes, environmental engineering, centrifuge and pump components, energy technique, onshore and offshore.

**Tolerances****Standard values**

Delivery condition: maximum 323 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni	N
0,06	0,7	1,5	0,04	0,03	17,0	1,5	6,0	0,02

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/S165M-7

**AISI / SAE S165M – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/S165M

via smartphone/tablet:


1.4841
3141.4571
316Ti**1.4418**
S 165 M1.4404/1.4401
316L/3161.4305
3031.4301
3041.4125
440C1.4122
1.41221.4112
440B1.4104
430F1.4057
4311.4034
1.40341.4031
4201.4021
4201.4006
410

PREMIUM 1.4404/1.4401 – AISI / SAE 316L/316 (X2CrNiMo17-12-2/X5CrNiMo17-12-2)

€co-Präz® 500 [€co]

Length: 500 mm

	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values (AISI / SAE 316L)**

Delivery condition: maximum 215 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni	N
0	0	0	0	0,015	16,5	2,0	10,0	0
0,03	1,0	2,0	0,04	0,03	18,5	2,50	13,0	0,10

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/316L-5

**Technical properties**

Stainless, austenitic chromium-nickel-molybdenum steel. polishable, suitable for low temperatures, high resistance with regards to non-oxidizing acids e.g. nitric acid, sulphuric acid and formic acid, easy to process and good weldability. Can also be used at high temperatures of up to 500°C, non-magnetisable. Working hardness: approx. 215 HB (delivery condition).

**Applications**

Chemical industry, pharmaceutical industry, food industry, valve and plant construction, building industry, automotive industry, aviation industry, mechanical engineering, offshore, petrochemical industry, electrical equipment, decorative uses and kitchen equipment.

**AISI / SAE 316L/316 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/316L

via smartphone/tablet:



PREMIUM 1.4404/1.4401 – AISI / SAE 316L/316 (X2CrNiMo17-12-2/X5CrNiMo17-12-2)

Precision round steel without machining allowance [PRS]

Specification: bright drawn / ground, ISO h9

	LENGTH [mm]		
	1.000		
Ø [mm]	Available dimensions [•]		
5,0	•	»	
6,0	•	30,0	•
7,0	•	32,0	•
8,0	•	35,0	•
9,0	•	36,0	•
10,0	•	38,0	•
11,0	•	40,0	•
12,0	•	45,0	•
14,0	•	50,0	•
15,0	•	55,0	•
16,0	•	60,0	•
18,0	•	65,0	•
20,0	•	70,0	•
22,0	•	80,0	•
24,0	•	90,0	•
25,0	•	100,0	•
28,0	•		
»			


Further diameters on request.

**Technical properties**

Stainless, austenitic chromium-nickel-molybdenum steel. polishable, suitable for low temperatures, high resistance with regards to non-oxidizing acids e.g. nitric acid, sulphuric acid and formic acid, easy to process and good weldability. Can also be used at high temperatures of up to 500°C, non-magnetisable. Working hardness: approx. 215 HB (delivery condition).

**Applications**

Chemical industry, pharmaceutical industry, food industry, valve and plant construction, building industry, automotive industry, aviation industry, mechanical engineering, offshore, petrochemical industry, electrical equipment, decorative uses and kitchen equipment.

**Tolerances****Standard values (AISI / SAE 316L)**

Delivery condition: maximum 215 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni	N
0	0	0	0	0,015	16,5	2,0	10,0	0
0,03	1,0	2,0	0,04	0,03	18,5	2,50	13,0	0,10

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/316L-6

**AISI / SAE 316L/316 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/316L

via smartphone/tablet:




PREMIUM 1.4305 – AISI / SAE 303 (X8CrNiS18-9)

€co-Präz® 500 [€co]

Length: 500 mm

	THICKNESS [mm]																
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3	
WIDTH	Available dimensions [mm]																
33	■	■	■	■	■	■	■										
43	■	■	■	■	■	■	■	■									
53	■	■	■	■	■	■	■	■	■								
63	■	■	■	■	■	■	■	■	■	■							
73	■	■	■	■	■	■	■	■	■	■	■						
83	■	■	■	■	■	■	■	■	■	■	■	■					
93	■	■	■	■	■	■	■	■	■	■	■	■	■				
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	

**Tolerances****Standard values**

Delivery condition: maximum 250 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Ni	Cu	N
0	0	0	0	0,15	17,0	8,0	0	0
0,1	1,0	2,0	0,045	0,35	19,0	10,0	1,0	0,11

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/303-5

**Technical properties**

Corrosion resistant austenitic stainless chrome-nickel-steel with additional sulphur content that allows excellent milling, however, not forgeable, non-weldable (cracking), limited polishing properties. Average mechanical properties, non-magnetisable and conditionally acid resistant.

Working hardness: 215-250 HB (delivery condition).

**Applications**

Food industry, photographic industry, paint industry, oil industry, soap industry, paper industry, textile industry, mechanical engineering, turned parts, fittings construction, kitchen equipment, decoration.

**AISI / SAE 303 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/303

via smartphone/tablet:



PREMIUM 1.4305 – AISI / SAE 303 (X8CrNiS18-9)

Precision round steel without machining allowance [PRS]

Specification: bright drawn/ground, ISO h9

Ø [mm]	LENGTH [mm]	
	1.000	
Ø [mm]	Available dimensions [•]	
2,0	•	»
3,0	•	25,0 •
4,0	•	26,0 •
5,0	•	28,0 •
6,0	•	30,0 •
7,0	•	32,0 •
8,0	•	34,0 •
9,0	•	35,0 •
10,0	•	36,0 •
11,0	•	38,0 •
12,0	•	40,0 •
13,0	•	45,0 •
14,0	•	50,0 •
15,0	•	55,0 •
16,0	•	60,0 •
17,0	•	65,0 •
18,0	•	70,0 •
19,0	•	80,0 •
20,0	•	90,0 •
22,0	•	100,0 •
24,0	•	
»		


Further diameters on request.

**Technical properties**

Corrosion resistant austenitic stainless chrome-nickel-steel with additional sulphur content that allows excellent milling, however, not forgeable, non-weldable (cracking), limited polishing properties. Average mechanical properties, non-magnetisable and conditionally acid resistant. Working hardness: 215-250 HB (delivery condition).

**Applications**

Food industry, photographic industry, paint industry, oil industry, soap industry, paper industry, textile industry, mechanical engineering, turned parts, fittings construction, kitchen equipment, decoration.

**Tolerances****Standard values**

Delivery condition: maximum 250 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Ni	Cu	N
0	0	0	0	0,15	17,0	8,0	0	0
0,1	1,0	2,0	0,045	0,35	19,0	10,0	1,0	0,11

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/303-6

**AISI / SAE 303 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/303

via smartphone/tablet:


NAVIGATION/
STEEL GRADES1.4841
3141.4571
316Ti1.4418
S 165 M1.4404/1.4401
316L/316**1.4305**
3031.4301
3041.4125
440C1.4122
1.41221.4112
440B1.4104
430F1.4057
4311.4034
1.40341.4031
4201.4021
4201.4006
410

PREMIUM 1.4301 – AISI /SAE 304 (X5CrNi18-10)

€co-Präz® 500 [€co]

Length: 500 mm

	THICKNESS [mm]																
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3	
WIDTH	Available dimensions [mm]																
33	■	■	■	■	■	■	■										
43	■	■	■	■	■	■	■	■									
53	■	■	■	■	■	■	■	■	■								
63	■	■	■	■	■	■	■	■	■	■							
73	■	■	■	■	■	■	■	■	■	■	■						
83	■	■	■	■	■	■	■	■	■	■	■	■					
93	■	■	■	■	■	■	■	■	■	■	■	■	■				
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	

**Tolerances****Standard values**

Delivery condition: maximum 215 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Ni	N
0	0	0	0	0	17,5	8,0	0
0,07	1,0	2,0	0,045	0,015	19,5	10,5	0,11

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/304-5

**Technical properties**

Corrosion resistant austenitic stainless chrome-nickel-steel with good processability and attractive appearance (ground-high-gloss polished). It has excellent deep drawing properties, is weldable and wear resistant but non-magnetisable and limited machining properties. Average mechanical properties, and conditionally acid resistant. Working hardness: 195-215 HB (delivery condition).

**Applications**

Food industry, photographic industry, paint industry, oil industry, soap industry, paper industry, textile industry, mechanical engineering, turned parts, fittings construction, kitchen equipment, decoration.

**AISI / SAE 304 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/304

via smartphone/tablet:



PREMIUM 1.4301 – AISI / SAE 304 (X5CrNi18-10)

Precision round steel without machining allowance [PRS]

Specification: bright drawn/ground, ISO h9

Ø [mm]	LENGTH [mm]	
	1.000	
Ø [mm]	Available dimensions [•]	
2,0	•	»
3,0	•	25,0
4,0	•	26,0
5,0	•	28,0
6,0	•	30,0
7,0	•	32,0
8,0	•	34,0
9,0	•	35,0
10,0	•	36,0
11,0	•	38,0
12,0	•	40,0
13,0	•	45,0
14,0	•	50,0
15,0	•	55,0
16,0	•	60,0
17,0	•	65,0
18,0	•	70,0
19,0	•	80,0
20,0	•	90,0
22,0	•	100,0
24,0	•	
»		


Further diameters on request.

**Technical properties**

Corrosion resistant austenitic stainless chrome-nickel-steel with good processability and attractive appearance (ground-high-gloss polished). It has excellent deep drawing properties, is weldable and wear resistant but non-magnetisable and limited machining properties. Average mechanical properties, and conditionally acid resistant. Working hardness: 195-215 HB (delivery condition).

**Applications**

Food industry, photographic industry, paint industry, oil industry, soap industry, paper industry, textile industry, mechanical engineering, turned parts, fittings construction, kitchen equipment, decoration.

**Tolerances****Standard values**

Delivery condition: maximum 215 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Ni	N
0	0	0	0	0	17,5	8,0	0
0,07	1,0	2,0	0,045	0,015	19,5	10,5	0,11

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/304-6

**AISI / SAE 304 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/304

via smartphone/tablet:

1.4841
3141.4571
316Ti1.4418
S 165 M1.4404/1.4401
316L/3161.4305
303**1.4301**
3041.4125
440C1.4122
1.41221.4112
440B1.4104
430F1.4057
4311.4034
1.40341.4031
4201.4021
4201.4006
410

ABRAMS®

TOOL STEEL I

TOOL STEEL II

HIGH SPEED STEEL

STAINLESS STEEL
corrosion resistant / acid resistant

HEAT-TREATABLE STEEL,
CASE HARDENING- &
NITRIDING STEEL

INFORMATION

HIGHEST PRECISION !

ABRAMS!
PREMIUM STEEL

PREMIUM 1.4125 – AISI / SAE 440C (X105CrMo17)

Eco-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Stainless, martensitic steel with high hardness and high wear resistance and good cutting power due to the higher carbon content. Compared to the AISI / SAE 440B this steel has a slightly higher hardenability at the expense of the corrosion resistance. The material is conditionally acid resistant. Working hardness: 57-60 HRC

**Applications**

Knives for the food industry, for example frozen food cutters, pork and beef cleaving knives and fish industry knives as well as accessories for meat grinders.

**Tolerances****Standard values**

Delivery condition: maximum 285 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo
0,95	0	0	0	0	16,0	0,4
1,20	1,0	1,0	0,04	0,015	18,0	0,8

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/440C-5

**AISI / SAE 440C – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/440C

via smartphone/tablet:


NAVIGATION/
STEEL GRADES1.4841
3141.4571
316Ti1.4418
S 165 M1.4404/1.4401
316L/3161.4305
3031.4301
3041.4125
440C1.4122
1.41221.4112
440B1.4104
430F1.4057
4311.4034
1.40341.4031
4201.4021
4201.4006
410

PREMIUM 1.4122 – AISI / SAE 1.4122 (X39CrMo17-1)

€co-Präz® 300 [€co]

Length: 300 mm

	THICKNESS [mm]																
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3	
WIDTH	Available dimensions [mm]																
33	■	■	■	■	■	■	■										
43	■	■	■	■	■	■	■	■									
53	■	■	■	■	■	■	■	■	■								
63	■	■	■	■	■	■	■	■	■	■							
73	■	■	■	■	■	■	■	■	■	■	■						
83	■	■	■	■	■	■	■	■	■	■	■	■					
93	■	■	■	■	■	■	■	■	■	■	■	■	■				
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	

**Tolerances****Standard values**

Delivery condition: maximum 325 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni
0,33	0	0	0	0	15,5	0,8	0
0,45	1,0	1,5	0,045	0,03	17,5	1,3	1,0

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/4122-3-5

**Technical properties**

Pre-hardened corrosion resistant chrome-steel with good polishing properties, heat resistance and wear resistance. Often used for processing chemically aggressive plastic materials (e.g. PVC). The material is conditionally acid resistant. Working hardness: approx. 30 HRC (delivery condition) up to 48 HRC.

**Applications**

Mechanical engineering, marine engineering, apparatus engineering, plastic processing, plastic moulds, extrusion tools, press moulds, fitting tools, shafts, spindles, bolts, pistons, valves, steam valves, water valves, beater bars, fittings parts, pump construction, pump rods, compressor construction, compressor parts, surgical Instruments.

**AISI / SAE 1.4122 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.4122

via smartphone/tablet:



PREMIUM 1.4122 – AISI / SAE 1.4122 (X39CrMo17-1)

Eco-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Pre-hardened corrosion resistant chrome-steel with good polishing properties, heat resistance and wear resistance. Often used for processing chemically aggressive plastic materials (e.g. PVC). The material is conditionally acid resistant. Working hardness: approx. 30 HRC (delivery condition) up to 48 HRC.

**Applications**

Mechanical engineering, marine engineering, apparatus engineering, plastic processing, plastic moulds, extrusion tools, press moulds, fitting tools, shafts, spindles, bolts, pistons, valves, steam valves, water valves, beater bars, fittings parts, pump construction, pump rods, compressor construction, compressor parts, surgical Instruments.

**Tolerances****Standard values**

Delivery condition: maximum 325 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni
0,33	0	0	0	0	15,5	0,8	0
0,45	1,0	1,5	0,045	0,03	17,5	1,3	1,0

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/4122-5-5


**AISI / SAE 1.4122 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.4122

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.4841
3141.4571
316Ti1.4418
S 165 M1.4404/1.4401
316L/3161.4305
3031.4301
3041.4125
440C**1.4122**
1.41221.4112
440B1.4104
430F1.4057
4311.4034
1.40341.4031
4201.4021
4201.4006
410

QUENCHED AND TEMPERED AND CORROSION RESISTANT ...



... AISI / SAE 1.4122 !

PREMIUM 1.4122 – AISI / SAE 1.4122 (X39CrMo17-1)


Precision round steel without machining allowance [PRS]
Specification: bright drawn/ground, ISO h9

Ø [mm]	LENGTH [mm]
	1.000
Available dimensions [•]	
16,0	•
18,0	•
20,0	•
22,0	•
25,0	•
28,0	•
30,0	•
35,0	•
40,0	•
45,0	•
50,0	•

Precision round steel with machining allowance [PRS/BA]
Specification: peeled /rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
Available dimensions [•]		
20,5	•	•
25,5	•	•
30,5	•	•
35,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
55,5	•	•
60,5	•	•
65,5		•
70,5		•
75,5		•
80,5		•
85,5		•
90,5		•
95,5		•
100,5		•

Larger diameters, up to 550,5 mm, and different lengths (e.g. round blanks) available on request!

**Tolerances****Standard values**

Delivery condition: maximum 325 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni
0,33	0	0	0	0	15,5	0,8	0
0,45	1,0	1,5	0,045	0,03	17,5	1,3	1,0

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop [PRS]**

www.premium-steel.eu/4122-6
[PRS/BA]
www.premium-steel.eu/4122-7

**Technical properties**

Pre-hardened corrosion resistant chrome-steel with good polishing properties, heat resistance and wear resistance. Often used for processing chemically aggressive plastic materials (e.g. PVC). The material is conditionally acid resistant. Working hardness: approx. 30 HRC (delivery condition) up to 48 HRC.

**Applications**

Mechanical engineering, marine engineering, apparatus engineering, plastic processing, plastic moulds, extrusion tools, press moulds, fitting tools, shafts, spindles, bolts, pistons, valves, steam valves, water valves, beater bars, fittings parts, pump construction, pump rods, compressor construction, compressor parts, surgical Instruments.

**AISI / SAE 1.4122 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.4122

via smartphone/tablet:



ABRAMS®

TOOL STEEL I

TOOL STEEL II

HIGH SPEED STEEL

STAINLESS STEEL
corrosion resistant / acid resistant

**HEAT-TREATABLE STEEL,
CASE HARDENING- &
NITRIDING STEEL**

INFORMATION

CORROSION RESISTANT AND HARDENABLE UP TO 58 HRC ...

... AISI / SAE 440B !

ABRAMS®
PREMIUM STEEL

PREMIUM 1.4112 – AISI / SAE 440B (X90CrMoV18)

Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm

	THICKNESS [mm]																	
	3,2	4,2	5,2	6,2	8,2	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3
WIDTH	Available dimensions [mm]																	
10,3						■												
12,3							■											
15,3								■										
20,3	■	■	■	■	■	■	■	■	■									
25,3	■	■	■	■	■	■	■	■	■	■								
30,3	■	■	■	■	■	■	■	■	■	■	■							
40,3	■	■	■	■	■	■	■	■	■	■	■	■						
50,3	■	■	■	■	■	■	■	■	■	■	■	■	■					
60,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
70,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
80,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
90,3					■	■	■	■	■	■	■	■	■	■	■	■	■	
100,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
120,3						■	■	■	■	■	■	■	■	■	■	■		■
150,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
200,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		■
250,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■		■		■
300,3	■	■	■	■	■	■	■	■	■	■	■	■	■	■		■		■
500*					■	■	■	■	■	■	■	■	■	■	■	■		■


* Width and length sawn/black with +tol./-0 mm

**Technical properties**

Corrosion resistant martensitic chrome-steel (approx. 18% Cr) for cold work. Reaches an unusually high hardness and high wear resistance after heat treatment. High gloss polishable and conditionally acid resistant.
Working hardness: 53-58 HRC.

**Applications**

Cutting tools, knives, knife blades, cutlery, guide rails, wear parts, perforated discs, screw elements, pump shafts, scale pans, horizontal cutting, surgical instruments, plastic moulds, injection nozzles, roller bearings, ball bearings, mechanical engineering, food industry, building industry.

**Tolerances****Standard values**

Delivery condition: maximum 265 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,85	0	0	0	0	17,0	0,9	0,07
0,95	1,0	1,0	0,04	0,015	19,0	1,3	0,12

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/440B-4

**AISI / SAE 440B – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/440B

via smartphone/tablet:


NAVIGATION/
STEEL GRADES1.4841
3141.4571
316Ti1.4418
S 165 M1.4404/1.4401
316L/3161.4305
3031.4301
3041.4125
440C1.4122
1.4122**1.4112**
440B1.4104
430F1.4057
4311.4034
1.40341.4031
4201.4021
4201.4006
410

PREMIUM 1.4112 – AISI / SAE 440B (X90CrMoV18)

€co-Präz® 300 [€co]

Length: 300 mm

	THICKNESS [mm]																		
	2,3	3,3	4,3	5,3	6,3	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3
WIDTH	Available dimensions [mm]																		
33	■	■	■	■	■	■	■	■	■	■	■	■							
43	■	■	■	■	■	■	■	■	■	■	■	■	■						
53	■	■	■	■	■	■	■	■	■	■	■	■	■	■					
63	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
73	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
83	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
93	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values**

Delivery condition: maximum 265 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,85	0	0	0	0	17,0	0,9	0,07
0,95	1,0	1,0	0,04	0,015	19,0	1,3	0,12

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/440B-3-5

**Technical properties**

Corrosion resistant martensitic chrome-steel (approx. 18% Cr) for cold work. Reaches an unusually high hardness and high wear resistance after heat treatment. High gloss polishable and conditionally acid resistant.
Working hardness: 53-58 HRC.

**Applications**

Cutting tools, knives, knife blades, cutlery, guide rails, wear parts, perforated discs, screw elements, pump shafts, scale pans, horizontal cutting, surgical instruments, plastic moulds, injection nozzles, roller bearings, ball bearings, mechanical engineering, food industry, building industry.

**AISI / SAE 440B – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/440B

via smartphone / tablet:



PREMIUM 1.4112 – AISI / SAE 440B (X90CrMoV18)

€co-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]																		
	2,3	3,3	4,3	5,3	6,3	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3
WIDTH	Available dimensions [mm]																		
33	■	■	■	■	■	■	■	■	■	■	■	■							
43	■	■	■	■	■	■	■	■	■	■	■	■	■						
53	■	■	■	■	■	■	■	■	■	■	■	■	■	■					
63	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
73	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
83	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
93	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
323	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
343	■	■	■	■	■	■	■	■	■	■	■	■							
353	■	■	■	■	■	■	■	■	■	■	■	■							
363	■	■	■	■	■	■	■	■	■	■	■	■							
383	■	■	■	■	■	■	■	■	■	■	■	■							
403	■	■	■	■	■	■	■	■	■	■	■	■							
423	■	■	■	■	■	■	■	■	■	■	■	■							
443	■	■	■	■	■	■	■	■	■	■	■	■							
453	■	■	■	■	■	■	■	■	■	■	■	■							
463	■	■	■	■	■	■	■	■	■	■	■	■							
483	■	■	■	■	■	■	■	■	■	■	■	■							
503	■	■	■	■	■	■	■	■	■	■	■	■							

**Technical properties**

Corrosion resistant martensitic chrome-steel (approx. 18% Cr) for cold work. Reaches an unusually high hardness and high wear resistance after heat treatment. High gloss polishable and conditionally acid resistant.
Working hardness: 53-58 HRC.

**Applications**

Cutting tools, knives, knife blades, cutlery, guide rails, wear parts, perforated discs, screw elements, pump shafts, scale pans, horizontal cutting, surgical instruments, plastic moulds, injection nozzles, roller bearings, ball bearings, mechanical engineering, food industry, building industry.

**Tolerances****Standard values**

Delivery condition: maximum 265 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,85	0	0	0	0	17,0	0,9	0,07
0,95	1,0	1,0	0,04	0,015	19,0	1,3	0,12

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/440B-5-5

**AISI / SAE 440B – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/440B

via smartphone/tablet:

1.4841
3141.4571
316Ti1.4418
S 165 M1.4404/1.4401
316L/3161.4305
3031.4301
3041.4125
440C1.4122
1.41221.4112
440B1.4104
430F1.4057
4311.4034
1.40341.4031
4201.4021
4201.4006
410

PREMIUM 1.4112 – AISI / SAE 440B (X90CrMoV18)**Hart-Präz® 250 [Hart]**

Length: 250 mm


	THICKNESS [mm]												
	2,2	2,7	3,2	3,7	4,2	4,7	5,2	6,2	7,2	8,2	9,2	10,2	12,2
WIDTH	Available dimensions [mm]												
250	■	■	■	■	■	■	■	■	■	■	■	■	■

Hart-Präz® 500 [Hart]

Length: 500 mm

	THICKNESS [mm]												
	2,2	2,7	3,2	3,7	4,2	4,7	5,2	6,2	7,2	8,2	9,2	10,2	12,2
WIDTH	Available dimensions [mm]												
250	■	■	■	■	■	■	■	■	■	■	■	■	■


Hardened dimensions are delivered with approx. 53 HRC, at least 2x tempered.

**Technical properties**

Corrosion resistant martensitic chrome-steel (approx. 18% Cr) for cold work. Reaches an unusually high hardness and high wear resistance after heat treatment. High gloss polishable and conditionally acid resistant.
Working hardness: 53-58 HRC.

**Applications**

Cutting tools, knives, knife blades, cutlery, guide rails, wear parts, perforated discs, screw elements, pump shafts, scale pans, horizontal cutting, surgical instruments, plastic moulds, injection nozzles, roller bearings, ball bearings, mechanical engineering, food industry, building industry.

**Tolerances****Standard values**

Delivery condition: approx. 53 HRC
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,85	0	0	0	0	17,0	0,9	0,07
0,95	1,0	1,0	0,04	0,015	19,0	1,3	0,12

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/440B-11-H

**AISI / SAE 440B – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/440B

via smartphone / tablet:



PREMIUM 1.4112 – AISI / SAE 440B (X90CrMoV18)

Precision round steel without machining allowance [PRS]
Specification: bright drawn/ground, ISO h9

Ø [mm]	LENGTH [mm]
	1.000
Available dimensions [•]	
10,0	•
12,0	•
14,0	•
15,0	•
16,0	•
18,0	•
20,0	•
25,0	•
30,0	•
35,0	•
40,0	•
45,0	•
50,0	•

Precision round steel with machining allowance [PRS/BA]
Specification: peeled /rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
Available dimensions [•]		
20,0	•	•
25,0	•	•
30,0	•	•
35,0	•	•
40,0	•	•
45,0	•	•
50,0	•	•
55,0	•	•
60,0	•	•
65,0		•
70,0		•
75,0		•
80,0		•
85,0		•
90,0		•
95,0		•
100,0		•


Larger diameters, up to 405,5 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Corrosion resistant martensitic chrome-steel (approx. 18% Cr) for cold work. Reaches an unusually high hardness and high wear resistance after heat treatment. High gloss polishable and conditionally acid resistant.
Working hardness: 53-58 HRC.

**Applications**

Cutting tools, knives, knife blades, cutlery, guide rails, wear parts, perforated discs, screw elements, pump shafts, scale pans, horizontal cutting, surgical instruments, plastic moulds, injection nozzles, roller bearings, ball bearings, mechanical engineering, food industry, building industry.

**Tolerances****Standard values**

Delivery condition: maximum 265 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,85	0	0	0	0	17,0	0,9	0,07
0,95	1,0	1,0	0,04	0,015	19,0	1,3	0,12

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

[PRS]
www.premium-steel.eu/440B-6
[PRS/BA]
www.premium-steel.eu/440B-7

**AISI / SAE 440B – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/440B

via smartphone / tablet:

NAVIGATION/
STEEL GRADES

1.4841
314

1.4571
316Ti

1.4418
S 165 M

1.4404/1.4401
316L/316

1.4305
303

1.4301
304

1.4125
440C

1.4122
1.4122

1.4112
440B

1.4104
430F

1.4057
431

1.4034
1.4034

1.4031
420

1.4021
420


1.4006
410

PREMIUM 1.4104 – AISI / SAE 430F (X14CrMoS17)

€co-Präz® 500 [€co]

Length: 500 mm

	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values**

Delivery condition: maximum 270 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo
0,10	0	0	0	0,15	15,5	0,20
0,17	1,0	1,5	0,04	0,35	17,5	0,60

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/430F-5

**Technical properties**

Martensitic chromium steel with good mechanical properties (tempered condition). The addition of sulphur makes it ideal for machining. It can also be polished very well and is conditionally acid resistant but difficult to weld.

Working hardness: approx. 26 HRC (approx. on delivery).

**Applications**

Automotive industry, electronic equipment, power engineering, mechanical engineering, connecting elements, architecture and decoration, construction parts for automatic machining in water and steam such as screws, spindles, axes, bushes, etc.

**AISI / SAE 430F – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/430F

via smartphone/tablet:



PREMIUM 1.4104 – AISI / SAE 430F (X14CrMoS17)

Precision round steel without machining allowance [PRS]

Specification: bright drawn/ground, ISO h9

Ø [mm]	LENGTH [mm]		
	1.000		
Ø [mm]	Available dimensions [•]		
10,0	•	»	
12,0	•	32,0	•
13,0	•	34,0	•
14,0	•	35,0	•
15,0	•	36,0	•
16,0	•	38,0	•
17,0	•	40,0	•
18,0	•	45,0	•
20,0	•	50,0	•
22,0	•	55,0	•
24,0	•	60,0	•
25,0	•	65,0	•
26,0	•	70,0	•
28,0	•	80,0	•
30,0	•		
»			

Further diameters on request.


**Technical properties**

Martensitic chromium steel with good mechanical properties (tempered condition). The addition of sulphur makes it ideal for machining. It can also be polished very well and is conditionally acid resistant but difficult to weld.

Working hardness: approx. 26 HRC (approx. on delivery).

**Applications**

Automotive industry, electronic equipment, power engineering, mechanical engineering, connecting elements, architecture and decoration, construction parts for automatic machining in water and steam such as screws, spindles, axes, bushes, etc.

**Tolerances****Standard values**

Delivery condition: maximum 270 HB

Chemical composition:

C	Si	Mn	P	S	Cr	Mo
0,10	0	0	0	0,15	15,5	0,20
0,17	1,0	1,5	0,04	0,35	17,5	0,60

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/430F-6

**AISI / SAE 430F – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/430F

via smartphone/tablet:


1.4841
3141.4571
316Ti1.4418
S 165 M1.4404/1.4401
316L/3161.4305
3031.4301
3041.4125
440C1.4122
1.41221.4112
440B**1.4104**
430F1.4057
4311.4034
1.40341.4031
4201.4021
4201.4006
410

PREMIUM 1.4057 – AISI / SAE 431 (X17CrNi16-2)

€co-Präz® 500 [€co]

Length: 500 mm

	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values**

Delivery condition: maximum 331 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Ni
0,12	0	0	0	0	15,0	1,5
0,22	1,0	1,5	0,04	0,03	17,0	2,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/431-5

**Technical properties**

Martensitic chromium steel with high strength (tempered condition) and good corrosion resistance (added nickel). It is easy to weld and is conditionally acid resistant. The material has poor forgeability. Working hardness: approx. 32 HRC (approx. on delivery) to 47 HRC.

**Applications**

Mechanical engineering, automotive industry, oil and petrochemical industry, aviation, food industry, soap industry, acetic acid industry, shafts, pump parts, perforated plates, spindles, piston rods, valve cones, turbine blades.

**AISI / SAE 431 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/431

via smartphone / tablet:



PREMIUM 1.4057 – AISI / SAE 431 (X17CrNi16-2)

Precision round steel without machining allowance [PRS]

Specification: bright drawn/ground, ISO h9

Ø [mm]	LENGTH [mm]		
	1.000		
Ø [mm]	Available dimensions [•]		
8,0	•	»	
10,0	•	30,0	•
12,0	•	32,0	•
14,0	•	35,0	•
15,0	•	40,0	•
16,0	•	45,0	•
18,0	•	50,0	•
20,0	•	55,0	•
22,0	•	60,0	•
24,0	•	70,0	•
25,0	•	80,0	•
28,0	•		
»			


Further diameters on request.

**Technical properties**

Martensitic chromium steel with high strength (tempered condition) and good corrosion resistance (added nickel). It is easy to weld and is conditionally acid resistant. The material has poor forgeability. Working hardness: approx. 32 HRC (approx. on delivery) to 47 HRC.

**Applications**

Mechanical engineering, automotive industry, oil and petrochemical industry, aviation, food industry, soap industry, acetic acid industry, shafts, pump parts, perforated plates, spindles, piston rods, valve cones, turbine blades.

**Tolerances****Standard values**

Delivery condition: maximum 331 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Ni
0,12	0	0	0	0	15,0	1,5
0,22	1,0	1,5	0,04	0,03	17,0	2,5

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/431-6

**AISI / SAE 431 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/431

via smartphone/tablet:

1.4841
3141.4571
316Ti1.4418
S 165 M1.4404/1.4401
316L/3161.4305
3031.4301
3041.4125
440C1.4122
1.41221.4112
440B1.4104
430F**1.4057**
4311.4034
1.40341.4031
4201.4021
4201.4006
410

PREMIUM 1.4034 – AISI / SAE 1.4034 (X46Cr13)

Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm

	THICKNESS [mm]															
		8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	40,3	50,3	60,3	70,3	80,3	100,3
WIDTH	Available dimensions [mm]															
1.4841 314																
1.4571 316Ti																
1.4418 S 165 M																
1.4404/1.4401 316L/316																
1.4305 303																
1.4301 304																
1.4125 440C																
1.4122 1.4122																
1.4112 440B																
1.4104 430F																
1.4057 431																
1.4034 1.4034																
1.4031 420																
1.4021 420																
1.4006 410																


*Width and length sawn/black with +tol./-0 mm

**Technical properties**

Corrosion resistant cold work and plastic mould steel with good machining properties, hardenable and polishable. Low distortion through-hardening steel with full hardenability and high wear resistance, conditionally acid resistant.
Working hardness: 50-55 HRC.

**Applications**

Mechanical engineering, medical technology, plastic moulds, synthetic resin mould tools, die casting tools, light metal die casting, cutting tools, machine knives, kitchen knives, razors, shears, scraper blades, surgical instruments, measuring tools, roller bearings, ball bearings, ice-skates, pump parts, valves.

**Tolerances****Standard values**

Delivery condition: maximum 241 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,43	0	0	0	0	12,5
0,5	1,0	1,0	0,04	0,015	14,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/4034-4

**AISI / SAE 1.4034 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.4034

via smartphone / tablet:



PREMIUM 1.4034 – AISI / SAE 1.4034 (X46Cr13)

Eco-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]													
	2,3	3,3	4,3	5,3	6,3	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3
WIDTH	Available dimensions [mm]													
33	■	■	■	■	■	■	■	■	■	■	■	■	■	■
43	■	■	■	■	■	■	■	■	■	■	■	■	■	■
53	■	■	■	■	■	■	■	■	■	■	■	■	■	■
63	■	■	■	■	■	■	■	■	■	■	■	■	■	■
73	■	■	■	■	■	■	■	■	■	■	■	■	■	■
83	■	■	■	■	■	■	■	■	■	■	■	■	■	■
93	■	■	■	■	■	■	■	■	■	■	■	■	■	■
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■
323	■	■	■	■	■	■	■	■	■	■	■	■	■	■
343	■	■	■	■	■	■	■	■	■	■	■	■	■	■
353	■	■	■	■	■	■	■	■	■	■	■	■	■	■
363	■	■	■	■	■	■	■	■	■	■	■	■	■	■
383	■	■	■	■	■	■	■	■	■	■	■	■	■	■
403	■	■	■	■	■	■	■	■	■	■	■	■	■	■
423	■	■	■	■	■	■	■	■	■	■	■	■	■	■
443	■	■	■	■	■	■	■	■	■	■	■	■	■	■
453	■	■	■	■	■	■	■	■	■	■	■	■	■	■
463	■	■	■	■	■	■	■	■	■	■	■	■	■	■
483	■	■	■	■	■	■	■	■	■	■	■	■	■	■
503	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Corrosion resistant cold work and plastic mould steel with good machining properties, hardenable and polishable. Low distortion through-hardening steel with full hardenability and high wear resistance, conditionally acid resistant.
Working hardness: 50-55 HRC.

**Applications**

Mechanical engineering, medical technology, plastic moulds, synthetic resin mould tools, die casting tools, light metal die casting, cutting tools, machine knives, kitchen knives, razors, shears, scraper blades, surgical instruments, measuring tools, roller bearings, ball bearings, ice-skates, pump parts, valves.

**Tolerances****Standard values**

Delivery condition: maximum 241 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,43	0	0	0	0	12,5
0,5	1,0	1,0	0,04	0,015	14,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/4034-5

**AISI / SAE 1.4034 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.4034

via smartphone/tablet:

1.4841
3141.4571
316Ti1.4418
S 165 M1.4404/1.4401
316L/3161.4305
3031.4301
3041.4125
440C1.4122
1.41221.4112
440B1.4104
430F1.4057
431**1.4034**
1.40341.4031
4201.4021
4201.4006
410

1.4841
3141.4571
316Ti1.4418
S 165 M1.4404/1.4401
316L/3161.4305
3031.4301
3041.4125
440C1.4122
1.41221.4112
440B1.4104
430F1.4057
4311.4034
1.40341.4031
4201.4021
4201.4006
410**PREMIUM 1.4034 – AISI / SAE 1.4034** (X46Cr13)**Hart-Präz® 250 [Hart]**

Length: 250 mm


	THICKNESS [mm]												
	2,2	2,7	3,2	3,7	4,2	4,7	5,2	6,2	7,2	8,2	9,2	10,2	12,2
WIDTH	Available dimensions [mm]												
250	■	■	■	■	■	■	■	■	■	■	■	■	■

Hart-Präz® 500 [Hart]

Length: 500 mm

	THICKNESS [mm]												
	2,2	2,7	3,2	3,7	4,2	4,7	5,2	6,2	7,2	8,2	9,2	10,2	12,2
WIDTH	Available dimensions [mm]												
250	■	■	■	■	■	■	■	■	■	■	■	■	■


Hardened dimensions are delivered with approx. 50 HRC, at least 2x tempered.

**Technical properties**

Corrosion resistant cold work and plastic mould steel with good machining properties, hardenable and polishable. Low distortion through-hardening steel with full hardenability and high wear resistance, conditionally acid resistant.
Working hardness: 50-55 HRC.

**Applications**

Mechanical engineering, medical technology, plastic moulds, synthetic resin mould tools, die casting tools, light metal die casting, cutting tools, machine knives, kitchen knives, razors, shears, scraper blades, surgical instruments, measuring tools, roller bearings, ball bearings, ice-skates, pump parts, valves.

**Tolerances****Standard values**

Delivery condition: approx. 50 HRC
Chemical composition:

C	Si	Mn	P	S	Cr
0,43	0	0	0	0	12,5
0,5	1,0	1,0	0,04	0,015	14,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/4034-11-H

**AISI / SAE 1.4034 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.4034

via smartphone/tablet:



PREMIUM 1.4034 – AISI / SAE 1.4034 (X46Cr13)


Precision round steel without machining allowance [PRS]
Specification: bright drawn/ground, ISO h9

Ø [mm]	LENGTH [mm]
	1.000
Available dimensions [•]	
15,0	•
16,0	•
18,0	•
20,0	•
25,0	•
30,0	•
35,0	•
40,0	•
45,0	•
50,0	•

Precision round steel with machining allowance [PRS/BA]
Specification: peeled /rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
Available dimensions [•]		
20,5	•	•
25,5	•	•
30,5	•	•
35,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
55,5	•	•
60,5	•	•
65,5		•
70,5		•
80,5		•
85,5		•
90,5		•
100,5		•

Larger diameters, up to 400,5 mm, and different lengths (e.g. round blanks) available on request!

**Tolerances****Standard values**

Delivery condition: maximum 241 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,43	0	0	0	0	12,5
0,5	1,0	1,0	0,04	0,015	14,5

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop [PRS]**

www.premium-steel.eu/4034-6

[PRS/BA]

www.premium-steel.eu/4034-7

**Technical properties**

Corrosion resistant cold work and plastic mould steel with good machining properties, hardenable and polishable. Low distortion through-hardening steel with full hardenability and high wear resistance, conditionally acid resistant.
Working hardness: 50-55 HRC.

**Applications**

Mechanical engineering, medical technology, plastic moulds, synthetic resin mould tools, die casting tools, light metal die casting, cutting tools, machine knives, kitchen knives, razors, shears, scraper blades, surgical instruments, measuring tools, roller bearings, ball bearings, ice-skates, pump parts, valves.

**AISI / SAE 1.4034 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.4034

via smartphone/tablet:



PREMIUM 1.4031 – AISI / SAE ~420 (X39Cr13)

Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm

WIDTH	THICKNESS [mm]														
	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	40,3	50,3	60,3	70,3	80,3	100,3
	Available dimensions [mm]														
1.4841 314															
1.4571 316Ti															
1.4418 S 165 M															
1.4404/1.4401 316L/316															
1.4305 303															
1.4301 304															
1.4125 440C															
1.4122 1.4122															
1.4112 440B															
1.4104 430F															
1.4057 431															
1.4034 1.4034															
1.4031 420															
1.4021 420															
1.4006 410															

*Width and length sawn/black with +tol./-0 mm


**Technical properties**

Martensitic chromium steel with good mechanical properties. Excellent polishing properties, good corrosion resistance, good chemical resistance and difficult to weld. Due to its high contents of carbon excellent to use for cutting tools. The material is conditionally acid resistant.

Working hardness: approx. 50-55 HRC.

**Applications**

Mechanical engineering, medical technology, machine knives, shears, cutting tools, razors, automotive industry, food technology, fasteners, decoration purposes, kitchen equipment, power engineering, springs, piston rods, screws.

**Tolerances****Standard values**

Delivery condition: maximum 241 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,36	0	0	0	0	12,5
0,42	1,0	1,0	0,04	0,015	14,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/4031-4

**AISI / SAE 1.4031 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.4031

via smartphone / tablet:



PREMIUM 1.4031 – AISI / SAE ~420 (X39Cr13)

€co-Präz® 500 [€co]

Length: 500 mm

	THICKNESS [mm]													
	2,3	3,3	4,3	5,3	6,3	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3
WIDTH	Available dimensions [mm]													
33	■	■	■	■	■	■	■	■	■	■	■	■	■	■
43	■	■	■	■	■	■	■	■	■	■	■	■	■	■
53	■	■	■	■	■	■	■	■	■	■	■	■	■	■
63	■	■	■	■	■	■	■	■	■	■	■	■	■	■
73	■	■	■	■	■	■	■	■	■	■	■	■	■	■
83	■	■	■	■	■	■	■	■	■	■	■	■	■	■
93	■	■	■	■	■	■	■	■	■	■	■	■	■	■
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■
323	■	■	■	■	■	■	■	■	■	■	■	■	■	■
343	■	■	■	■	■	■	■	■	■	■	■	■	■	■
353	■	■	■	■	■	■	■	■	■	■	■	■	■	■
363	■	■	■	■	■	■	■	■	■	■	■	■	■	■
383	■	■	■	■	■	■	■	■	■	■	■	■	■	■
403	■	■	■	■	■	■	■	■	■	■	■	■	■	■
423	■	■	■	■	■	■	■	■	■	■	■	■	■	■
443	■	■	■	■	■	■	■	■	■	■	■	■	■	■
453	■	■	■	■	■	■	■	■	■	■	■	■	■	■
463	■	■	■	■	■	■	■	■	■	■	■	■	■	■
483	■	■	■	■	■	■	■	■	■	■	■	■	■	■
503	■	■	■	■	■	■	■	■	■	■	■	■	■	■


**Technical properties**

Martensitic chromium steel with good mechanical properties. Excellent polishing properties, good corrosion resistance, good chemical resistance and difficult to weld. Due to its high contents of carbon excellent to use for cutting tools. The material is conditionally acid resistant.

Working hardness: approx. 50-55 HRC.

**Applications**

Mechanical engineering, medical technology, machine knives, shears, cutting tools, razors, automotive industry, food technology, fasteners, decoration purposes, kitchen equipment, power engineering, springs, piston rods, screws.

**Tolerances****Standard values**

Delivery condition: maximum 241 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,36	0	0	0	0	12,5
0,42	1,0	1,0	0,04	0,015	14,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/4031-5

**AISI / SAE 1.4031 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.4031

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.4841
3141.4571
316Ti1.4418
S 165 M1.4404/1.4401
316L/3161.4305
3031.4301
3041.4125
440C1.4122
1.41221.4112
440B1.4104
430F1.4057
4311.4034
1.40341.4031
4201.4021
4201.4006
410

1.4841
3141.4571
316Ti1.4418
S 165 M1.4404/1.4401
316L/3161.4305
3031.4301
3041.4125
440C1.4122
1.41221.4112
440B1.4104
430F1.4057
4311.4034
1.40341.4031
4201.4021
4201.4006
410**PREMIUM 1.4031 – AISI / SAE ~420 (X39Cr13)****Hart-Präz® 250 [Hart]**

Length: 250 mm


	THICKNESS [mm]												
	2,2	2,7	3,2	3,7	4,2	4,7	5,2	6,2	7,2	8,2	9,2	10,2	12,2
WIDTH	Available dimensions [mm]												
250	■	■	■	■	■	■	■	■	■	■	■	■	■

Hart-Präz® 500 [Hart]

Length: 500 mm

	THICKNESS [mm]												
	2,2	2,7	3,2	3,7	4,2	4,7	5,2	6,2	7,2	8,2	9,2	10,2	12,2
WIDTH	Available dimensions [mm]												
250	■	■	■	■	■	■	■	■	■	■	■	■	■

Hardened dimensions are delivered with approx. 50 HRC, at least 2x tempered.


**Technical properties**

Martensitic chromium steel with good mechanical properties. Excellent polishing properties, good corrosion resistance, good chemical resistance and difficult to weld. Due to its high contents of carbon excellent to use for cutting tools. The material is conditionally acid resistant.

Working hardness: approx. 50-55 HRC.

**Applications**

Mechanical engineering, medical technology, machine knives, shears, cutting tools, razors, automotive industry, food technology, fasteners, decoration purposes, kitchen equipment, power engineering, springs, piston rods, screws.

**Tolerances****Standard values**

Delivery condition: approx. 50 HRC
Chemical composition:

C	Si	Mn	P	S	Cr
0,36	0	0	0	0	12,5
0,42	1,0	1,0	0,04	0,015	14,5

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/4031-11-H

**AISI / SAE 1.4031 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.4031

via smartphone/tablet:



PREMIUM 1.4031 – AISI / SAE ~420 (X39Cr13)


Precision round steel without machining allowance [PRS]
Specification: bright drawn/ground, ISO h9

Ø [mm]	LENGTH [mm]
	1.000
Available dimensions [•]	
15,0	•
16,0	•
18,0	•
20,0	•
25,0	•
30,0	•
35,0	•
40,0	•
45,0	•
50,0	•

Precision round steel with machining allowance [PRS/BA]
Specification: peeled /rough-turned

Ø [mm]	LENGTH [mm]	
	500	1.000
Available dimensions [•]		
20,5	•	•
25,5	•	•
30,5	•	•
35,5	•	•
40,5	•	•
45,5	•	•
50,5	•	•
55,5	•	•
60,5	•	•
65,5		•
70,5		•
80,5		•
85,5		•
90,5		•
100,5		•

Larger diameters, up to 400,5 mm, and different lengths (e.g. round blanks) available on request!

**Tolerances****Standard values**

Delivery condition: maximum 241 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,36	0	0	0	0	12,5
0,42	1,0	1,0	0,04	0,015	14,5

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop [PRS]**

www.premium-steel.eu/4031-6

[PRS/BA]

www.premium-steel.eu/4031-7

**Technical properties**

Martensitic chromium steel with good mechanical properties. Excellent polishing properties, good corrosion resistance, good chemical resistance and difficult to weld. Due to its high contents of carbon excellent to use for cutting tools. The material is conditionally acid resistant.
Working hardness: approx. 50-55 HRC.

**Applications**

Mechanical engineering, medical technology, machine knives, shears, cutting tools, razors, automotive industry, food technology, fasteners, decoration purposes, kitchen equipment, power engineering, springs, piston rods, screws.

**AISI / SAE 1.4031 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.4031

via smartphone/tablet:

NAVIGATION/
STEEL GRADES

1.4841
314

1.4571
316Ti

1.4418
S 165 M

1.4404/1.4401
316L/316

1.4305
303

1.4301
304

1.4125
440C

1.4122
1.4122

1.4112
440B

1.4104
430F

1.4057
431

1.4034
1.4034

1.4031
420

1.4021
420


1.4006
410

PREMIUM 1.4021 – AISI / SAE ~420 (X20Cr13)

€co-Präz® 500 [€co]

Length: 500 mm

	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values**

Delivery condition: maximum 252 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,16	0	0	0	0	12,0
0,25	1,0	1,5	0,04	0,015	14,0

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/4021-5

**Technical properties**

Martensitic chromium steel with good mechanical properties (tempered condition). With the ability to polish this material to a high gloss finish it is ideally suited as knife steel. Good forgeability, medium weldability and is conditionally acid resistant. Working hardness: approx. 25 HRC (delivery condition) up to 47 HRC.

**Applications**

Automotive industry, power engineering, turbine and power plant construction, medical technology, mechanical engineering, petrochemical industry, cutting tool industry, knives, fasteners, architecture and decoration.

**AISI / SAE 1.4021 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.4021

via smartphone/tablet:



PREMIUM 1.4021 – AISI / SAE ~420 (X20Cr13)

Precision round steel without machining allowance [PRS]

Specification: bright drawn / ground, ISO h9

Ø [mm]	LENGTH [mm]		
	1.000		
Ø [mm]	Available dimensions [•]		
8,0	•	»	
10,0	•	30,0	•
11,0	•	32,0	•
12,0	•	35,0	•
14,0	•	36,0	•
15,0	•	38,0	•
16,0	•	40,0	•
18,0	•	45,0	•
20,0	•	50,0	•
22,0	•	55,0	•
24,0	•	60,0	•
25,0	•	70,0	•
26,0	•	80,0	•
28,0	•		
»			


Further diameters on request.

**Technical properties**

Martensitic chromium steel with good mechanical properties (tempered condition). With the ability to polish this material to a high gloss finish it is ideally suited as knife steel. Good forgeability, medium weldability and is conditionally acid resistant. Working hardness: approx. 25 HRC (delivery condition) up to 47 HRC.

**Applications**

Automotive industry, power engineering, turbine and power plant construction, medical technology, mechanical engineering, petrochemical industry, cutting tool industry, knives, fasteners, architecture and decoration.

**Tolerances****Standard values**

Delivery condition: maximum 252 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,16	0	0	0	0	12,0
0,25	1,0	1,5	0,04	0,015	14,0

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/4021-6

**AISI / SAE 1.4021 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.4021

via smartphone / tablet:

1.4841
3141.4571
316Ti1.4418
S 165 M1.4404/1.4401
316L/3161.4305
3031.4301
3041.4125
440C1.4122
1.41221.4112
440B1.4104
430F1.4057
4311.4034
1.40341.4031
420**1.4021**
4201.4006
410

ABRAMS®

TOOL STEEL I

TOOL STEEL II

HIGH SPEED STEEL

STAINLESS STEEL
corrosion resistant / acid resistant

**HEAT-TREATABLE STEEL,
CASE HARDENING- &
NITRIDING STEEL**

INFORMATION



ORDER THE SMALLEST AMOUNT - WITHOUT A MINIMUM ORDER VALUE!

ABRAMS!
PREMIUM STEEL

PREMIUM 1.4006 – AISI / SAE 410 (X12Cr13)

Eco-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Corrosion resistant, martensitic steel (tempered condition), which shows good mechanical and good corrosion resistance in moderately aggressive substances. It has a low susceptibility to embrittlement, is polishable to a high gloss and can be used at temperatures up to 400°C. Working hardness: approx. 25 HRC (delivery condition) up to 31 HRC.

**Applications**

Hydraulic engineering, mechanical engineering, pump industry, oil industry, petrochemical industry, decorative uses, kitchen equipment, food industry, environmental technology, energy technology (hydroelectric power).

**Tolerances****Standard values**

Delivery condition: maximum 252 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Ni
0,08	0	0	0	0	11,5	0
0,15	1,0	1,5	0,04	0,03	13,5	0,75

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/410-5

**AISI / SAE 410 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/410

via smartphone/tablet:

NAVIGATION/
STEEL GRADES1.4841
3141.4571
316Ti1.4418
S 165 M1.4404/1.4401
316L/3161.4305
3031.4301
3041.4125
440C1.4122
1.41221.4112
440B1.4104
430F1.4057
4311.4034
1.40341.4031
4201.4021
4201.4006
410

SPECIFICATIONS !

Our delivery program contains 32.629 different specification / standard dimensions.

Any dimension is available in different **heights**, **widths** and **lengths**. On request – according to your needs!



Precision flat steel without machining allowance [PFS] acc. to DIN 59350

For example: 100,0 x 20,0 x 1.000 mm

- **W** ground/milled, tol. +0,2 /-0 mm
- **T** coplanar ground, tol. +0,05 /-0 mm
- **L** milled/sawn, tol. +35 /-0 mm
- **Exception: PREMIUM 1.1730 – AISI / SAE 1045: W** +0,4 /-0 mm, **T** +0,25 /-0 mm



Precision round steel without machining allowance [PRS]

- bright ground, tol.: Ø ISO h8, **L** +10 /-10 mm
- bright drawn/finely peeled /ground, tol.: Ø ISO h9, **L** +10 /-10 mm
- bright finely peeled, tol.: Ø ISO h11, **L** +10 /-10 mm



Precision flat steel with machining allowance [PRS/BA]

For example: 100,3 x 20,3 x 1.000 mm

- **W** ground/milled, tol. +0,4 /-0 mm
- **T** coplanar ground/finely milled, tol. +0, /-0 mm
- **L** milled/sawn, tol. +35 /-0 mm



Precision round steel with machining allowance [PRS/BA]

- peeled / rough-turned, tol.: Ø +tol./-0 mm, **L** +tol./-0 mm
- **Exception PREMIUM 1.3343 – AISI / SAE M2:**
L 1.000 mm, tol. **L** +10 /-10 mm
- **Particularity: PREMIUM 1.2826 – AISI / SAE 1.2826, PREMIUM 1.2360 – AISI / SAE –Chipper, PREMIUM 1.2067 – AISI / SAE L3:**
Ø are metric full values (for example 30,0 mm), therefore there is no basic machining allowance (for example 30,5 mm)



Eco-Präz® [Eco]

For example: 103 x 20,3 x 500 mm

- **W** sawn/black, tol. +3 /-0 mm
- **T** finely milled, tol. +0, /-0 mm
- **L** sawn/black, tol. +15 /-0 mm



Round steel [RS]

- black, tol.: Ø +1 /-1 mm (aspired), **L** +tol./-0 mm



Hart-Präz® [Hart]

For example: 250 x 10,2 x 500 mm

- **W** sawn/black, Tol. +10/-0 mm
- **T** coplanar ground, Tol. +0,2/-0 mm
- **L** sawn/black, Tol. +10/-0 mm

Planeness: +0,2/-0 mm of the entire surface (aspired)



Erosion block/EDM block – annealed or hardened [EB]

For example: 200,3 x 200,3 x 40,0 mm

- **Square dimension** milled/ground, tol. +2 /-0 mm
- **T** finely milled /ground, tol. +0,25/-0 mm
- Grain structure is vertically directed in relation to base surface

STEEL CLASSIFICATIONS !

Steel grades are classified by their technical **properties** and/or by their intended use.

For example:

Cold work steel, hot work steel, plastic mould steel, high speed steel, corrosion resistant steel or case hardening steel.

Steel grades are often assigned to several classification groups.

For more details on classification see www.steel-guide.eu/glossary



PREMIUM 1.8550 – AISI / SAE 1.8550 (34CrAlNi7)

Round steel [RS]

Specification: black

Ø [mm]	LENGTH [mm]	
	500	1.000
Available dimensions [•]		
15	•	•
20	•	•
25	•	•
30	•	•
35	•	•
40	•	•
45	•	•
50	•	•
55	•	•
60	•	•
65		•
70		•
75		•
80		•
85		•
90		•
95		•
100		•


Larger diameters, up to 650 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

The AISI / SAE 1.8550 is a CrAlNiMo alloyed nitriding steel (tempered condition), which is used for heavy duty parts in mechanical engineering due to its high wear resistance. Hardenable surface, difficult to weld. Achievable nitriding hardness approx. 950 HV (approx. 68 HRC).

**Applications**

Mechanical engineering, plastic processing, automotive industry, plant engineering, engine and piston construction, drive technology, cam plates, eccentric, pinion shafts.

**Tolerances****Standard values**

Delivery condition: maximum 323 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni	Al
0,30	0	0,40	0	0	1,50	0,15	0,85	0,8
0,37	0,40	0,70	0,025	0,03	1,80	0,25	1,15	1,2

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/8550-8

**AISI / SAE 1.8550 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.8550

via smartphone / tablet:



PREMIUM 1.8519 – AISI / SAE 1.8519 (31CrMoV9)

Round steel [RS]
Specification: black

Ø [mm]	LENGTH [mm]	
	500	1.000
	Available dimensions [•]	
20	•	•
25	•	•
30	•	•
35	•	•
40	•	•
45	•	•
50	•	•
55	•	•
60	•	•
65		•
70		•
75		•
80		•
85		•
90		•
95		•
100		•


Larger diameters, up to 600 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

CrMoV alloyed nitriding steel (tempered condition), which is used for automotive engineering and propulsion techniques due to its high wear resistance.
Achievable nitriding hardness approx. 800 HV (approx. 64 HRC).

**Applications**

Automotive industry, drive technology, mechanical engineering, valve construction, plant engineering, engine and piston construction.

**Tolerances****Standard values**

Delivery condition: maximum 352 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	V
0,27	0	0,4	0	0	2,3	0,15	0,10
0,34	0,4	0,7	0,025	0,035	2,7	0,25	0,25

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/8519-8

**AISI / SAE 1.8519 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.8519

via smartphone/tablet:



1.8550
1.8550

1.8519
1.8519

1.7227
4140

1.7225
4140

1.7225+QT
4140+QT

1.7147
5120

1.7131
5115

1.6587
4820

1.6582
4337

1.6580
4340

GOOD MACHINABILITY ...




... DUE TO ADDED SULPHUR – BS 709 M 40 !

PREMIUM 1.7227 – AISI / SAE 4140 (42CrMoS4)

Eco-Präz® 500 [€co]

Length: 500 mm

	THICKNESS [mm]															
	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	60,3	70,3	80,3	90,3	100,3	120,3	140,3
WIDTH	Available dimensions [mm]															
33	■	■	■	■	■	■	■									
43	■	■	■	■	■	■	■	■								
53	■	■	■	■	■	■	■	■	■							
63	■	■	■	■	■	■	■	■	■	■						
73	■	■	■	■	■	■	■	■	■	■	■					
83	■	■	■	■	■	■	■	■	■	■	■	■				
93	■	■	■	■	■	■	■	■	■	■	■	■	■			
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Tolerances****Standard values**

Delivery condition: maximum 217 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo
0,38	0	0,6	0	0,02	0,9	0,15
0,45	0,4	0,9	0,035	0,04	1,2	0,3

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/7227-5

**Technical properties**

Versatile heat-treatable steel (annealed condition) with high strength and high toughness, that is often used for demanding applications in automotive engineering. Better machinability due to the addition of sulphur, very low distortion.
Working hardness: approx. 27-48 HRC.

**Applications**

Mechanical engineering, machine components, axes, knuckles, connecting rods, crankshafts, gear shafts, pinions, gears, bandages, base plates, assembling parts.

**AISI / SAE 1.7227 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/1.7227

via smartphone/tablet:



1.8550
1.8550

1.8519
1.8519

1.7227
4140

1.7225
4140

1.7225+QT
4140+QT

1.7147
5120

1.7131
5115

1.6587
4820

1.6582
4337

1.6580
4340

PREMIUM 1.7225 – AISI / SAE 4140 (42CrMo4)

€co-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]																	
	2,3	3,3	4,3	5,3	6,3	8,3	10,3	12,3	15,3	20,3	25,3	30,3	35,3	40,3	50,3	60,3	80,3	
WIDTH	Available dimensions [mm]																	
33	■	■	■	■	■	■	■	■	■	■	■	■						
43	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
53	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
63	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
73	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
83	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
93	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
323	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
343	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
353	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
363	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
383	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
403	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
423	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
443	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
453	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
463	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
483	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
503	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	

**Technical properties**

Heat-treatable steel (annealed condition) that can be used for a wide range of applications with a high degree of strength and toughness. Often used for demanding applications in automotive engineering. In quenched and tempered condition it is used in machine construction. Working hardness: 27-48 HRC.

**Applications**

Mechanical engineering, machine parts, axes, knuckles, connecting rods, crankshafts, gear shafts, pinions, gears, bandages, base plates, assembling parts.

**Tolerances****Standard values**

Delivery condition: maximum 217 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo
0,38	0	0,6	0	0	0,9	0,15
0,45	0,4	0,9	0,035	0,035	1,2	0,3

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/4140-5

**AISI / SAE 4140 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/4140

via smartphone/tablet:



PREMIUM 1.7225 – AISI / SAE 4140 (42CrMo4)

€co-Präz® 1.000 [€co]

Length: 1.000 mm


	THICKNESS [mm]																
	2,3	3,3	4,3	5,3	6,3	8,3	10,3	12,3	15,3	20,3	25,3	30,3	35,3	40,3	50,3	60,3	80,3
WIDTH	Available dimensions [mm]																
33	■	■	■	■	■	■	■	■	■	■	■	■					
43	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
53	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		
63	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
73	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
83	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
93	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
353	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
403	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
453	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
503	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Heat-treatable steel (annealed condition) that can be used for a wide range of applications with a high degree of strength and toughness. Often used for demanding applications in automotive engineering. In quenched and tempered condition it is used in machine construction. Working hardness: 27-48 HRC.

**Applications**

Mechanical engineering, machine parts, axes, knuckles, connecting rods, crankshafts, gear shafts, pinions, gears, bandages, base plates, assembling parts.

**Tolerances****Standard values**

Delivery condition: maximum 217 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo
0,38	0	0,6	0	0	0,9	0,15
0,45	0,4	0,9	0,035	0,035	1,2	0,3

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/4140-10

**AISI / SAE 4140 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/4140

via smartphone/tablet:



1.8550

1.8550

1.8519

1.8519

1.7227

4140

1.7225

4140

1.7225+QT

4140+QT

1.7147

5120

1.7131

5115

1.6587

4820

1.6582

4337

1.6580

4340

ABRAMS®

TOOL STEEL I

TOOL STEEL II

HIGH SPEED STEEL

STAINLESS STEEL
corrosion resistant / acid resistant

HEAT-TREATABLE STEEL,
CASE HARDENING- &
NITRIDING STEEL

INFORMATION

PASSION !

ABRAMS![®]
PREMIUM STEEL

PREMIUM 1.7225+QT – AISI / SAE 4140+QT (42CrMo4+QT)

Round steel [RS]
Specification: black

Ø [mm]	LENGTH [mm]	
	500	1.000
	Available dimensions [•]	
16	•	•
18	•	•
20	•	•
22	•	•
25	•	•
30	•	•
32	•	•
35	•	•
40	•	•
42	•	•
45	•	•
50	•	•
55	•	•
60	•	•
65		•
70		•
75		•
80		•
90		•
100		•

Larger diameters, up to 120 mm, and different lengths (e.g. round blanks) available on request!


**Technical properties**

Heat-treatable steel (tempered condition) that can be used for a wide range of applications with a high degree of strength and toughness. Often used for demanding applications in automotive engineering. In quenched and tempered condition it is used in machine construction.

Working hardness: 27 (min. hardness/delivery condition) - 48 HRC.

**Applications**

Mechanical engineering, machine parts, axes, knuckles, connecting rods, crankshafts, gear shafts, pinions, gears, bandages, base plates, assembling parts.

**Tolerances****Standard values**

Delivery condition: maximum 380 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo
0,38	0	0,6	0	0	0,9	0,15
0,45	0,4	0,9	0,035	0,035	1,2	0,3

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/4140QT-8

**AISI / SAE 4140+QT – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/4140QT

via smartphone/tablet:



1.8550
1.8550

1.8519
1.8519

1.7227
4140

1.7225
4140

1.7225+QT
4140+QT

1.7147
5120

1.7131
5115

1.6587
4820

1.6582
4337

1.6580
4340

CASE HARDENING STEEL !




PREMIUM 1.7147 – AISI / SAE 5120 (20MnCr5, EC100)

Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm

	THICKNESS [mm]															
	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	36,3	40,3	50,3	60,3	70,3	80,3	100,3
WIDTH	Available dimensions [mm]															
15,3				■												
20,3	■	■	■	■	■	■										
25,3	■	■	■	■	■	■	■									
30,3	■	■	■	■	■	■	■	■								
32,3	■	■	■	■	■	■	■	■	■							
40,3	■	■	■	■	■	■	■	■		■	■					
50,3	■	■	■	■	■	■	■	■		■	■	■				
60,3	■	■	■	■	■	■	■	■		■	■	■	■			
70,3	■	■	■	■	■	■	■	■		■	■	■	■	■		
80,3	■	■	■	■	■	■	■	■		■	■	■	■	■	■	
100,3	■	■	■	■	■	■	■	■		■	■	■	■	■		■
120,3	■	■	■	■	■	■	■	■		■	■	■	■			
150,3	■	■	■	■	■	■	■	■		■	■	■	■			
180,3	■	■	■	■	■	■	■	■		■	■	■	■			
200,3	■	■	■	■	■	■	■	■		■	■	■	■			
250,3	■	■	■	■	■	■	■	■		■	■	■	■			
300,3	■	■	■	■	■	■	■	■		■	■	■	■			
500 *		■	■	■	■	■	■	■		■	■	■	■			

* Width and length sawn/black with +tol./-0 mm

**Tolerances****Standard values**

Delivery condition: maximum 217 HB

Chemical composition:

C	Si	Mn	P	S	Cr
0,17	0	1,1	0	0	1,0
0,22	0,4	1,4	0,025	0,035	1,3

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**www.premium-steel.eu/7147-4**Technical properties**

Cold work and plastic mould steel (group of case hardening steel) with the objective of high surface hardness with core toughness. Excellent machinability, good cold hobbing and polishing properties. The tensile strength is a result of the combination of hardened surface and tough core. Working hardness (surface): 58-60 HRC.

**Applications**

Mechanical engineering, jig construction, plant engineering, apparatus engineering, plastic processing, plastic moulds, synthetic resin moulds, base plates, bending bars, guide columns, gear parts, joint parts, shafts, gears, rods, bevel gears, crown wheels, piston pins, camshafts, bolts, pins, cardan joints.

1.8550

1.8550

1.8519

1.8519

1.7227

4140

1.7225

4140

1.7225+QT

4140+QT

1.7147**5120**

1.7131

5115

1.6587

4820

1.6582

4337

1.6580

4340

**AISI / SAE 5120 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/7147

via smartphone/tablet:



PREMIUM 1.7147 – AISI / SAE 5120 (20MnCr5, EC100)

€co-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]										
	6,3	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	
WIDTH	Available dimensions [mm]										
33	■	■	■	■	■	■	■	■			
43	■	■	■	■	■	■	■	■	■		
53	■	■	■	■	■	■	■	■	■	■	■
63	■	■	■	■	■	■	■	■	■	■	■
73	■	■	■	■	■	■	■	■	■	■	■
83	■	■	■	■	■	■	■	■	■	■	■
93	■	■	■	■	■	■	■	■	■	■	■
103	■	■	■	■	■	■	■	■	■	■	■
123	■	■	■	■	■	■	■	■	■	■	■
143	■	■	■	■	■	■	■	■	■	■	■
153	■	■	■	■	■	■	■	■	■	■	■
163	■	■	■	■	■	■	■	■	■	■	■
183	■	■	■	■	■	■	■	■	■	■	■
203	■	■	■	■	■	■	■	■	■	■	■
223	■	■	■	■	■	■	■	■	■	■	■
243	■	■	■	■	■	■	■	■	■	■	■
253	■	■	■	■	■	■	■	■	■	■	■
263	■	■	■	■	■	■	■	■	■	■	■
283	■	■	■	■	■	■	■	■	■	■	■
303	■	■	■	■	■	■	■	■	■	■	■
323	■	■	■	■	■	■	■	■	■	■	■
343	■	■	■	■	■	■	■	■	■	■	■
353	■	■	■	■	■	■	■	■	■	■	■
363	■	■	■	■	■	■	■	■	■	■	■
383	■	■	■	■	■	■	■	■	■	■	■
403	■	■	■	■	■	■	■	■	■	■	■
423	■	■	■	■	■	■	■	■	■	■	■
443	■	■	■	■	■	■	■	■	■	■	■
453	■	■	■	■	■	■	■	■	■	■	■
463	■	■	■	■	■	■	■	■	■	■	■
483	■	■	■	■	■	■	■	■	■	■	■
503	■	■	■	■	■	■	■	■	■	■	■

**Technical properties**

Cold work and plastic mould steel (group of case hardening steel) with the objective of high surface hardness with core toughness. Excellent machinability, good cold hobbing and polishing properties. The tensile strength is a result of the combination of hardened surface and tough core. Working hardness (surface): 58-60 HRC.

**Applications**

Mechanical engineering, jig construction, plant engineering, apparatus engineering, plastic processing, plastic moulds, synthetic resin moulds, base plates, bending bars, guide columns, gear parts, joint parts, shafts, gears, rods, bevel gears, crown wheels, piston pins, camshafts, bolts, pins, cardan joints.

**Tolerances****Standard values**

Delivery condition: maximum 217 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,17	0	1,1	0	0	1,0
0,22	0,4	1,4	0,025	0,035	1,3

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/5120-5

**AISI / SAE 5120 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/5120

via smartphone/tablet:



PREMIUM 1.7147 – AISI / SAE 5120 (20MnCr5, EC100)

Round steel [RS]

Specification: black

	LENGTH [mm]	
	500	1.000
Ø [mm]	Available dimensions [•]	
20	•	•
25	•	•
30	•	•
35	•	•
40	•	•
45	•	•
50	•	•
55	•	•
60	•	•
65		•
70		•
75		•
80		•
85		•
90		•
100		•


Larger diameters, up to 200 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Cold work and plastic mould steel (group of case hardening steel) with the objective of high surface hardness with core toughness. Excellent machinability, good cold hobbing and polishing properties. The tensile strength is a result of the combination of hardened surface and tough core. Working hardness (surface): 58-60 HRC.

**Applications**

Mechanical engineering, jig construction, plant engineering, apparatus engineering, plastic processing, plastic moulds, synthetic resin moulds, base plates, bending bars, guide columns, gear parts, joint parts, shafts, gears, rods, bevel gears, crown wheels, piston pins, camshafts, bolts, pins, cardan joints.

**Tolerances****Standard values**

Delivery condition: maximum 217 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,17	0	1,1	0	0	1,0
0,22	0,4	1,4	0,025	0,035	1,3

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/5120-8

**AISI / SAE 5120 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/5120

via smartphone/tablet:



1.8550
1.8550

1.8519
1.8519

1.7227
4140

1.7225
4140

1.7225+QT
4140+QT

1.7147
5120

1.7131
5115

1.6587
4820

1.6582
4337

1.6580
4340

HEART AND SOUL IN STEEL !




PREMIUM 1.7131 – AISI / SAE 5115 (16MnCr5, EC80)

Precision flat steel with machining allowance [PFS/BA]

Length: 1.000 mm

	THICKNESS [mm]															
	8,2	10,3	12,3	15,3	16,3	20,3	25,3	30,3	32,3	36,3	40,3	50,3	60,3	70,3	80,3	100,3
WIDTH	Available dimensions [mm]															
15,3				■												
20,3	■	■	■	■	■	■										
25,3	■	■	■	■	■	■	■									
30,3	■	■	■	■	■	■	■	■								
32,3	■	■	■	■	■	■	■	■	■							
40,3	■	■	■	■	■	■	■	■		■	■					
50,3	■	■	■	■	■	■	■	■		■	■	■				
60,3	■	■	■	■	■	■	■	■		■	■	■	■			
70,3	■	■	■	■	■	■	■	■		■	■	■	■	■		
80,3	■	■	■	■	■	■	■	■		■	■	■	■		■	
100,3	■	■	■	■	■	■	■	■		■	■	■	■			■
120,3	■	■	■	■	■	■	■	■		■	■	■	■			
150,3	■	■	■	■	■	■	■	■		■	■	■	■			
180,3	■	■	■	■	■	■	■	■		■	■	■	■			
200,3	■	■	■	■	■	■	■	■		■	■	■	■			
250,3	■	■	■	■	■	■	■	■		■	■	■	■			
300,3	■	■	■	■	■	■	■	■		■	■	■	■			
500 *		■	■	■	■	■	■	■		■	■	■	■			

* Width and length sawn/black with +tol./-0 mm

**Tolerances****Standard values**

Delivery condition: maximum 217 HB

Chemical composition:

C	Si	Mn	P	S	Cr
0,14	0	1,0	0	0	0,8
0,19	0,4	1,3	0,025	0,035	1,1

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**www.premium-steel.eu/5115-4**Technical properties**

Cold work and plastic mould steel (group of case hardening steel) with the objective of high surface hardness with core toughness. Excellent machinability, good cold hobbing and polishing properties. The tensile strength is a result of the combination of hardened surface and tough core. Working hardness (surface): 58-60 HRC.

**Applications**

Mechanical engineering, jig construction, plant engineering, apparatus engineering, plastic processing, plastic moulds, synthetic resin moulds, base plates, bending bars, guide columns, gear parts, joint parts, shafts, gears, rods, bevel gears, crown wheels, piston pins, camshafts, bolts, pins, cardan joints.

1.8550

1.8550

1.8519

1.8519

1.7227

4140

1.7225

4140

1.7225+QT

4140+QT

1.7147

5120

1.7131

5115

1.6587

4820

1.6582

4337

1.6580

4340

**AISI / SAE 5115 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/5115

via smartphone/tablet:



PREMIUM 1.7131 – AISI / SAE 5115 (16MnCr5, EC80)

€co-Präz® 500 [€co]

Length: 500 mm


	THICKNESS [mm]														
	2,3	3,3	4,3	5,3	6,3	8,3	10,3	12,3	15,3	20,3	25,3	30,3	40,3	50,3	
WIDTH	Available dimensions [mm]														
33	■	■	■	■	■	■	■	■	■	■	■	■			
43	■	■	■	■	■	■	■	■	■	■	■	■	■		
53	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
63	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
73	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
83	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
93	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
103	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
123	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
143	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
153	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
163	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
183	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
203	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
223	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
243	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
253	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
263	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
283	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
303	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
323	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
343	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
353	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
363	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
383	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
403	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
423	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
443	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
453	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
463	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
483	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
503	■	■	■	■	■	■	■	■	■	■	■	■	■	■	

**Technical properties**

Cold work and plastic mould steel (group of case hardening steel) with the objective of high surface hardness with core toughness. Excellent machinability, good cold hobbing and polishing properties. The tensile strength is a result of the combination of hardened surface and tough core. Working hardness (surface): 58 - 60 HRC.

**Applications**

Mechanical engineering, jig construction, plant engineering, apparatus engineering, plastic processing, plastic moulds, synthetic resin moulds, base plates, bending bars, guide columns, gear parts, joint parts, shafts, gears, rods, bevel gears, crown wheels, piston pins, camshafts, bolts, pins, cardan joints.

**Tolerances****Standard values**

Delivery condition: maximum 217 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,14	0	1,0	0	0	0,8
0,19	0,4	1,3	0,025	0,035	1,1

**If you need customised dimensions -**

Any dimension available in different heights, widths and lengths.
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/5115-5

**AISI / SAE 5115 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/5115

via smartphone/tablet:



PREMIUM 1.7131 – AISI / SAE 5115 (16MnCr5, EC80)

Round steel [RS]
Specification: black

	LENGTH [mm]	
	500	1.000
Ø [mm]	Available dimensions [•]	
20	•	•
25	•	•
30	•	•
35	•	•
40	•	•
45	•	•
50	•	•
55	•	•
60	•	•
65		•
70		•
75		•
80		•
85		•
90		•
100		•


Larger diameters, up to 200 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

Cold work and plastic mould steel (group of case hardening steel) with the objective of high surface hardness with core toughness. Excellent machinability, good cold hobbing and polishing properties. The tensile strength is a result of the combination of hardened surface and tough core. Working hardness (surface): 58-60 HRC.

**Applications**

Mechanical engineering, jig construction, plant engineering, apparatus engineering, plastic processing, plastic moulds, synthetic resin moulds, base plates, bending bars, guide columns, gear parts, joint parts, shafts, gears, rods, bevel gears, crown wheels, piston pins, camshafts, bolts, pins, cardan joints.

**Tolerances****Standard values**

Delivery condition: maximum 217 HB
Chemical composition:

C	Si	Mn	P	S	Cr
0,14	0	1,0	0	0	0,8
0,19	0,4	1,3	0,025	0,035	1,1

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).
On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/5115-8

**AISI / SAE 5115 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/5115

via smartphone/tablet:



1.8550
1.8550

1.8519
1.8519

1.7227
4140

1.7225
4140

1.7225+QT
4140+QT

1.7147
5120

1.7131
5115

1.6587
4820

1.6582
4337

1.6580
4340

ABRAMS®

TOOL STEEL I

TOOL STEEL II

HIGH SPEED STEEL

STAINLESS STEEL
corrosion resistant / acid resistant

**HEAT-TREATABLE STEEL,
CASE HARDENING- &
NITRIDING STEEL**

INFORMATION



STEEL MADE WITH "STYLE"!

ABRAMS!
PREMIUM STEEL®

PREMIUM 1.6587 – AISI / SAE 4820 (18CrNiMo7-6)

Round steel [RS]

Specification: black

	LENGTH [mm]	
	500	1.000
Ø [mm]	Available dimensions [•]	
20	•	•
25	•	•
30	•	•
35	•	•
40	•	•
45	•	•
50	•	•
55	•	•
60	•	•
65		•
70		•
75		•
80		•
85		•
90		•
95		•
100		•


Larger diameters, up to 700 mm, and different lengths (e.g. round blanks) available on request!

**Technical properties**

CrNiMo alloyed case-hardening steel for highly stressed components with high core strength and toughness. This steel is used for gear parts such as ring gears or drive pinions and gear wheels. The AISI / SAE 4820 is usually difficult to weld. Surface hardens according to case hardness: approx. 58-60 HRC.

**Applications**

Shafts, gear parts, gears, bevel gears, driving pinion.

**Tolerances****Standard values**

Delivery condition: maximum 229 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni
0,15	0	0,5	0	0	1,5	0,25	1,4
0,21	0,4	0,9	0,025	0,035	1,8	0,35	1,7

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/4820-8

**AISI / SAE 4820 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/4820

via smartphone/tablet:



1.8550
1.8550

1.8519
1.8519

1.7227
4140

1.7225
4140

1.7225+QT
4140+QT

1.7147
5120

1.7131
5115

1.6587
4820

1.6582
4337

1.6580
4340


PREMIUM 1.6582 – AISI / SAE 4337 (34CrNiMo6)

Round steel [RS]

Specification: black

	LENGTH [mm]	
	500	1.000
Ø [mm]	Available dimensions [•]	
20	•	•
25	•	•
30	•	•
35	•	•
40	•	•
45	•	•
50	•	•
55	•	•
60	•	•
65		•
70		•
75		•
80		•
85		•
90		•
95		•
100		•

Larger diameters, up to 700 mm, and different lengths (e.g. round blanks) available on request!

**Tolerances****Standard values**

Delivery condition: maximum 352 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni
0,3	0	0,5	0	0	1,3	0,15	1,3
0,38	0,4	0,8	0,025	0,035	1,7	0,3	1,7

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/4337-8

**Technical properties**

CrNiMo alloyed heat-treatable steel (tempered condition) for components with high strength and toughness. It is used for through-hardening components in automotive and mechanical engineering. The material is usually difficult to weld.

Components are usually used in the quenched and tempered state. An optionally achievable surface hardness through nitriding: approx. 58-62HRC.

**Applications**

Shafts, gear parts, gears, bevel gears, driving pinion.

**AISI / SAE 4337 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/4337

via smartphone / tablet:




PREMIUM 1.6580 – AISI / SAE 4340 (30CrNiMo8)

Round steel [RS]

Specification: black

Ø [mm]	LENGTH [mm]	
	500	1.000
	Available dimensions [•]	
25	•	•
30	•	•
35	•	•
40	•	•
45	•	•
50	•	•
55	•	•
60	•	•
65		•
70		•
75		•
80		•
85		•
90		•
95		•
100		•

Larger diameters, up to 700 mm, and different lengths (e.g. round blanks) available on request!

**Tolerances****Standard values**

Delivery condition: maximum 380 HB
Chemical composition:

C	Si	Mn	P	S	Cr	Mo	Ni
0,26	0	0,3	0	0	1,8	0,3	1,8
0,34	0,4	0,6	0,025	0,035	2,2	0,5	2,2

**If you need customised dimensions -**

Any dimension available in different lengths (e.g. round blanks).

On request - according to your needs!

**Contact us**

T: +49 (0) 5 41/3 57 39-0

E: sales@abrams-industries.eu

**Direct access to our online shop**

www.premium-steel.eu/4340-8

**Technical properties**

CrNiMo alloyed heat-treatable steel (tempered condition) for components with high strength and toughness. It is used for through-hardening components in automotive and mechanical Engineering. The material is usually difficult to weld. Components are usually used in the quenched and tempered state. An optionally achievable surface hardness through nitriding: approx. 60-64HRC.

**Applications**

Shafts, gear parts, gears, bevel gears, driving pinion.

**AISI / SAE 4340 – all at a glance!**

Datasheets, online shop,
ABRAMS STEEL GUIDE® for alternatives:
www.premium-steel.eu/4340

via smartphone/tablet:



1.8550
1.8550

1.8519
1.8519

1.7227
4140

1.7225
4140

1.7225+QT
4140+QT

1.7147
5120

1.7131
5115

1.6587
4820

1.6582
4337

1.6580
4340

ABRAMS ARTPROJECTE !

„EXCELLENT WORK!“,

... ABRAMS PREMIUM STEEL® is proud to have produced a photographic calendar of the highest quality which has been very well received by our valued customers.

It has given us great pleasure to have had parts of our calendar included several times in the “JAHRBUCH DER WERBUNG/ GERMANY” as well as in a variety of trade journals. Through our photographic art project, we have sought to contrast the highly technical qualities of our steel with the softness and beauty of the human body.

To date, our efforts have been presented in six limited edition art calendars, which we trust will continue to bring delight to your working day.

For more information about all our art projects see www.premium-steel.eu/artprojects. You can also download our free PREMIUM-SCREENSAVER with all the pictures of the previous calendar projects and select pictures every three month as PREMIUM-WALLPAPER for your PC-screen or tablet (see category “downloads“).





WEIGHT TABLES !

Weight table for flat, square and round precision steel (in kg with a nominal dimension of 1.000 mm in length).

Also see www.premium-steel.eu/weights

	THICKNESS [mm]													
	2	3	4	5	6	8	10	12	15	20	25	30	40	50
WIDTH	Weight [kg/m]													
10	0,2	0,2	0,3	0,4	0,5	0,6	0,8							
15	0,2	0,4	0,5	0,6	0,7	0,9	1,2	1,4	1,8					
20	0,3	0,5	0,6	0,8	0,9	1,3	1,6	1,9	2,4	3,1				
25	0,4	0,6	0,8	1,0	1,2	1,6	2,0	2,4	2,9	3,9	4,9			
30	0,5	0,7	0,9	1,2	1,4	1,9	2,4	2,8	3,5	4,7	5,9	7,1		
40	0,6	0,9	1,3	1,6	1,9	2,5	3,1	3,8	4,7	6,3	7,9	9,4	12,6	
50	0,8	1,2	1,6	2,0	2,4	3,1	3,9	4,7	5,9	7,9	9,8	11,8	15,7	19,6
60	0,9	1,4	1,9	2,4	2,8	3,8	4,7	5,7	7,1	9,4	11,8	14,1	18,8	23,6
70	1,1	1,6	2,2	2,7	3,3	4,4	5,5	6,6	8,2	11,0	13,7	16,5	22,0	27,5
80	1,3	1,9	2,5	3,1	3,8	5,0	6,3	7,5	9,4	12,6	15,7	18,8	25,1	31,4
100	1,6	2,4	3,1	3,9	4,7	6,3	7,9	9,4	11,8	15,7	19,6	23,6	31,4	39,3
125	2,0	2,9	3,9	4,9	5,9	7,9	9,8	11,8	14,7	19,6	24,5	29,4	39,3	49,1
150	2,4	3,5	4,7	5,9	7,1	9,4	11,8	14,1	17,7	23,6	29,4	35,3	47,1	58,9
175	2,7	4,1	5,5	6,9	8,2	11,0	13,7	16,5	20,6	27,5	34,3	41,2	55,0	68,7
200	3,1	4,7	6,3	7,9	9,4	12,6	15,7	18,8	23,6	31,4	39,3	47,1	62,8	78,5
250	3,9	5,9	7,9	9,8	11,8	15,7	19,6	23,6	29,4	39,3	49,1	58,9	78,5	98,1
300	4,7	7,1	9,4	11,8	14,1	18,8	23,6	28,3	35,3	47,1	58,9	70,7	94,2	117,8

	DIAMETER Ø [mm]														
	3	5	10	15	20	25	30	40	50	60	70	80	90	100	»
	Weight [kg/m]														
	0,1	0,2	0,6	1,4	2,5	3,9	5,6	9,9	15,5	22,3	30,4	39,7	50,2	62,0	
»	120	140	160	180	200	250	300	350	400	450	500	550	600	650	
	Weight [kg/m]														
	89,3	121,5	158,7	200,9	248,0	387,5	558,0	759,5	992,0	1.255,5	1.550,0	1.875,5	2.232,0	2.619,5	

TRANSPARENCY IN ALL DETAILS !

Information regarding our portfolio (valid as of August 2024):

This product catalogue provides you with an overview of our 70 steel grades in 33.895 dimensions. For our current prices please refer to our online shop under www.premium-steel.eu/shop

Minimum order value:

Any quantity - however small - there is no minimum order value for you!

Packaging:

All products are carefully packed.

Handling and Delivery Fees:

Consignments of up to 40kg are dispatched via parcel. Consignments above 40kg are dispatched via freight forwarders. At ABRAMS PREMIUM STEEL®, we base all of our shipping costs on the principle that they are as transparent and comprehensible for our clients as possible.

Our current shipping costs are available on request: sales@abrams-industries.eu

For larger quantities please contact us.

For deliveries outside the EU, deliveries on Saturdays or express delivery services (guaranteed date and time) please contact us.

Delivery Time:

Standard products defined in our programme will be delivered as quickly as possible from stock. Individual custom requests will be manufactured and delivered on a short term basis. The standard delivery time is 3-5 working days.

Condition of payment:

Within 14 days net from invoice (subject to a positive credit screening).

HELPFUL INFORMATION CONCERNING PRECISION STEEL

ABRAMS INDUSTRIES®

ABRAMS PREMIUM STEEL®	www.premium-steel.eu	ABRAMS STEEL GUIDE®	www.steel-guide.eu
ABRAMS PREMIUM STEEL® Shop	www.premium-steel.eu/shop	ABRAMS® INDUSTRIES®	www.abrams-industries.eu
Steel grades		ABRAMS® News	www.abrams-industries.eu/news
Steel specifications	www.premium-steel.eu/specifications	ABRAMS GTC	www.abrams-industries.eu/gtc
Steel weight table (flat- and round)	www.premium-steel.eu/weights	ABRAMS PREMIUM ALUMINIUM®	premium-aluminium.eu
Current alloy surcharges	www.premium-steel.eu/alloysurcharges	ABRAMS® PREMIUM TOOLS	www.premium-gewindebohrer.eu
Current delivery informations	www.premium-steel.eu/deliveryfees	ABRAMS® Artprojects	abramsartprojects.com

The price list gives an overview of the general attributes and possible applications of precision tool steel which will support your choice of product depending on the various applications of the products, a guarantee of specific attributes and values must be confirmed contractual .

Errors and printing mistakes may occur.

©2024 Abrams Industries GmbH & Co. KG

ABRAMS!®

PREMIUM STEEL

								1.8550
								1.8519
1.2990 mod.	1.2714+QT L6+QT	1.2361	1.2312 P20+S			1.4841 314	1.4122	1.7227 4140
1.2842 O2	1.2709 ESU	1.2360 ~ Chipper	1.2311 P20	1.2083 ESU 420 ESR		1.4571 316Ti	1.4112 440B	1.7225 4140
1.2510 O1	1.2550 S1	1.2358	1.2294	1.2080 mod. D3 mod.		1.4418 S 165 M	1.4104 430F	1.7225+QT 4140+QT
1.2826	1.2436 D6	1.2344 H13	1.2210 L2	1.2067 L3 / L1		1.4404 316L	1.4057 431	1.7147 5120
1.2767 6F7	1.2379 D2	1.2344 ESU H13 ESR	1.2162	1.1730 1045	HSS 1.3343 M2	1.4401 316	1.4034	1.7131 5115
1.2767 ESU 6F7 ESR	1.2367	1.2343 H11	1.2099	1.0570 (St 52-3)	HSS PM 30 PM 30	1.4305 303	1.4031 420	1.6587 4820
1.2738 P20+Ni	1.2365 H10	1.2343 ESU H11 ESR	1.2085 420FM	Toolox 33	HSS PM 23 M3	1.4301 304	1.4021 420	1.6582 4337
1.2714 L6	1.2363 A2	1.2316	1.2083 420	Toolox 44	HSS PM 4 M4	1.4125 440C	1.4006 410	1.6580 4340

- + 70 STEELGRADES in 32.629 DIMENSIONS as
 - + PRECISION FLAT STEEL with / without machining allowance
 - + **€co-Präz®** - Standardized precision blanks
 - + **Hart-Präz®** - Hardened precision plates
 - + PRECISION ROUND STEEL with / without machining allowance
 - + ROUNDSTEEL
 - + EROSION BLOCK annealed / hardened
 - + WITHOUT MINIMUM ORDER VALUE AND AMOUNT
 - + SPECIAL CUSTOM DIMENSIONS SAWN - MILLED - GROUND
-
- = SUM OF YOUR COMPETITIVE ADVANTAGES!

ABRAMS PREMIUM STEEL®

is a registered trademark of
Abrams Industries GmbH & Co. KG
Hannoversche Str. 38/46
49084 Osnabrück/Germany

WEB

www.premium-steel.eu
www.premium-steel.eu/shop
www.steel-guide.eu
www.abrams-industries.eu/LinkedIn

SALES

T: +49 (0) 5 41/3 57 39-0
E: sales@abrams-industries.eu

* You will be redirected to our
English speaking accounts
management team in Germany.

